



# **Bridge Structures Hydraulics Survey**

**General Data** 

Ochiciai Data									
Project Key Number	Bridge Key	Number	(proposed)	Project Nun	nber			Date	
Project Title			Local Structure Name						
Station/Milepost			Latitude/Lor	Latitude/Longitude Vertica		Vertical Da	cal Datum (all elevations in this form)		
Location	County	County							
Roadway Identification			Crossing Type ☐ Creek ☐ River ☐ Canal ☐ Other						
Feature Crossed				A Tributary Of					
Hydrologic Data									
Hydrology Methods Used to Determine	ne Design Flo	ows							
USGS Stream Gage Statisti	cs (Bulletir	17C)	☐ Flood	Insurance Stu	udy 🗌 L	JSGS Regre	ssion Equ	ations/	StreamStats
☐ Canal Flows Data ☐ O	ther (Describ	e)							
Description of Watershed or Canal									
Drainage Basin Area ☐ mi²	acres								
Stream/Crossing Data									
☐ Natural Stream ☐ Other		List M	lonths in the D	Ory, If Any	Streambe	ed Material Size	e, D <sub>50</sub>	in	ches
Character of Streambed ☐ Stable ☐ Aggrading ☐ [									
Describe Streambed									
Flow Controlled	If Cont	rolled, Ex	voloin						
☐ Upstream ☐ Downstream	n		•						
Stream Carries an Appreciable Amou	int of Ice	ce Thick	ness			arries an Appr	eciable Amo	ount of D	)ebris
☐ No ☐ Yes				in	☐ No	Yes (desc	cribe)		
Located in Regulatory Floodplain (or Yes No	adjacent to)	NFIF	Community	Name					
Flood Insurance Rate Map (FIRM) Pa	anel Number	& Date	Regulatory I	Floodway	If Yes. Flo	odway Map Pa	nel Number	 Г	
			Yes	☐ No	,				
Existing Structure									
☐ Bridge ☐ Culvert ☐	] None (De	escribe	the Bridge,	Culvert or exi	sting cond	ditions)			
General Condition									Year Constructed
Describe Any Existing Adverse Cond	itions								
Structure Dimensions, Diameter, Etc.				Type of Bridge	Piers		Numbe	er of Pier	rs
outdeture dimensions, diameter, Ltc.			Spread F		Piles	Tambe	511 161	-	

Distribution: Consultant – Signed & Sealed to Bridge Design/LHTAC Project Manager Bridge Design – Signed & Sealed to Project File

No additional copies required



### Bridge Structures Hydraulics Survey

Total Structure Clear Span Normal to Channel Bridge Clearance Above		/e Q <sub>Design</sub> WSE	Velocity(max) Through Structure at Q <sub>Design</sub>	
ft		ft		fps
Streambed Elevation at Upstream Face		Streambed Slope through Structure		
ft				ft/ft
Existing Structure Carried Flow Adequately (per cu	rrent standards)	If No, Explain		
☐ Yes ☐ No				

**Design Flows & Proposed Condition Values** 

Flood	Discharge	Water Surface Elevation	Velocity***
Ordinary High Water [Q ]*	cfs	ft	fps
Design [Q ]**	cfs	ft	fps
Base [Q <sub>100</sub> ] (Scour Design)	cfs	ft	fps
Scour Check [Q ]	cfs	ft	fps
Canal Design Flow	cfs	ft	fps
Canal Max Flow (scour check)	cfs	ft	fps

<sup>\*</sup> OHW as determined by resource agency request for environmental considerations (generally Q<sub>1.5</sub> or Q<sub>2.0</sub>)

Proposed Bridge (10' or greater)

: 10pocoa 211ago (10 di gicator)				
Structure Type		Number and Length of Spans		
Skew Angle of Bridge		Streambed Elevation at Upstream Face	1	Streambed Slope through Structure
	0	ft	t	ft/ft
Total Bridge Clear Span Normal to Channel		Distance from Upstream Structure Face to Point Where Freeboard is Measured		Bottom of Superstructure Elevation (low chord)
	ft	ft	t	ft
Flow Angle to Pier(s)		Q <sub>50</sub> Freeboard		Q <sub>100</sub> Freeboard
	0	ft	t	ft

#### Scour Calculations

	Maximum S	cour at Abutment			
Flood	General Scour Abutment Scour (NCHRP 24-20 method includes contraction scour in abutment scour calcs)		Total Scour	Scour Elevation	
Scour Design [Q <sub>100</sub> ]	ft		ft	ft	ft
Scour Check [Lessor of: Q <sub>500 or</sub> Q <sub>overtopping</sub> ]	ft		ft	ft	ft
Canal Max Flow	ft		ft	ft	ft
	Maximum	Scour at Pier			1
Flood	General Scour	Pier Scour	<b>Contraction Scour</b>	Total Scour	Scour Elevation
Scour Design [Q <sub>100</sub> ]	ft	ft	ft	ft	ft
Scour Check [Lessor of: Q500 or Qovertopping]	ft	ft	ft	ft	ft
Canal Max Flow	ft	ft	ft	ft	ft

### **Scour Countermeasures**

Countermeasure Design Flow [minimum Q <sub>100</sub> ]	Calculated Riprap Size, D <sub>50</sub>	Design Riprap Size, D <sub>50</sub>
cfs	ft	ft
Countermeasure Filter Type		Riprap Thickness
		ft

Distribution: Consultant – Signed & Sealed to Bridge Design/LHTAC Project Manager Bridge Design – Signed & Sealed to Project File

No additional copies required

<sup>\*\*</sup> Use  $Q_{50}$  for bridges and bridge-sized culverts 10' or greater.

<sup>\*\*\*</sup> Maximum velocity through the structure.



# Bridge Structures Hydraulics Survey

ITD 0211 (Rev. 05-21) itd.idaho.gov

in addition to the above informatio	n, submit and check each of the fo	bliowing that apply.					
☐ Hydraulic Report* (see Bridge Hydrau	ilics Manual for format) including the follo	owing as applicable:					
☐ Hydraulic Risk Assessment Memoran	dum						
A vicinity map, such as a county map, with the location of the structure clearly indicated.							
☐ A contour map of the structure site showing 1 foot contours.							
A roadway centerline profile to the same scale as the contour map.							
☐ A streambed profile of the entire hydr	aulic reach analyzed for the structure inc	cluding the location of the structure.					
☐ A typical proposed roadway section a	t the structure.						
☐ Elevation view of the upstream face of	f proposed structure with dimensions.						
☐ Documentation supporting hydrology	methods used to develop design flows.						
$\hfill \square$ Photographs of the existing structure	and channel upstream and downstream	from the site.					
☐ Channel change or canal lining details	s (typical section, plan and profile, and li	mits).					
☐ Computations for scour based on Sco	our Design Flood flow and Scour Check I	Flood flow or Maximum Canal flow.					
$\hfill \square$ Letter of approval from canal compan	Letter of approval from canal company or irrigation district.						
$\ \ \square$ Floodplain data including copy of map	panel at the structure location (FIRMett	te).					
$\hfill \square$ Floodplain Development Permit from	the Local Floodplain Administrator if the	structure is located in the 100-year floodplain.					
☐ Preliminary Bridge Situation & Layout	Plan Sheet						
☐ Riprap details (typical section, dimens	sions, limits, size, toe embedment, etc.) t	for proposed locations.					
A hydraulic report should accompany	bridges and bridge-sized culverts with	n hydraulic openings greater than 10'.					
Prepared By	Title	Engineer's Signature and Seal					
Accepted by LHTAC Administrator, Bridge Engir	neer, or District Engineer   Signature/Date						