

Idaho Transportation Department

Monthly WIM Distribution for Jan-2024

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	5	904	659	5	47	23	3	29	316	29	2	2	25	0
	Flex	.05	.00	.00	.95	.30	.25	.50	.16	1.15	.59	1.42	.52	.97	0.00
	Rigid	.11	.00	.00	1.27	.29	.43	1.24	.18	2.16	1.39	1.37	.67	1.88	0.00
	GVW	12.3	2.6	4.0	40.4	17.7	29.4	49.2	24.9	67.8	75.6	56.1	56.6	89.4	0.0
SE	Num	4	450	337	3	24	9	2	13	211	17	2	2	10	0
	Flex	.08	.00	.00	.94	.31	.30	.25	.19	1.28	.59	1.36	.65	.86	0.00
	Rigid	.16	.00	.00	1.20	.30	.52	.46	.21	2.44	1.41	1.33	.84	1.70	0.00
	GVW	14.5	2.6	4.2	39.7	18.0	29.9	39.8	26.3	71.0	74.6	52.9	58.2	76.1	0.0
NW	Num	3	454	322	2	23	15	3	15	105	12	1	1	15	0
	Flex	.04	.00	.00	.95	.28	.24	.53	.14	.89	.59	1.15	.49	1.03	0.00
	Rigid	.08	.00	.00	1.25	.27	.40	1.35	.16	1.60	1.35	1.11	.65	1.96	0.00
	GVW	11.4	2.7	3.8	38.2	17.5	29.3	50.3	23.7	61.3	76.5	53.2	57.4	98.0	0.0
NW Lane1	Num	3	454	322	2	23	15	3	15	105	12	1	1	15	0
	Flex	.04	.00	.00	.95	.28	.24	.53	.14	.89	.59	1.15	.49	1.03	0.00
	Rigid	.08	.00	.00	1.25	.27	.40	1.35	.16	1.60	1.35	1.11	.65	1.96	0.00
	GVW	11.4	2.7	3.8	38.2	17.5	29.3	50.3	23.7	61.3	76.5	53.2	57.4	98.0	0.0
SE Lane1	Num	4	450	337	3	24	9	2	13	211	17	2	2	10	0
	Flex	.08	.00	.00	.94	.31	.30	.25	.19	1.28	.59	1.36	.65	.86	0.00
	Rigid	.16	.00	.00	1.20	.30	.52	.46	.21	2.44	1.41	1.33	.84	1.70	0.00
	GVW	14.5	2.6	4.2	39.7	18.0	29.9	39.8	26.3	71.0	74.6	52.9	58.2	76.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2024

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9