

Idaho Transportation Department

Monthly WIM Distribution for Feb-2024

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	974	701	6	48	17	2	33	347	32	3	2	25	0
	Flex	.12	.00	.00	.85	.32	.29	.39	.15	1.16	.57	1.34	.78	.87	0.00
	Rigid	.25	.00	.00	1.08	.31	.47	.93	.17	2.18	1.31	1.30	.95	1.83	0.00
	GVW	15.3	2.5	4.0	38.2	18.1	30.0	45.4	24.1	67.9	73.9	56.7	58.9	93.1	0.0
SE	Num	2	482	356	4	25	6	1	15	223	19	2	1	9	0
	Flex	.30	.00	.00	1.01	.36	.34	.08	.19	1.32	.52	1.62	1.67	.75	0.00
	Rigid	.63	.00	.00	1.31	.35	.55	.28	.21	2.51	1.23	1.58	1.86	1.49	0.00
	GVW	21.5	2.5	4.2	42.2	18.7	31.1	34.3	26.0	71.5	71.6	58.6	69.5	78.2	0.0
NW	Num	3	492	345	3	23	11	3	17	124	13	2	1	16	0
	Flex	.08	.00	.00	.59	.28	.28	.70	.13	.87	.63	1.11	.64	.92	0.00
	Rigid	.18	.00	.00	.74	.27	.45	1.56	.15	1.57	1.41	1.07	.85	1.99	0.00
	GVW	13.8	2.5	3.7	32.3	17.5	29.7	53.7	22.6	61.2	77.3	53.9	55.8	101.3	0.0
NW Lane1	Num	3	492	345	3	23	11	3	17	124	13	2	1	16	0
	Flex	.08	.00	.00	.59	.28	.28	.70	.13	.87	.63	1.11	.64	.92	0.00
	Rigid	.18	.00	.00	.74	.27	.45	1.56	.15	1.57	1.41	1.07	.85	1.99	0.00
	GVW	13.8	2.5	3.7	32.3	17.5	29.7	53.7	22.6	61.2	77.3	53.9	55.8	101.3	0.0
SE Lane1	Num	2	482	356	4	25	6	1	15	223	19	2	1	9	0
	Flex	.30	.00	.00	1.01	.36	.34	.08	.19	1.32	.52	1.62	1.67	.75	0.00
	Rigid	.63	.00	.00	1.31	.35	.55	.28	.21	2.51	1.23	1.58	1.86	1.49	0.00
	GVW	21.5	2.5	4.2	42.2	18.7	31.1	34.3	26.0	71.5	71.6	58.6	69.5	78.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2024

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9