

Idaho Transportation Department

Monthly WIM Distribution for Mar-2024

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,008	702	7	49	17	2	31	363	35	2	2	32	0
	Flex	.07	.00	.00	.86	.30	.28	.43	.17	1.13	.62	1.35	1.15	.96	0.00
	Rigid	.16	.00	.00	1.08	.29	.46	.92	.19	2.13	1.46	1.30	1.73	1.78	0.00
	GVW	13.5	2.5	4.0	36.8	17.7	29.1	45.7	24.8	67.2	73.7	58.8	66.9	89.0	0.0
SE	Num	2	505	357	4	26	6	1	14	234	21	2	1	13	0
	Flex	.18	.00	.00	.89	.29	.32	.52	.19	1.27	.61	1.76	1.07	.71	0.00
	Rigid	.39	.00	.00	1.15	.28	.49	1.12	.21	2.43	1.45	1.70	1.43	1.31	0.00
	GVW	18.3	2.5	4.2	36.4	17.7	30.4	52.0	26.7	70.9	73.9	64.3	69.7	76.5	0.0
NW	Num	2	503	344	3	23	11	2	17	129	13	2	2	19	0
	Flex	.02	.00	.00	.77	.31	.27	.43	.15	.89	.65	1.10	1.04	1.14	0.00
	Rigid	.05	.00	.00	.93	.30	.45	.85	.16	1.60	1.51	1.06	1.63	2.11	0.00
	GVW	11.6	2.5	3.8	36.2	17.6	28.6	47.3	23.3	60.6	74.6	55.7	60.7	97.2	0.0
NW Lane1	Num	2	503	344	3	23	11	2	17	129	13	2	2	19	0
	Flex	.02	.00	.00	.77	.31	.27	.43	.15	.89	.65	1.10	1.04	1.14	0.00
	Rigid	.05	.00	.00	.93	.30	.45	.85	.16	1.60	1.51	1.06	1.63	2.11	0.00
	GVW	11.6	2.5	3.8	36.2	17.6	28.6	47.3	23.3	60.6	74.6	55.7	60.7	97.2	0.0
SE Lane1	Num	2	505	357	4	26	6	1	14	234	21	2	1	13	0
	Flex	.18	.00	.00	.89	.29	.32	.52	.19	1.27	.61	1.76	1.07	.71	0.00
	Rigid	.39	.00	.00	1.15	.28	.49	1.12	.21	2.43	1.45	1.70	1.43	1.31	0.00
	GVW	18.3	2.5	4.2	36.4	17.7	30.4	52.0	26.7	70.9	73.9	64.3	69.7	76.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2024

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9