



Date: February 15, 2023
File: CD22068A

Travis Frei
Facility Management Contract Officer
Idaho Transportation Department
11331 W Chinden Blvd.
Boise, ID 83714

RE: **Geotechnical Engineering Evaluation**
Powell Maintenance Building
U.S. Highway 12
Idaho County, Idaho

Greetings:

STRATA is pleased to provide geotechnical recommendations for the proposed Maintenance Building project planned at the Powell Maintenance Yard located at latitude 46°52'14.1" and longitude 114°70'14.1" in Idaho County, Idaho. The purpose of our geotechnical engineering evaluation was to obtain subsurface information at the site and provide geotechnical opinions and recommendations to assist project planning, design, and construction. We accomplished our geotechnical services referencing our authorized proposal, dated October 27, 2022.

Our geotechnical recommendations presented herein must be read and implemented in their entirety; portions or individual sections of our report cannot be relied upon without the supporting text. The following report provides specific geotechnical recommendations for earthwork activities, shallow foundation design, concrete slab-on-grade floors, retaining wall design parameters, and pavement design.

Project construction success will depend, in part, upon the design team and contractor following our report recommendations, the contractor adhering to good construction practices, and the owner and/or contractor providing the necessary construction monitoring, testing, and geotechnical consultation to verify the work has been accomplished as recommended herein. Geotechnical continuity is an imperative part of the geotechnical design process, as it allows the geotechnical engineer-of-record to confirm soil conditions and potentially address changed conditions rapidly during construction. Therefore, we strongly recommend the Idaho Transportation Department (ITD) retain STRATA to provide geotechnical construction monitoring, testing, and consultation services to verify conditions encountered, and to ensure our report recommendations are being followed. If, for some reason, we are not provided the opportunity to provide geotechnical continuity during construction, we cannot be responsible for designer or contractor errors, omissions, or report misinterpretations.

We appreciate the opportunity to assist ITD with this project and look forward to our continued involvement during the construction phase. We strive to provide quality, innovative, and timely geoprofessional services.

Sincerely,
STRATA



Luke R. Michels, P.E.
Engineering Services Manager



Steven J. Litalien, E.I.
Staff Engineer



Ryan M. Lewis, P.E.
North Regional Manager

SJL/LRM/RML/si




Geotechnical Engineering Evaluation
Powell Maintenance Building
U.S. Highway 12
Idaho County, Idaho

Prepared For:
Travis Frei
Facility Management Contract Officer
Idaho Transportation Department
11331 W. Chinden Blvd.
Boise, ID 83714



Prepared By:
STRATA
1016 West Hayden Avenue
Hayden, Idaho 83835



February 15, 2023



TABLE OF CONTENTS

| | PAGE NO. |
|--|----------|
| SCOPE OF SERVICE | 1 |
| PROJECT UNDERSTANDING | 2 |
| EXISTING SITE CONDITIONS | 2 |
| PROPOSED CONSTRUCTION | 2 |
| FIELD AND LABORATORY EVALUATION | 3 |
| SITE EXPLORATION | 3 |
| SUBSURFACE CONDITIONS..... | 4 |
| <i>General</i> | 4 |
| <i>Undocumented Fill – Previous Building Footprint</i> | 4 |
| <i>Undocumented Fill – North of Proposed Building</i> | 4 |
| <i>Undocumented Fill – Fuel Island Area</i> | 4 |
| <i>Undocumented Fill – General Driving Areas</i> | 4 |
| <i>Undocumented Fill – East of Salt Shed</i> | 5 |
| <i>Topsoil</i> | 5 |
| <i>Native Sand</i> | 5 |
| <i>Groundwater</i> | 5 |
| <i>Subsurface Variability</i> | 6 |
| LABORATORY TESTING..... | 6 |
| GEOTECHNICAL OPINIONS AND RECOMMENDATIONS..... | 6 |
| GENERAL PROJECT CONSIDERATIONS DISCUSSION | 6 |
| EARTHWORK | 7 |
| <i>Site and Subgrade Preparation</i> | 7 |
| <i>Pavement Area and Hardscapes Subgrade Preparation</i> | 7 |
| <i>Soil Improvements – Footings</i> | 8 |
| <i>Interior Slab and Fuel Island Slab Subgrade Preparation</i> | 8 |
| <i>Excavation Characteristics</i> | 8 |
| <i>Soil Product Specifications and Required Compaction</i> | 9 |
| Soil Products and Re-use..... | 9 |
| Compaction | 11 |
| Coarse Soil Conditions..... | 11 |
| <i>Wet Weather, Wet Soil Construction and Over-excavations</i> | 11 |
| <i>Utility Trench Construction</i> | 12 |
| <i>Geotextile Applications</i> | 12 |
| FOUNDATION DESIGN | 13 |
| <i>General Requirements</i> | 13 |
| <i>Design Parameters</i> | 13 |
| <i>Corrosivity</i> | 13 |
| <i>Seismicity</i> | 13 |
| <i>Foundation Drainage</i> | 14 |
| <i>Concrete Slab-on-Grade Floors</i> | 14 |
| <i>Moisture Protection</i> | 14 |
| <i>Exterior Slabs</i> | 16 |
| LATERAL EARTH PRESSURES..... | 16 |
| PAVEMENT SECTION DESIGN | 17 |
| <i>Pavement Maintenance and Drainage</i> | 17 |
| ADDITIONAL RECOMMENDED SERVICES..... | 18 |
| EVALUATION LIMITATIONS..... | 18 |



REPORT TABLES

| | |
|---|----|
| TABLE OF CONTENTS | 2 |
| TABLE 1. SOIL SPECIFICATIONS AND ALLOWABLE USE | 10 |
| TABLE 2. REQUIRED SOIL PRODUCTS FOR DESIGNATED PROJECT AREAS | 11 |
| TABLE 3. SEISMIC DESIGN CRITERIA..... | 14 |
| FIGURE 1: VAPOR RETARDER FLOWCHART..... | 15 |
| TABLE 4: <i>STRUCTURAL FILL</i> - PARAMETERS FOR RETAINING WALL AND FOUNDATION WALL DESIGN..... | 16 |
| TABLE 5. FLEXIBLE PAVEMENT SECTION DESIGN..... | 17 |



Geotechnical Engineering Evaluation

Powell Maintenance Building
U.S. Highway 12
Idaho County, Idaho

SCOPE OF SERVICE

We accomplished the following services referencing our authorized proposal, dated October 27, 2022:

1. Coordinated with ITD to delineate exploration schedules, locations, utility issues, cleanup expectations, site access issues, and other exploration-specific considerations.
2. Conducted a site visit to establish and mark proposed exploration locations prior to public and private utility locating.
3. Contacted the Idaho Digline utility notification center prior to exploration to identify known public utilities within 50 feet of proposed boring locations (required by Idaho state law).
4. Subcontracted a private utility locator to perform ground penetrating radar (GPR) and electromagnetic (EM) utility locating within 50 feet of boring locations prior to our subsurface investigation.
5. Subcontracted a trailer-mounted drill rig and operator to advance 9 exploratory borings at the site up to 38 feet below the ground surface. Two (2) planned borings (B-6 and B-7) could not be advanced due to the presence of boulders in the surficial undocumented fill. Boring locations are illustrated on Plate 1, *Exploration Location Plan*. STRATA collected Standard Penetration Test (SPT) soil samples at 2.5- to 5.0-foot intervals, extending to each boring's termination depth. Strata also pushed relatively undisturbed Shelby tube samples at select locations when soil conditions allowed.
6. Observed 4 test pits excavated up to 5 feet below the existing ground surface by an ITD supplied track hoe and operator. STRATA obtained bulk samples of the subgrade during test pit exploration.
7. Logged the subsurface profiles, visually described, and classified the soil encountered referencing the *Unified Soil Classification System (USCS)*. Prior to departing the site, we staked/painted and labeled each location following exploration activities to assist future surveying. Additionally, we documented exploration locations using a commercially available global positioning system (GPS) device and confirmed by measuring from existing site features.
8. Accomplished laboratory testing on samples obtained during fieldwork referencing *ASTM International*, *AASHTO*, or *ITD* test standards. Laboratory test results were used to assist soil classification and characterize soil engineering parameters. Laboratory testing included:
 - Grain size evaluations
 - In-place moisture content
 - Atterberg limits
 - In-situ unit weight
 - pH/resistivity/sulfate content
 - Direct Shear
 - Idaho R-Value
 - Moisture-density relationship (modified Proctor)
9. Reviewed the design team's development documents and provided geotechnical design and construction recommendations for:
 - Earthwork
 - Shallow foundation design
 - Concrete slab-on-grade floors



- Pavement Section Design
 - Soil parameters for Retaining Walls
 - Additional Services Recommended
10. Prepared a draft geotechnical engineering evaluation, including exploration logs, laboratory test results, and related visual aids.
11. After receiving draft report review comments, we incorporated feedback and issue this stamped report deliverable.

PROJECT UNDERSTANDING

ITD is planning to construct a new maintenance building and make other site improvements at their Powell Yard facility. Miller Stauffer Architects has been selected to provide architectural design services and DCI Engineers has been selected to provide structural engineering design services for the project. You requested STRATA provide this report with geotechnical design recommendations to assist civil and structural design progression. We base our project understanding on the following:

- Our telephone and electronic mail conversations with Travis Frei and Tony Pirc, with ITD;
- Our telephone conversations with Micheal Walker, with Miller Stauffer Architects;
- Our telephone and electronic mail conversations with Kelly Andersen, P.E., S.E., with DCI Engineers;
- Reviewing the *Site Plan* document provided by Miller Stauffer dated August 10, 2022;
- Reviewing the design drawings for the previous maintenance building provided by ITD, dated April 25, 1962 and July 27, 1998;
- Reviewing the *Materials Phase IV Report* for the Powell Equipment Storage Building dated May 24, 2016; and
- Our previous experience with similar soil conditions near the project site.

Existing Site Conditions

The Powell Maintenance Yard is located on Lochsa Road in the Nez Perce-Clearwater National Forest on U.S. 12 approximately 10 miles southwest of the Montana border. The area surrounding the maintenance yard is heavily wooded with a creek flowing north to south along the east edge of the property. Lochsa Road is the only portion of the site that is paved (asphalt), with the immediate surrounding area of buildings on the site surfaced with gravel fill. The site generally slopes downward to the south, with approximately 30 feet of elevation change between the north and south ends of the existing parking area. There is approximately 3 feet of elevation change within the proposed maintenance building footprint. There is an approximately 35,000 square foot parking/driving area east of the current vehicle storage building and south of the proposed maintenance building. On the northwest and southwest corners of the site exist several overnight bunk houses for ITD employees. On the east side of the site is an approximately 7,500 square foot salt shed for winter road maintenance.

Proposed Construction

The project includes constructing an approximately 8,000 square foot vehicle maintenance building, an approximately 1,500 square foot fuel and power island, a 275 lineal foot retaining



wall wrapping around the west and north sides of the vehicle maintenance building, and approximately 55,000 square feet of new asphalt pavement.

The new building is located within the footprint of the previous maintenance building that has already been removed. Although we could not verify during exploration, it is our understanding that underground storage tanks have been removed and backfilled on the east end of the proposed building. The previous building was a slab-on-grade structure constructed on spread footings bearing 2 feet, 8 inches below grade. The burial depth of the previously removed underground storage tanks is unknown. The new building will be a single-story, slab-on-grade, steel-framed structure supported by a conventional shallow foundation system consisting of continuous spread and isolated column footings. Based on preliminary structural loading information provided by DCI Engineers, maximum column loads are anticipated to be on the order of 132 kips and maximum wall loads are anticipated to be 2 kips per lineal foot.

The new fuel and power island will be located approximately 150 feet west of the salt shed. Per our conversations with DCI Engineers, the new island will be founded on a concrete slab-on-grade with bearing pressures less than 500 pounds per square foot (psf).

The new retaining wall will be a cast in place concrete wall with heights up to 8 feet. Stormwater will be routed to an existing drainage ditch along U.S. Highway 12.

FIELD AND LABORATORY EVALUATION

Site Exploration

We evaluated subsurface conditions within the proposed building addition footprint by advancing nine (9) exploratory borings (B-1, B-1A, B-2, B-3, B-4, B-5, B-8, B-9, and B-10) and four (4) test pits on November 15th and 16th, 2022. Planned borings B-6 and B-7 could not be advanced due to boulders within the surficial undocumented fill. Plate 1, *Exploration Location Plan*, illustrates the approximate boring locations documented in the field with a commercially available GPS unit.

We advanced borings at the site between 5.5 and 38.0 feet below the existing ground surface using a G-2400 trailer-mounted drill rig equipped with 7-inch outside-diameter hollow-stem augers. Soil samples were obtained in the borings at 2.5- to 5.0-foot intervals via standard penetration testing (SPT) using 2-inch- and 3-inch diameter split spoon samplers. We advanced the SPT samplers 18 inches with a 140-pound hammer falling 30 inches. We obtained the SPT N-value by counting the number of hammer blows required to advance the sampler over the interval from 6 to 18 inches. The blow counts for each 6-inch sampler segment are presented on the boring logs. The SPT N-values reported on the boring logs are not corrected for overburden pressure, the larger diameter of the modified California sampler, or dilation effects on the sampler.

We observed ITD staff excavate test pits at the site between 4.5- to 5.0-feet below the existing ground surface using a Caterpillar 306 CR Mini Excavator equipped with an 18-inch-wide bucket. The excavator was supplied and operated by ITD personnel.

Mr. Steve Litalien, E.I. visually described, classified, and logged the subsurface conditions encountered during exploration referencing the USCS. Appendix A presents exploration logs and a USCS explanation, which should be used to help interpret soil terms used throughout this report and on the exploration logs.

Following exploration completion, we loosely backfilled borings and test pits with on-site cuttings finished approximately level with the surrounding ground surface. The test pits were



loosely compacted utilizing the mini excavator. STRATA staked and/or labeled the boring/test pit locations prior to departing the site.

Subsurface Conditions

General

In general, we encountered undocumented fill overlying native sand in all borings and test pits with the exception of TP-4, which was terminated within undocumented fill due to refusal on boulders. In the six borings drilled within the previous building footprint (B-1 through B-5, and B-1A) we encountered 0.8 to 3.5 feet of well-graded sand with silt and gravel (SW-SM) fill over the native silty sand with gravel (SM), extending to the maximum depth of all borings. In the 2 borings and 1 test pit (B-9, B-10, and TP-1) explored north of the former and proposed building footprint, we encountered 0.2 to 0.6 feet of gravel surfacing classifying as silty sand with gravel (SM) underlain by native sand. In the general driving areas west and east of the proposed and former building footprint (B-8 and TP-2) we encountered 0.1 to 1.5 feet of gravel surfacing visually classifying as poorly graded gravel with silt and sand (GP-GM). The gravel surfacing was underlain by native sand in B-8 and remnant topsoil over native sand in TP-2. In the area east of the salt shed (TP-3) we encountered 4.5 feet of undocumented fill derived from topsoil overlaying native sand. In the proposed fuel island area, we were unable to advance the two proposed borings (B-6 and B-7) due to boulders within the undocumented fill. In the test pit excavated southwest of the proposed fuel island (TP-4), we encountered 4.5-feet of undocumented fill before refusal on boulders.

Undocumented Fill – Previous Building Footprint

We encountered undocumented fill in all borings located in the previous maintenance building footprint (B-1, B-1A, B-2, B-3, B-4, B-5). The fill classified as well graded sand with silt and gravel (SW-SM) according to the ASTM classification system. The fill was brown and gray and moist, with an in-situ moisture content of 8.3 percent. Penetration resistance values in the undocumented fill were 10 blows per foot, indicating a loose stratum. We measured a fines content (percent passing the No. 200 sieve) of 11.3 percent. Atterberg limits testing indicated the fill is non-plastic.

Undocumented Fill – North of Proposed Building

North of the proposed and previous building footprint we encountered undocumented fill in both borings and the test pit (B-9, B-10, TP-1) extending to 0.5-feet below existing grade. The undocumented fill consisted of gravel surfacing that classified as silty sand with gravel (SM) according to the ASTM classification system. The fill was brown to gray and moist, with an in-situ moisture content of 16.3 percent. We measured a fines content of 13.9 percent and Atterberg limits testing indicated the fill is non-plastic.

Undocumented Fill – Fuel Island Area

In the large parking/driving area to the west of the salt shed where the proposed fuel island will be, we encountered undocumented fill in TP-4 extending to 4.5-feet below existing grade. The undocumented fill visually classified as poorly graded gravel with silt and sand (GP-GM) according to ASTM D2488. The fill contained cobbles and boulders which increased in size as depth increased. Asphalt and concrete debris were also observed throughout the fill. The total depth of the undocumented fill in this area is unknown.

Undocumented Fill – General Driving Areas

In the general driving areas to the west and east of the previous maintenance building footprint we encountered 0.1 to 1.5 feet of undocumented fill consisting of gravel surfacing.



The gravel surfacing encountered in B-8 and TP-2 visually classified as a poorly graded gravel with silt and sand (GP-GM) according to ASTM D2488. The gravel fill was described as brown or gray and moist.

Undocumented Fill – East of Salt Shed

Undocumented fill was encountered east of the salt shed in TP-3 and extended to 4.5 feet below existing grade. The undocumented fill was derived from topsoil and visually classified as silty sand with gravel (SM) according to ASTM D2488. The fill was dark brown to black, moist, and contained roots and other organic material. We measured an organic content of 5.1% in a sample of the undocumented fill obtained from TP-3.

Topsoil

A 1-foot layer of remnant topsoil was encountered below the undocumented fill in TP-2 from 1.5 to 2.5 feet below ground surface. The topsoil visually classified as silt with sand (ML) according to ASTM D2488. The topsoil was dark brown to black and moist based on visual observations noted in the field. Roots and other organic material were observed in the remnant topsoil layer.

Native Sand

Native sand was encountered below the remnant topsoil or undocumented fill in each boring and test pit except for TP-4 and extended to the boring termination depths (5.5 to 38 feet). The native sand classified as silty sand with gravel (SM) or silty sand (SM) according to the ASTM classification system. The gravel content within the native sand varied inconsistently relative to both depth below ground surface and boring location. The native sand was described as brown and gray, and moist to wet, with in-situ moisture contents above the groundwater table ranging from 5.2 to 24.4 percent. Penetration resistance values in the sand ranged from 2 to 11 blows per foot in layers with lower gravel content, indicating a very loose to medium dense soil stratum, while penetration resistance values ranged from 13 to over 50 blows per foot in the interbedded layers of native sand with higher gravel content. We measured a fines content in the native sand between 32.4 and 46 percent. Atterberg limits testing indicated that the native sand is non-plastic. Moisture-density relationship testing (modified Proctor, AASHTO T180 on the sand resulted in a corrected maximum dry density of 134.3 pounds per cubic foot (pcf), with an optimum moisture content of 6.8-percent. R-value testing on the native sand indicated the native sand has an Idaho IT-8 R-value of 50. Direct shear testing resulted in an internal friction angle of 33.5 degrees. We measured in-situ dry densities of 104.3 and 114.7 pounds per cubic foot (pcf) in relatively undisturbed samples of the native sand.

Groundwater

Groundwater was encountered at the time of drilling in three of the previous building footprint borings: B-2, B-3 and B-5. Depth to groundwater ranged from 20.0 to 21.5 feet below the existing ground surface. Groundwater can vary with seasonal changes in irrigation, infiltration, precipitation, and adjacent site developments. Groundwater is common as small, nuisance seeps and springs in the subsurface primarily associated with subsurface water conduits (utilities) and seasonal runoff management facilities.

Bedrock

Bedrock was not encountered at any of the boring or test pit locations within the depths explored. Based on our research on past explorations and review of available well logs in the



area, we do not anticipate bedrock will be encountered within the upper 50-feet of the soil profile.

Subsurface Variability

Exploratory borings and test pits only allow observation of a relatively small sample of the subsurface conditions at the site. Variations may exist between and beyond exploration locations. Such variations will not be apparent until construction and may impact project schedules and costs. Where such variations exist, it may affect the opinions and recommendations presented in this report as well as construction timing and costs and we must be contacted to review the encountered conditions and our recommendations to make any necessary revisions.

Laboratory Testing

We performed laboratory testing on select soil samples collected in the field referencing *ASTM International* (ASTM), AASHTO, and ITD test standards. We used laboratory test results to verify soil classification and to estimate soil engineering properties. Laboratory testing included grain size evaluations, in-situ moisture content and unit weight, Atterberg limits, pH/resistivity/sulfate content, moisture-density relationship curve (modified Proctor), direct shear, and R-value testing. Index laboratory test results are presented on exploratory logs in Appendix A. Graphical test results are provided in Appendix B.

GEOTECHNICAL OPINIONS AND RECOMMENDATIONS

We present the following geotechnical recommendations to assist project planning, design, and construction for the Powell Maintenance Building project planned in Idaho County, Idaho. We based our geotechnical recommendations on our experience with similar soil and geologic conditions, findings from our field and laboratory evaluation, geotechnical engineering analyses, and our understanding of the proposed construction. If development plans change, we should be contacted to review the project modifications and revise our recommendations as necessary.

General Project Considerations Discussion

Based on our field and laboratory evaluation, our opinion is the project site is suitable for the proposed construction, provided our recommendations are incorporated into project plans and specifications, and are followed and verified during construction.

Undocumented fill associated with previous site development was encountered in each boring and test pit. Remnant topsoil was also encountered in the proposed pavement area east of the salt shed and could be encountered at other parts of the site. The undocumented fill and topsoil (remnant or surficial) is not suitable to support foundations or slabs (interior and exterior). All undocumented fill and topsoil should be removed below foundations and slabs. The undocumented fill used as gravel surfacing north of the proposed building footprint and in the general driving areas along with the undocumented fill used as backfill in the previous building footprint may be repurposed as *Structural Fill* used in the soil improvement areas below footings or in embankment fill areas provided it meets the requirements outlined in Table 1 below. The undocumented fill encountered east of the salt shed, the undocumented fill encountered in the fuel island area, and the on-site native sand does not meet the requirements of Table 1 below and cannot be used as *Structural Fill*.

The native sand is loose within the foundation depths and will differentially settle under variable loading conditions. In an effort to minimize differential settlement, a 3-foot-thick



Structural Fill soil improvement must be placed and compacted below building foundations, including continuous and isolated footings. Similarly, a 1-foot thick soil improvement zone is required below interior slabs-on-grade and the fuel island slab-on-grade.

Earthwork

Site and Subgrade Preparation

We recommend topsoil, defined as soil containing greater than 3 percent vegetation and organics by weight (per ASTM D2974), and undocumented fill be removed below any planned improvement, structure, or soil embankment area.

We encountered undocumented fill and/or remnant topsoil extending to depths between 0.1- and 4.5 feet in every boring and test pit. The undocumented fill in the fuel island area is likely deeper than 4.5 feet. Undocumented fill has a variable density and can result in excessive total and differential settlement of structures over time due to soil consolidation, which is extremely variable and difficult to predict in granular soil. Therefore, we recommend topsoil and undocumented fill be removed to expose undisturbed native sand. We recommend undocumented fill removal extend a minimum 5 lateral feet outside foundations and interior slabs and a minimum 3 lateral feet outside exterior hardscapes and pavements. If there are areas where the excavation required for undocumented fill removal extends deeper than 5-feet, the excavation should extend a minimum 1-foot laterally for every 1-foot of vertical depth (i.e. 7-foot excavation requires fill removal extend 7 feet beyond the foundation, slab, or pavement).

Following topsoil stripping and undocumented fill removal, we recommend 12 inches of the resulting surface be scarified, moisture-conditioned to within 3 percent of optimum moisture content, and re-compacted to the requirements presented in this report's *Soil Product Specifications and Required Compaction* section. Re-compacting the subgrade will require moisture-conditioning and soil processing. Such subgrade preparations can often help identify areas susceptible to subgrade pumping and rutting. Pumping or rutting subgrade areas should be removed to a depth of 12 inches below the subgrade elevation as discussed in this report's *Wet Weather, Wet Soil Construction and Over-excavations* section. After the subgrade has been moisture-conditioned, compacted, and reviewed by STRATA, *Structural Fill* or separation fabric placement may commence.

Pavement Area and Hardscapes Subgrade Preparation

We understand project costs may prohibit complete undocumented fill removal beneath new asphalt pavement areas and hardscapes (sidewalks, etc.) planned for the new maintenance building and fuel island. ITD may elect to leave the undocumented fill provided they accept the risks associated with reduced pavement performance due to settlement, and an associated increase in pavement maintenance. **Constructing pavements over undocumented fill is not without risk of settlement, ponding, increased weathering, cracking, and long-term distress.** We provide the following relative risk summary for potential settlement within the proposed parking area:

- Low Risk – Complete removal and replacement of undocumented fill with compacted *Structural Fill* meeting the requirements outlined in Table 1 below.
- Moderate Risk – Partial removal of undocumented fill within pavement areas. Removal of upper 18 inches of fill, scarification and re-compaction of resulting surface, followed



by placement of a geotextile separation fabric and compacted *Structural Fill* to achieve construction grades.

- High Risk – No removal of undocumented fill within pavement areas. Scarification and re-compaction of the upper 12 inches of on-site fill followed by placement of geotextile separation fabric and compacted *Structural Fill* to achieve construction grades.

We recommend ITD communicate the desired pavement subgrade preparation method (i.e. low, moderate, or high risk option) to perspective earthwork contractors during the bidding phase.

After STRATA has reviewed and approved the subgrades within the pavement footprint, we recommend the contractor place a woven or nonwoven geotextile separation fabric between the subgrade soil and the supporting *Crushed Aggregate Base* layer. Refer to this report's *Geotextile Applications* section for additional information.

Soil Improvements – Footings

The following section applies to new continuous or isolated column footings. We recommend the contractor place a 3.0-foot-thick layer of *Structural Fill* below new footings. This soil improvement below new footings is necessary to maintain acceptable project settlement tolerances (<1.0-inch total settlement and <0.5-inch differential settlement). Based on our exploration, removal of native soil will be required to construct the 3-foot-thick soil improvement below footings. Although it may aid in subgrade compaction, a separation fabric is not required between the *Structural Fill* and recompacted native sand below the footings.

Interior Slab and Fuel Island Slab Subgrade Preparation

Following topsoil and undocumented fill removal, we recommend the resulting native sand be scarified, moisture conditioned, and re-compacted per the above *Site and Subgrade Preparation* section of this report. Although it may aid in subgrade compaction, a separation fabric is not required between the *Structural Fill* and recompacted native sand below slabs.

Excavation Characteristics

We anticipate the on-site undocumented fill and native sand may be excavated using conventional excavation techniques. The earthwork contractor should plan to remove boulders ranging from 1-foot to 1.8 feet in the fuel island area. In general, slopes and excavations must be excavated, shored and/or braced in accordance with the *Occupational Safety and Health Administration* (OSHA) regulations and codes. The on-site soil is classified as a "C" type soil according to OSHA requirements. As such, we recommend provisions be made to allow temporary excavations of soil to be sloped back to at least 1.5H:1V (horizontal to vertical) or as otherwise determined to be safe according to the selected contractor's competent person. Ultimately, the selected contractor is responsible for site safety and determining appropriate excavation stability. We recommend temporary slopes deeper than 20 feet be designed by a qualified engineer licensed in the State of Idaho.

Excavations must be planned carefully, allowing water collection points and utilizing conventional sumps and pumps to remove nuisance water from runoff, precipitation or groundwater seeps. If soil excavations are not immediately backfilled, they may degrade when exposed to water and require over excavation and replacement with *Structural Fill*. We recommend construction activities and excavation backfilling be performed as rapidly as possible to reduce the potential for subgrades to degrade under construction traffic.



The on-site native soil is moderately moisture-sensitive and susceptible to disturbance when moist or wet. Soil disturbance will negatively impact the soil's performance below slabs, pavements, and foundations. *Disturbed and/or uncompacted soil shall not be allowed below any structure.* Equipment with large tracks, lugs or having toothed buckets has a significant potential to disturb the site soil prior to or following compaction. Rubber-tired transport vehicles should not access prepared subgrades unless the subgrade is sufficiently stiff to allow construction traffic without disturbance. We recommend project earthwork specifications specifically outline that the contractor is required to maintain the subgrade in a compacted condition and protect subgrades from construction traffic disturbance after they have been prepared and meet compaction requirements.

Soil Product Specifications and Required Compaction

Soil Products and Re-use

We recommend any fill placed below foundations and slabs to meet site grades comprise *Structural Fill* meeting the requirements presented in Table 1. The undocumented fill used as gravel surfacing north of the proposed building footprint and in the general driving areas along with the undocumented fill used as backfill in the previous building footprint may be repurposed as *Structural Fill* provided it meets the requirements outlined in Table 1 below. The undocumented fill encountered east of the salt shed, the undocumented fill encountered in the fuel island area, the on-site topsoil, and the on-site native sand does not meet *Structural Fill* requirements specified in Table 1 below, but may be used as *Non-Structural Fill* in landscaping areas.



Table 1. Soil Specifications and Allowable Use

| Soil Fill Product | Allowable Use | Material Specifications |
|------------------------------------|--|--|
| Non-Structural Fill | <ul style="list-style-type: none"> Any area that will not contain structures (typically landscape areas) | Soil must be classified as GP, GM, GW, GC SP, SM, SW, SC, CL or ML according to the USCS. Soil may not contain particles larger than 12 inches in median diameter. Soil must be reasonably free from deleterious substances such as wood, metal, plastic, waste, etc. |
| Structural Fill¹ | <ul style="list-style-type: none"> Soil improvement below foundations and slabs Embankment fills Foundation and retaining wall backfill beyond foundation drainage course. Over-excavations Utility trench backfill above bedding course for underground pipe | Soil must meet the requirements for “Aggregate for Granular Subbase” from <i>Section 703.11</i> in the ITD SSHC ² . Soil must contain less than 3% organics and vegetation by weight (per ASTM D2974) Soil must contain less than 3% wood, metal, plastic, or other deleterious substances (quantity can be approximated by the geotechnical engineer-of-record). |
| Crushed Aggregate Base | <ul style="list-style-type: none"> Slab-on-grade aggregate Pavement support aggregate Structural Fill uses | Must meet “3/4-inch B” nominal maximum size aggregate gradation requirement specified in Table 703.04-1 from <i>Section 703 – Aggregates</i> of ITD SSHC. ² |
| Pipe Bedding Course | <ul style="list-style-type: none"> Utility pipe bedding | Must meet “Size No. 1”, “Size No. 2a” or “Size No. 2b” Coarse Aggregate gradation requirements specified in Table 703.02-6 – from <i>Section 703 – Aggregates</i> of ITD SSHC. ² . |
| Drainage Course | <ul style="list-style-type: none"> Foundation drains | Must meet “Size No. 4”, or “Size No. 5” Coarse Aggregate gradation requirements specified in Table 703.02-6 – from <i>Section 703 – Aggregates</i> of ITD SSHC. ² . |
| Unsatisfactory Soil | <ul style="list-style-type: none"> NONE | Soil classified as CH, MH, OH, OL or PT may not be used at the project site. Any soil type not maintaining moisture contents within 3% of optimum during compaction is unsatisfactory soil. ³ |

1. The undocumented fill used as gravel surfacing north of the proposed building footprint and in the general driving areas along with the undocumented fill used as backfill in the previous building footprint within the planned construction depths generally meets the intent of our recommendations for *Structural Fill*.
2. The 2018 version of *Idaho Transportation Department (ITD) Standard Specifications for Highway Construction (SSHC)*
3. Unsatisfactory soil that is wetted or dried to within 3% of optimum moisture may be used as *Structural Fill*, providing other criteria are met for appropriate *Structural Fill* use per Table 1 above.



Compaction

Table 2 summarizes soil product compaction requirements in designated project areas.

Table 2. Required Soil Products for Designated Project Areas

| Project Area | Required Soil Product | Compaction Requirement |
|--|--|------------------------|
| Subgrades beneath foundations, slabs, and pavements | 12 inches of native soil (scarified and recompacted) | 95% ¹ |
| Soil improvement below footings and slabs | Structural Fill | 95% ² |
| Embankments below structures (including foundations and slabs), wall backfill, and utility trench backfill | Structural Fill | 95% ² |
| Directly beneath pavements, slabs, and hardscapes | Crushed Aggregate Base | 95% ² |
| Over-excavations caused by wet weather and/or wet soil conditions | Structural Fill | 95% ² |
| Landscaped areas | Non-Structural Fill | 85% ¹ |

1. Reference American Association of State Highway and Transportation Officials (AASHTO) T180.
2. Reference Idaho IT-74, *Idaho Standard Method of Test for Vibratory Spring-Load Compaction for Coarse Granular Material*.

Place soil products over subgrades that have been reviewed and approved by the Geotechnical Engineer of Record. Never place soil products over frozen, saturated, or soft subgrades. Soil products must be moisture conditioned to within 3 percent of the optimum moisture content and placed in maximum 12-inch-thick, loose lifts. The contractor is responsible for selecting compaction equipment suitable for achieving compaction. If the contractor is unable to achieve the specified compaction requirements listed in Table 2 using the selected compaction equipment, a lift thickness reduction may be required.

Coarse Soil Conditions

ITD recommends granular subbase (*Structural Fill*) and *Crushed Aggregate Base* be compacted according to Idaho IT-74, *Idaho Standard Method of Test for Vibratory Spring-Load Compaction for Coarse Granular Material*.

Alternatively, ITD recommends on-site or imported soil products that contain more than 10 percent retained on the 3-inch sieve or more than 30 percent particles retained on the ¾-inch sieve be compacted per *Section 205.03.F.2* in the ITD SSHC.

Wet Weather, Wet Soil Construction and Over-excavations

We strongly recommend earthwork construction take place during dry weather conditions. In soft or wet soil areas and during wet weather conditions, earthwork contractors must be familiar with the hazards of using rubber-tired equipment, which exerts a point load on the subgrade. Staggering wheel paths, using tracked equipment to traverse exposed subgrades and other techniques are important processes that reduce the potential for subgrade pumping, rutting, and contractor rework.

Earthwork should not be performed immediately after rainfall, or until soil can dry sufficiently to allow construction traffic without disturbing the subgrade. Potential disturbance may require isolated removal and replacement during construction. We recommend any soil exhibiting pumping, rutting, weaving, or otherwise exhibiting unstable performance be moisture-



conditioned to within 3 percent of the optimum moisture content and recompacted to *Structural Fill* requirements, or removed. If moisture-conditioning is impractical or may create project delays, the soil should be removed to undisturbed native soil using smooth-blade equipment and *Structural Fill* placed to desired grades. We recommend the “over-excavation” process occur as follows:

1. STRATA and/or the selected contractor should identify and delineate unstable subgrade soil conditions. STRATA must review the affected area and provide the contractor and the design team feedback to help facilitate the over-excavation process.
2. After attempting proper moisture conditioning, remove unstable areas using smooth-blade equipment to a minimum depth of 1.0 foot below the subgrade surface. Extend the over-excavation a minimum of 2.0 feet laterally beyond the delineated unstable area.
3. STRATA shall verify the over-excavation base consists of undisturbed native soil or documented embankment fill.
4. A geotextile fabric may be placed over the verified over-excavation base to assist soil stabilization efforts. Refer to this report’s *Geotextile Applications* section for additional information.
5. Place *Structural Fill* in the over-excavation to desired grades in accordance with the *Soil Product Specifications and Required Compaction* report section.

In some instances, a 1.0-foot-deep over-excavation may not be sufficient to expose suitable native soil; additional over-excavation depth may be needed. Further, areas may require a woven or nonwoven geotextile fabric to assist remediation. We recommend STRATA be present to observe all over-excavations to verify they have been constructed according to the above criteria, but also to provide immediate on-site feedback and discussion with the project team regarding soft soil conditions to help facilitate the construction schedule.

Utility Trench Construction

Loose soil must be removed from the base of utility trenches prior to placing pipe bedding course. Based on our observations during exploration, loose soil and sloughing will be likely at the base of utility trenches. In addition, groundwater in utility trenches can be present during wet weather conditions and standing water must be removed from the utility trench base before placing pipe bedding course. We recommend bedding course and trench backfill be placed according to ITD’s *Standard Drawing No. 601-1*.

Geotextile Applications

Nonwoven or woven geotextiles should meet requirements outlined in the subgrade separation geotextile property requirements provided in *Section 718.07* of the ITD SSHC.

Geotextiles shall be applied directly on approved subgrade, taut, overlapped at least 18 inches or otherwise placed according to manufacturers’ recommendations. When used for over-excavation applications, geotextile fabric must completely separate native soil from *Structural Fill*. STRATA should be consulted to review geotextile applications, soil reinforcement methods, or other subgrade improvement alternatives during construction.

Geotextile fabrics may be useful in situations with soft, pumping, and rutting subgrade soil conditions, but cannot be used to reduce or eliminate the risk of undocumented fill settlement associated with fill compression/consolidation or debris decay.



Foundation Design

General Requirements

If our recommendations are followed, the foundation design criteria presented herein can be applied to project foundations, assuming the loading conditions stated in our *Proposed Construction* report section are accurate. We recommend any foundation for the proposed structures bear on a minimum 3-foot layer of compacted *Structural Fill* above recompacted native sand as discussed in our *Earthwork* report section. We recommend *Structural Fill* subgrades remain in a compacted condition during foundation preparations, construction of concrete formwork, and reinforcing steel placement. All foundation bearing surfaces should be free of loose soil and debris and be compacted to the requirements listed in Table 2.

Design Parameters

Based on preparing the foundation bearing soil units as described herein, the following items provide our recommended shallow foundation design parameters:

- Maximum allowable bearing pressure: 2,500 pounds per square foot (psf)
 - Minimum continuous wall footing width: 1.5 feet
 - Minimum isolated column footing width: 3.0 feet
 - Maximum 30 percent increase allowed for short term load increases such as wind or seismic.
- Estimated foundation vertical settlement:
 - Total settlement: Less than 1.0 inch.
 - Differential settlement: Less than 0.5 inches over 30 lateral feet
- Lateral load resistance:
 - Foundation base friction coefficient (nominal, **unfactored** value):
 - 0.40 for foundations cast directly on *Structural Fill* soil.
- Footing embedment:
 - Bottom of exterior footings must extend at least 30 inches below the final, exterior ground surface to help protect against frost action.
 - Bottom of interior footings located within heated buildings must extend at least 12 inches below the top of slab to meet the provided maximum allowable bearing pressure.

Corrosivity

Based on laboratory test results, the soil at the site maintains a basic pH (8.54) and has severe corrosivity potential (resistivity = 828 ohms-cm). We recommend all foundations and utility conduits have appropriate corrosion protection and the design team adhere to all code-minimum steel reinforcement clearances. Sulfate content testing indicates a negligible (47.2 mg/kg dry) capacity for sulfate attack of concrete. Type I/II Portland Cement Concrete is used commonly in the area without known concrete-soil reaction impacts.

Seismicity

From the subsurface soil conditions encountered in the borings and information provided in Table 630.04.01.1 in the *ITD Materials Manual*, our opinion is a Seismic Site Class “D” should be used for the structural design of the building and retaining wall.



Based on the project site location, Figures 630.04.01.1, 630.04.01.2, and 630.04.01.3 in the *ITD Materials Manual* and Tables 630.04.02.1 and 630.04.02.2 in the *ITD Materials Manual*, we recommend the seismic parameters presented in Table 3 be used for design.

Table 3. Seismic Design Criteria

| Period (seconds) | Standard Acceleration Coefficients for Site Class B (g) | Site Factor for Site Class D | Spectral Acceleration Parameters for Site Class D (g) |
|------------------|---|------------------------------|---|
| 0.0 (Peak) | PGA = 0.09 | $F_{PGA} = 1.6$ | $A_s = 0.144 (PGA * F_{PGA})$ |
| 0.2 (Short) | $S_s = 0.20$ | $F_a = 1.6$ | $S_{MS} = 0.32 (F_a * S_s)$ |
| 1.0 | $S_1 = 0.07$ | $F_v = 2.4$ | $S_{M1} = 0.168 (F_v * S_1)$ |

Based on the subsurface conditions encountered, our opinion is liquefaction potential and seismic-induced settlement at the site is low.

Foundation Drainage

We recommend foundation stem walls and retaining walls be backfilled with *Structural Fill* to prevent pore water pressure build up against the structures. We also recommend that a foundation drain be placed at the lowest bearing elevation around the perimeter of foundations and walls and daylighted at an appropriate disposal area. An example foundation drainage system is presented on Plate 2, *Foundation and Wall Drain Schematic*. Roof drains should never be connected to foundation drains.

Concrete Slab-on-Grade Floors

We recommend concrete slab-on-grade floors (including the fuel island slab) be supported by *Crushed Aggregate Base* placed and compacted over a minimum 12 inches of *Structural Fill* meeting the requirements in Table 1. The *Structural Fill* should extend to recompacted native sand. The recommendations provided in this section assume compacted *Structural Fill* subgrades below the *Crushed Aggregate Base* will be prepared per the *Earthwork* report section. The slab's supporting *Crushed Aggregate Base* should be constructed once the majority of under slab plumbing and utilities are completed.

Floor slabs must be designed for the anticipated use and equipment or storage loading conditions. If at least 4 inches of *Crushed Aggregate Base* is used below slabs, we recommend concrete slab design utilize an allowable modulus of subgrade reaction (k) of 250 pounds per cubic inch (pci).

Moisture Protection

Interior floor slabs may be susceptible to moisture migration caused by subsurface capillary action and vapor pressure. Moisture migration through floor slabs can break down a floor covering, its adhesive, or cause various other floor covering performance problems. Specifically, STRATA has participated in numerous projects where inadequate vapor protection caused significant damage to moisture-susceptible flooring systems. Often, these moisture problems were associated with either no moisture protection below the slab or, alternatively, un- or inadequately sealed sub slab penetrations that allowed vapor migration and damage the flooring system. Plumbing penetrations are notoriously problematic for under slab vapor protection.

Vapor retarders must consist of thick, puncture-proof polyethylene sheeting placed



immediately below the floor slab. An example of this material is Stego Wrap Vapor Barrier a 15-mil retarder. Alternatively, the vapor barrier may be covered with an additional 2-inch-thick layer of clean, coarse sand placed between the *Crushed Aggregate Base* and the concrete slab-on-grade floors, if the *Crushed Aggregate Base* and slabs are placed with a waterproofing system in-place. Vapor barrier installation options are outlined in Figure 1.




Figure 1: Vapor Retarder Flowchart
 (Adapted from Figure 3-1 of ACI 302.1R-04)

Form stakes, piping, or other sub-slab penetrations must never penetrate the vapor retarder. Carefully design and construct any vapor retarder penetrations to reduce vapor transport through such penetrations. Even if these recommendations are used, water vapor migration through the concrete floor slab is still possible. Floor covering should be selected accordingly and, when practical, flooring manufacturers should be consulted regarding moisture barriers, their location and product warranties. Manufacturer's recommendations should be strictly followed. Where vapor retarders are utilized, the flooring and concrete slab contractors, as well as the plastic sheeting manufacturer, should be consulted regarding additional slab cure time requirements and/or the potential for slab curling.

Ultimately, the location of the vapor retarder should be carefully considered by the project design team. ASTM E1643 and American Concrete Institute (ACI) Committee 302 are 2 publications that provide considerations for vapor retarder locations. Studies have shown that decreased water cement ratios, higher strength concrete and good construction finishing practices significantly decrease any negative impacts associated with the above options for



vapor retarder locations.

Exterior Slabs

Non-critical exterior slabs may be supported on either undisturbed native sand or existing undocumented fill after the vegetation, topsoil, and root zone have been removed. Critical exterior slabs, such as those at entrances, will likely require some additional subgrade preparation as described below. As previously indicated, the undocumented fill encountered on the site could result in excessive settlement of exterior slabs. To reduce this risk, we recommend removing the undocumented fill beneath critical exterior slabs down to native sand, then replacing it with *Structural Fill* compacted per the requirements in Table 2.

Lateral Earth Pressures

We recommend foundations and retaining walls be backfilled using *Structural Fill* conforming to Section 703.11 “Aggregate for Granular Subbase” of the latest edition of the ITD SSHC. Lateral earth pressures will be realized from retained soil behind the structures as well as any surcharge from equipment, vehicle traffic, or material placed adjacent to walls. Based on the topographic map provided by Miller Stauffer Architects, we anticipate foundation stem walls and the retaining wall will have a close to horizontal backslope. We recommend lateral earth pressures for foundation and retaining walls be estimated using the following equivalent fluid pressures (EFP) from Table 4.

Table 4: *Structural Fill* - Parameters for Retaining Wall and Foundation Wall Design

| Parameter | Horizontal Backfill |
|---|---------------------|
| Unit Weight (moist, compacted) | 130 pcf |
| Friction Angle | 34° |
| Active Earth Pressure, K_a | 0.28 |
| Equivalent Active Fluid Pressure for walls free to rotate at the top | 36 pcf |
| At-Rest Earth Pressure, K_o | 0.44 |
| Equivalent At-Rest Fluid Pressure for walls restrained at the top | 57 pcf |
| Passive Earth Pressure, K_p | 3.50 |
| Equivalent Passive Fluid Pressure for walls free to rotate at the top | 455 pcf |

The equivalent fluid pressures provided in Table 4 are for above-groundwater conditions, assuming fully drained conditions and no hydrostatic forces acting on the wall. These parameters also assume the wall is vertical and there is no friction acting between the wall and backfill material. The earth pressures provided in Table 6 are nominal, unfactored values; the wall design engineer should apply appropriate factors for wall design.

For walls that cannot tolerate lateral movement, we recommend they be designed utilizing at-rest equivalent earth pressures. Lateral surcharge pressures due to equipment, vehicle traffic, slopes, storage loads, etc. have not been included in the above lateral earth pressure



recommendations. A lateral earth pressure coefficient of 0.44, acting over the entire below-grade wall height should be used to estimate the lateral surcharge loads from equipment, vehicle traffic, and adjacent foundations behind and above walls. Surcharge pressures must be added to the at-rest EFP recommended above.

The passive earth pressure provided in Table 4 also assumes the retaining wall rotates the amount required to fully mobilize the passive resistance, or $H/100$ for granular soil conditions, where H is defined as the height of the wall.

Fill, debris and loose soil should be removed before placing backfill behind walls. Care should be taken to avoid over compaction of the backfill behind the walls so that the walls are not displaced or damaged. Only light hand operated compaction equipment should be used within 5 feet of backfilled walls.

Pavement Section Design

STRATA performed pavement design analyses referencing the ITD Gravel Equivalency (GE) method. For our design, we utilized a subgrade support ITD R-Value of 50 and estimate a traffic index (T.I.) of 7.5, which corresponds to approximately 220,000 ESALs to account for the snowplows, maintenance vehicles, equipment transport vehicles, and passenger vehicles expected to access the pavement over a 20-year design life. Table 5 describes our flexible pavement section design.

Table 5. Flexible Pavement Section Design

| Pavement Section Material | Recommended Thickness (inches) | Material Specifications |
|---------------------------|--------------------------------|---|
| Asphalt Concrete Pavement | 4.0 | Asphalt concrete meeting ITD Superpave, SP2 or SP3 mix standards specified in Table 405.02-1 from <i>Section 405 – Superpave Hot Mix Asphalt</i> of ITD SSHC. We recommend asphalt concrete be placed in two, 2-inch thick lifts rather than a single, 4-inch thick lift. |
| Crushed Aggregate Base | 9.0 | “3/4-inch B” nominal maximum size aggregate gradation requirement specified in Table 703.04-1 from <i>Section 703 – Aggregates</i> of ITD SSHC |
| Geotextile Fabric | N/A | Nonwoven or woven subgrade separation geotextile meeting <i>Section 718.07 of the ITD SSHC</i> . |

We recommend ITD’s most recent Asphalt special provisions and memos be referenced along with *Section 405 – Superpave Hot Mix Asphalt* of the ITD SSHC.

Pavement Maintenance and Drainage

We recommend crack maintenance be accomplished on all pavement surfaces every 3 to 5 years to reduce the potential for surface water infiltration into the underlying pavement subgrade. Slurry seals and chip seals can extend flexible pavement life and reduce water infiltration to the subgrade. As asphalt pavements age, brittle/thermal cracking, and isolated areas of distress and deterioration are normal and commensurate with pavement design assumptions. Pavement maintenance and reducing water to pavement subgrades will slow pavement distress and may extend pavement life beyond 20 years.

Surface and subgrade drainage are extremely important to the performance of the pavement section. Therefore, we recommend the subgrade, *Aggregate Base Course* and pavement



surfaces slope at no less than 2 percent to an appropriate stormwater disposal system or other appropriate location that does not impact adjacent buildings or properties. Surface irrigation water crossings, ponded water or other water infiltrating the pavement surface must be avoided to the maximum extent practical. Pavement performance will depend upon achieving adequate drainage throughout the section and especially at the subgrade. Water that ponds at the pavement subgrade surface reduces pavement support, can induce heaving during the freeze-thaw process and create pavement distress.

ADDITIONAL RECOMMENDED SERVICES

The information contained in this report is based on our understanding of the planned construction, anticipated structural loads, and site grades. Changes in final slab and foundation elevations, slab and footing configuration, structural loads, site geometry, and actual subsurface conditions can alter our opinions and design recommendations. Therefore, we recommend STRATA provide geotechnical continuity through final project planning and design as individual design aspects become available. We further recommend STRATA be retained to review the structural engineer's foundation design to verify our recommendations have been correctly interpreted. Further, verification of the subsurface conditions during construction is an important part of the geotechnical design process. We recommend you retain STRATA to be on-site during undocumented fill removal and subgrade preparations to verify the conditions encountered during exploration are exposed during construction and our recommendations are followed.


EVALUATION LIMITATIONS

This report has been prepared to assist project planning, design and construction for the Powell Maintenance Building project planned at ITD's Powell Yard in Idaho County, Idaho. Our services consist of professional opinions and recommendations provided in accordance with generally accepted geotechnical engineering principles and practices as they exist at this time, and in the area of this report. This report has been prepared specifically for this project and exclusively for the use of the Idaho Transportation Department and the project design team. We do not authorize its use by firms other than the design team, as a reference document to support the design process. The geotechnical recommendations provided herein are based on the premise that STRATA will continue our project involvement to observe and document our recommendations are implemented during construction, and to confirm conditions between exploration locations. This acknowledgement is in lieu of any express or implied warranty.

The following plates and appendices accompany this report:

- Plate 1: Exploration Location Plan
- Plate 2: Foundation and Wall Drain Schematic
- Appendix A: USCS Explanation and Exploratory Logs
- Appendix B: Laboratory Test Results





LEGEND

- B-1**
 Boring (B) location.
- TP-1**
 Test Pit (TP) location.
- [R.A.S.]** Refusal At Surface
- [10]** Exploration depth (in feet).



EXPLORATION LOCATION PLAN
Powell Maintenance Building
Highway 12
Idaho County, Idaho

CD22068A Plate 1

Base Image Reference: Project Site Plan document provided by Miller Stauffer, dated August 12, 2022.

NOTE:

THIS DRAWINGS' CROSS-SECTIONS MAY BE USED FOR GRAVITY WALLS. THIS IS NOT A STRUCTURAL DETAIL.



NOTE:

REFER TO MANUFACTURER'S SPECIFICATIONS AND TEXT OF REPORT FOR INFORMATION REGARDING DRAINAGE SYSTEM, WALL DESIGN AND RELATED GEOTECHNICAL CONSIDERATIONS.

INFORMATIONAL ONLY (NOT TO SCALE)

FOUNDATION AND WALL DRAIN SCHEMATIC



Appendix A

Exploration Logs and
USCS Explanation

UNIFIED SOIL CLASSIFICATION SYSTEM

SHORTHAND NOTATION

- SPT - STANDARD PENETRATION TEST
- PL - PLASTIC LIMIT
- LL - LIQUID LIMIT
- PI - PLASTICITY INDEX
- MC - MOISTURE CONTENT
- DD - DRY DENSITY
- WD - WET DENSITY
- UC - UNCONFINED COMPRESSION
- OC - ORGANIC CONTENT
- BGS - BELOW GROUND SURFACE
- N.E. - NOT ENCOUNTERED

| MAJOR DIVISIONS | | | GRAPH SYMBOL | LETTER SYMBOL | TYPICAL NAMES |
|--|---|---------------------------------------|--------------|---------------|---|
| COARSE GRAINED SOIL MORE THAN 50% RETAINED ON NO. 200 SIEVE | GRAVELS >50% COARSE FRACTION RETAINED #4 SIEVE | CLEAN GRAVELS WITH LITTLE OR NO FINES | | GW | WELL-GRADED GRAVELS, GRAVEL-SAND MIXTURES |
| | | GRAVELS WITH >12% FINES | | GP | POORLY GRADED GRAVELS, GRAVEL-SAND MIXTURES |
| | SANDS >50% COARSE FRACTION PASSES #4 SIEVE | CLEAN SANDS WITH LITTLE OR NO FINES | | GM | SILTY GRAVELS, GRAVEL-SAND-SILT MIXTURES |
| | | | | GC | CLAYEY GRAVELS, GRAVEL-SAND-SILT MIXTURES |
| | | SANDS WITH >12% FINES | | SW | WELL-GRADED SANDS, GRAVELY SANDS |
| | | | | SP | POORLY GRADED SANDS, GRAVELY SANDS |
| FINE GRAINED SOIL 50% OR MORE PASSING NO. 200 SIEVE | SILTS AND CLAYS LIQUID LIMIT LESS THAN 50 | INORGANIC | | ML | INORGANIC SILTS, SANDY OR CLAYEY SILTS |
| | | ORGANIC | | CL | INORGANIC CLAYS OF LOW TO MEDIUM PLASTICITY, SANDY OR SILTY CLAYS |
| | SILTS AND CLAYS LIQUID LIMIT 50 OR MORE | INORGANIC | | OL | ORGANIC SILTS AND CLAYS OF LOW PLASTICITY |
| | | | | MH | INORGANIC SILTS, MICACEOUS SILTS, PLASTIC SILTS |
| | | ORGANIC | | CH | INORGANIC CLAYS OF HIGH PLASTICITY, FAT CLAYS |
| | | | | OH | ORGANIC CLAYS OF MEDIUM TO HIGH PLASTICITY |
| HIGHLY ORGANIC SOILS | | | | PT | PEAT, MUCK AND OTHER HIGHLY ORGANIC SOIL |

MATERIAL DESCRIPTION CONTACT

- DISTINCT SOIL LAYER CONTACT WITHIN SOIL PROFILE
- APPROXIMATE SOIL LAYER CONTACT WITHIN SOIL PROFILE

NOTES

1. MIXED UNIFIED SOIL CLASSIFICATION SYSTEM SYMBOLS ARE USED TO INDICATE DUAL SOIL CLASSIFICATIONS.
2. THE SPT N-VALUE, REPORTED IN BLOWS PER FOOT, IS THE SUM OF THE NUMBER OF BLOWS REQUIRED TO DRIVE THE STANDARD SPLIT SPOON SAMPLER A DISTANCE OF 12-INCHES AFTER AN INITIAL 6-INCHES OF PENETRATION. IF A TOTAL OF 50 BLOWS ARE INSUFFICIENT TO ADVANCE ANY OF THE THREE 6-INCH INTERVALS, THE PENETRATION DEPTH AFTER 50 BLOWS IS ALSO REPORTED.

ADDITIONAL MATERIAL SYMBOLS

BORING LOG SYMBOLS

| GRAPH SYMBOL | DESCRIPTION |
|--------------|--|
| | STANDARD 2-INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER |
| | MODIFIED CALIFORNIA 3-INCH OUTSIDE DIAMETER SAMPLER |
| | ROCK CORE |
| | SHELBY TUBE 3-INCH OUTSIDE DIAMETER SAMPLER |

| GRAPH SYMBOL | LETTER SYMBOL | TYPICAL NAMES |
|--------------|---------------|--------------------------|
| | AC | ASPHALT CONCRETE |
| | CC | PORTLAND CEMENT CONCRETE |
| | TS | TOPSOIL |
| | FL | FILL |

TEST PIT LOG SYMBOLS

| GRAPH SYMBOL | DESCRIPTION |
|--------------|---------------|
| | BAGGIE SAMPLE |
| | BULK SAMPLE |
| | RING SAMPLE |

GROUNDWATER SYMBOLS

| GRAPH SYMBOL | DESCRIPTION |
|--------------|--|
| | GROUNDWATER LEVEL AT TIME OF DRILLING |
| | GROUNDWATER LEVEL AT END OF DRILLING |
| | GROUNDWATER LEVEL 24 HOURS AFTER DRILLING COMPLETION |
| 04-10-18 | DATE OF GROUNDWATER READING |

EXPLORATION LOG KEY - SOIL




GRAIN SIZE

| DESCRIPTION | SIEVE SIZE | GRAIN SIZE | APPROXIMATE SIZE | |
|-------------|--------------|------------|-------------------------------|---------------------------------|
| Boulders | >12" | >12" | Larger than basketball-size. | |
| Cobbles | 3" - 12" | 3" - 12" | Fist-size to basketball-size. | |
| Gravel | coarse | 3/4" - 3" | 3/4" - 3" | Thumb-sized to fist sized. |
| | fine | #4 - 3/4" | 0.19 - 0.75" | Pea-sized to thumb-sized. |
| Sand | coarse | #10 - #4 | 0.079 - 0.19" | Rock salt-sized to pea-sized. |
| | medium | #40 - #10 | 0.017 - 0.079" | Sugar-sized to rock salt-sized. |
| | fine | #200 - #40 | 0.0029 - 0.017" | Flour-sized to sugar-sized. |
| Fines | Passing #200 | <0.0029" | Flour-sized and smaller. | |

MODIFIERS

| DESCRIPTION | % |
|-------------|-------|
| Trace | <5 |
| Few | 5-10 |
| Little | 15-25 |
| Some | 30-45 |

PLASTICITY CHART



STRATIFICATION

| DESCRIPTION | THICKNESS |
|-------------|-------------|
| Parting | 1/16 - 1/4" |
| Lense | 1/4 - 4" |
| Layer | 4 - 12" |

MOISTURE CONTENT

| DESCRIPTION | FIELD TEST |
|-------------|---|
| Dry | Absence of moisture, dusty, dry to touch. |
| Moist | Slightly damp, some apparent moisture. |
| Wet | Saturated, visible free water, soil is below water table. |

| DESCRIPTION | THICKNESS |
|-------------|--------------------------------------|
| Occasional | One or less per foot of thickness. |
| Frequent | More than one per foot of thickness. |

APPARENT RELATIVE DENSITY OF COARSE-GRAINED SOIL

| APPARENT DENSITY | SPT blows/ft | CALIFORNIA SAMPLER blows/ft | D & M SAMPLER blows/ft | RELATIVE DENSITY (%) | FIELD TEST |
|------------------|--------------|-----------------------------|------------------------|----------------------|--|
| Very Loose | 0-4 | <4 | <5 | 0-15 | Easily penetrated with 1/2" reinforcing rod pushed by hand. |
| Loose | 5-10 | 5-12 | 5-15 | 15-35 | Difficult to penetrate with 1/2" reinforcing rod pushed by hand. |
| Medium Dense | 11-30 | 12-35 | 15-40 | 35-65 | Easily penetrated a foot with 1/2" reinforcing rod driven with 5-lb hammer. |
| Dense | 31-50 | 35-60 | 40-70 | 65-85 | Difficult to penetrate a foot with 1/2" reinforcing rod driven with 5-lb hammer. |
| Very Dense | >50 | >60 | >70 | 85-100 | Penetrated only a few inches with 1/2" reinforcing rod driven with 5-lb hammer. |

CONSISTENCY FINE-GRAINED SOIL

| CONSISTENCY | SPT blows/ft | TORVANE | POCKET PENETROMETER | FIELD TEST |
|-------------|--------------|--------------------------------|---------------------------------------|---|
| | | UNDRAINED SHEAR STRENGTH (tsf) | UNCONFINED COMPRESSIVE STRENGTH (tsf) | |
| Very Soft | <2 | <0.125 | <0.25 | Easily penetrated several inches by thumb. Extrudes between thumb and finger when squeezed in hand. |
| Soft | 2-3 | 0.125-0.25 | 0.25-0.5 | Penetrated about 1/4 inch by thumb with moderate effort. Molded by strong finger pressure. |
| Firm | 4-7 | 0.25-0.5 | 0.5-1.0 | Penetrated about 1/4 inch by thumb with moderate effort. Molded by strong finger pressure. |
| Stiff | 8-14 | 0.5-1.0 | 1.0-2.0 | Indented about 1/2 inch by thumb only with great effort. |
| Very Stiff | 15-30 | 1.0-2.0 | 2.0-4.0 | Readily indented with difficulty by thumbnail. |
| Hard | >30 | >2.0 | >4.0 | Indented with difficulty by thumbnail. |

REACTION WITH HCl

| | |
|--------|---|
| None | No visible reaction. |
| Weak | Some reaction, with bubbles forming slowly. |
| Strong | Violent reaction, with bubbles forming immediately. |


CEMENTATION

| | |
|----------|---|
| Weak | Crumbles or breaks with handling or little finger pressure. |
| Moderate | Crumbles or breaks with considerable finger pressure. |
| Strong | Will not crumble or break with finger pressure. |

STRUCTURE

| | |
|--------------|--|
| Stratified | Alternating layers of varying material or color with layers at least 1/4" thick; note thickness. |
| Laminated | Alternating layers of varying material or color with layers at least 1/2" thick; note thickness. |
| Fissured | Breaks along definite planes of fracture with little resistance to fracturing. |
| Slickensided | Fracture planes appear polished or glossy, sometimes striated. |
| Blocky | Cohesive soil that can be broken down into small macular lumps which resist further breakdown. |
| Lensed | Inclusion of small pockets of different soil, such as small lenses or sand scattered through a mass of clay; note thickness. |
| Homogeneous | Same color and thickness throughout. |

PARTICLE SHAPE



EXPLORATION LOG KEY - SOIL



Project: CD22068A - Powell Maintenance Building
 Client: Idaho Transportation Department
 Date Drilled: 11-16-2022
 Depth to Groundwater: N.E.

Drill Rig: G-2400
 Borehole Diameter: 7.0"
 Logged By: S. Litalien




Boring:
 B-1

TEST BOREHOLE - STRATA.GDT - 1/19/23 12:06 - C:\USERS\MICHELSDROPOX (STRATA)\CDP22068 - ITD DISTRICT 2 FACILITY UPGRADES\CDP22068 - POWELL YARD\LOGS\CD22068A.LOGS.GPJ

| Depth (ft) | USCS Description | Symbol | Sample Type | Recovery (in) | Blows Per 6 Inches | SPT N-Value | Pocket Pen (TSF) | Moisture Content (%) | Dry Density (pcf) | Percent Passing the No. 200 Sieve | Liquid Limit | Plasticity Index | Remarks | |
|------------|---|--------|-------------|----------------|--------------------|-------------|------------------|----------------------|-------------------|-----------------------------------|--------------|------------------|---|---|
| 0 | <p>Fill - Well-Graded Sand with Silt and Gravel (SW-SM) - Gray, moist, medium dense, fine to coarse rounded to subangular. Gravel surfacing.</p> <p>Silty Sand with Gravel (SM) - Brown, moist to wet, loose to very dense, fine to coarse rounded to subangular.</p> | SW-SM | 18 | 20 12 11 | 23 | | | | | | | | <p>Note: BGS = Below Ground Surface</p> | |
| 18 | | SM | 18 | 2 3 5 | 8 | | 16 | | | | | | | |
| 5 | | SM | 14 | 2 2 3 | 5 | | | | | | | | | |
| 7 | | SM | 7 | 4 50/3.0" | 50+ | | | | | | | | | Higher gravel content from 7.5-17 feet BGS. |
| 10 | | SM | 13 | 11 6 14 | 20 | | 9.4 | | | | | | | |
| 15 | | SM | 18 | 22 24 13 | 37 | | | | | | | | | |
| 20 | | | 0 | 4 3 2 | 5 | | | | | | | | Attempted Shelby tube, could not penetrate. | |

Borehole Terminated at 21.5 Feet.

Latitude: 46.52147
 Longitude: -114.70158

| | | | |
|--|--------------------------------|--|-----------------------------------|
| Project: CD22068A - Powell Maintenance Building | |  | Boring: B-1A |
| Client: Idaho Transportation Department | Drill Rig: G-2400 | | |
| Date Drilled: 11-16-2022 | Borehole Diameter: 7.0" | | |
| Depth to Groundwater: N.E. | Logged By: S. Litalien | | |

| Depth (ft) | USCS Description | Symbol | Sample Type | Recovery (in) | Blows Per 6 Inches | SPT N-Value | Pocket Pen (TSF) | Moisture Content (%) | Dry Density (pcf) | Percent Passing the No. 200 Sieve | Liquid Limit | Plasticity Index | Remarks |
|------------|--|--------|-------------|---------------|--------------------|-------------|------------------|----------------------|-------------------|-----------------------------------|--------------|------------------|----------------------------------|
| 0 | Fill - Well-Graded Sand with Silt and Gravel (SW-SM) - Gray, moist, fine to coarse rounded to subangular. Gravel surfacing. Silty Sand with Gravel (SM) - Brown, moist, fine to coarse rounded to subangular. | SW-SM | | | | | | | | | | | Note: BGS = Below Ground Surface |
| 5 | | SM | | 6 | 6 7 | 13 | | 17.6 | 104.3 | | | | |

Borehole Terminated at 5.5 Feet.

Latitude: 46.52147
Longitude: -114.70158

TEST BOREHOLE - STRATA.GDT - 1/19/23 12:06 - C:\USERS\MICHELSDROPBOX (STRATA)\CDP22068 - ITD DISTRICT 2 FACILITY UPGRADES\CDP22068 - POWELL YARD\LOGS\CD22068A.LOGS.GPJ

| | |
|--|--------------------------------|
| Project: CD22068A - Powell Maintenance Building | |
| Client: Idaho Transportation Department | Drill Rig: G-2400 |
| Date Drilled: 11-16-2022 | Borehole Diameter: 7.0" |
| Depth to Groundwater: 20' | Logged By: S. Litalien |



Boring:
B-2

TEST BOREHOLE - STRATA.GDT - 1/19/23 12:06 - C:\USERS\MICHELSDROPOX (STRATA)\CDP22068 - ITD DISTRICT 2 FACILITY UPGRADES\CDP22068 - POWELL YARD\LOGS\CD22068A.LOGS.GPJ

| Depth (ft) | USCS Description | Symbol | Sample Type | Recovery (in) | Blows Per 6 Inches | SPT N-Value | Pocket Pen (TSF) | Moisture Content (%) | Dry Density (pcf) | Percent Passing the No. 200 Sieve | Liquid Limit | Plasticity Index | Remarks |
|------------|--|--------|-------------|---------------|--------------------|-------------|------------------|----------------------|-------------------|-----------------------------------|--------------|--|----------------------------------|
| 0 | Fill - Well-Graded Sand with Silt and Gravel (SW-SM) - Brown, moist, very loose to loose, fine to coarse rounded to subangular. Fill placed in previous building footprint. | | | 13 | 3 4 6 | 10 | | 8.3 | | | | | Note: BGS = Below Ground Surface |
| | | | | 3 | 4 2 2 | 4 | | | | | | | |
| 5 | Silty Sand with Gravel (SM) - Brown, moist to wet, very loose to dense, fine to coarse rounded to subangular. Layers of higher gravel content throughout. | | | 10 | 2 2 2 | 4 | | 13.7 | | | | | |
| | | | | 13 | 2 1 3 | 4 | | | | | | | |
| | | | | 13 | 15 16 20 | 36 | | | | | | | |
| | | | | 18 | 3 4 2 | 6 | | 24.7 | | | | | |
| 20 | | | | 18 | 2 2 4 | 6 | | | | | | Higher gravel content from 10-11.5 feet BGS. | |
| | | | | | | | | | | | | Water Level Measured 11-16-22 | |

Borehole Terminated at 21.5 Feet.

Latitude: 46.52141
Longitude: -114.70125

Project: CD22068A - Powell Maintenance Building
 Client: Idaho Transportation Department
 Date Drilled: 11-16-2022
 Depth to Groundwater: 20'

Drill Rig: G-2400
 Borehole Diameter: 7.0"
 Logged By: S. Litalien



Boring:
 B-3

TEST BOREHOLE - STRATA.GDT - 1/19/23 12:06 - C:\USERS\MICHELSDROPOX (STRATA)\CDP22068 - ITD DISTRICT 2 FACILITY UPGRADES\CDP22068 - POWELL YARD\LOGS\CD22068A.LOGS.GPJ

| Depth (ft) | USCS Description | Symbol | Sample Type | Recovery (in) | Blows Per 6 Inches | SPT N-Value | Pocket Pen (TSF) | Moisture Content (%) | Dry Density (pcf) | Percent Passing the No. 200 Sieve | Liquid Limit | Plasticity Index | Remarks |
|------------|---|--------|-------------|---------------|--------------------|-------------|------------------|----------------------|-------------------|-----------------------------------|--------------|------------------|---|
| 0 | <p>Fill - Well-Graded Sand with Silt and Gravel (SW-SM) - Brown, moist, loose, fine to coarse rounded to subangular. Fill placed in previous building footprint.</p> <p>Silty Sand with Gravel (SM) - Brown, moist, loose to dense, fine to coarse rounded to subangular. Layers of higher gravel content throughout.</p> | | | 11 | 2 2 4 | 6 | | 17.3 | | | | | <p>Note: BGS = Below Ground Surface</p> |
| | | | | 8 | 3 3 3 | 6 | | | | | | | |
| 5 | | | | 18 | 2 3 5 | 8 | | | | | | | |
| | | | | 18 | 1 3 2 | 5 | | | | | | | |
| 10 | | | | 15 | 9 4 3 | 7 | | | | | | | |
| | | | | 15 | 15 17 21 | 38 | | | | | | | |
| 15 | | | | | | | | | | | | | |
| | | | | 9 | 2 3 6 | 9 | | | | | | | |
| 20 | | | | | | | | | | | | | |

Borehole Terminated at 21.5 Feet.

Latitude: 46.52131
 Longitude: -114.70163

Project: CD22068A - Powell Maintenance Building
Client: Idaho Transportation Department
Date Drilled: 11-16-2022
Depth to Groundwater: N.E.

Drill Rig: G-2400
Borehole Diameter: 7.0"
Logged By: S. Litalien



Boring:
B-4

| Depth (ft) | USCS Description | Symbol | Sample Type | Recovery (in) | Blows Per 6 Inches | SPT N-Value | Pocket Pen (TSF) | Moisture Content (%) | Dry Density (pcf) | Percent Passing the No. 200 Sieve | Liquid Limit | Plasticity Index | Remarks |
|------------|---|--------|-------------|---------------|--------------------|-------------|------------------|----------------------|-------------------|-----------------------------------|--------------|------------------|---|
| 0 | <p>Fill - Well-Graded Sand with Silt and Gravel (SW-SM) - Brown, moist, loose, fine rounded to subangular. Fill placed in previous building footprint.</p> <p>Silty Sand with Gravel (SM) - Brown, moist, loose to dense, fine to coarse rounded to subangular. Layers of higher gravel content throughout.</p> | | | 13 | 2 2 4 | 6 | | 16.9 | | | | | <p>Note: BGS = Below Ground Surface</p> |
| 18 | | | | 2 2 3 | 5 | | | | | | | | |
| 5 | | | | 2 2 4 | 6 | | | | | | | | |
| 18 | | | | 2 4 6 | 10 | | | | | | | | |
| 12 | | | | 7 26 15 | 41 | 8.4 | | | | | | | |


Higher gravel content from 10-13 feet BGS.

Auger refusal at 13.0 feet BGS, due to suspected cobble or boulder.



Borehole Terminated at 13.0 Feet.

Latitude: 46.52133
Longitude: -114.70119

TEST BOREHOLE - STRATA.GDT - 1/19/23 12:06 - C:\USERS\MICHELSDROPOBOX (STRATA)\CDP22068 - ITD DISTRICT 2 FACILITY UPGRADES\CDP22068 - POWELL YARD\LOGS\CD22068A.LOGS.GPJ

| | | | |
|--|--------------------------------|--|----------------------------------|
| Project: CD22068A - Powell Maintenance Building | |  | Boring: B-5 |
| Client: Idaho Transportation Department | Drill Rig: G-2400 | | |
| Date Drilled: 11-16-2022 | Borehole Diameter: 7.0" | | |
| Depth to Groundwater: 21.5' | Logged By: S. Litalien | | |

TEST BOREHOLE - STRATA.GDT - 1/19/23 12:06 - C:\USERS\MICHELSDROPOX (STRATA)\CDP22068 - ITD DISTRICT 2 FACILITY UPGRADES\CDP22068 - POWELL YARD\LOGS\CD22068A.LOGS.GPJ

| Depth (ft) | USCS Description | Symbol | Sample Type | Recovery (in) | Blows Per 6 Inches | SPT N-Value | Pocket Pen (TSF) | Moisture Content (%) | Dry Density (pcf) | Percent Passing the No. 200 Sieve | Liquid Limit | Plasticity Index | Remarks |
|------------|--|--|--|----------------|--------------------|-------------|------------------|----------------------|-------------------|-----------------------------------|--------------|------------------|---|
| 0 | <p>Fill - Well-Graded Sand with Silt and Gravel (SW-SM) - Moist, loose, fine rounded to subangular. Fill placed in previous building footprint.</p> <p>Silty Sand with Gravel (SM) - Brown, moist, very loose to very dense, fine to coarse rounded to subangular. Layers of higher gravel content throughout.</p> |  |  | 18 | 4 4 5 | 9 | | 16.1 | | | | | <p>Note: BGS = Below Ground Surface</p> |
| 7 | | | | 2 3 2 | 5 | | | | | | | | |
| 5 | | | | 3 3 3 | 6 | | | | | | | | |
| 18 | | | | 2 2 2 | 4 | | | | | | | | |
| 10 | | | | 4 12 25 | 37 | | | | | | | | |
| 15 | | | | 24 21 31 | 52 | 6 | | | | | | | |
| 20 | | | | 2 3 6 | 9 | | | | | | | | |
| 25 | | | | 9 10 9 | 19 | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |

pH = 8.54
Sulfate = 47.2 mg/kg dry
Resistivity = 828 ohms-cm

Higher gravel content from 10-16.5 feet BGS.

Water Level Measured 11-16-22

Project: CD22068A - Powell Maintenance Building
Client: Idaho Transportation Department
Date Drilled: 11-16-2022
Depth to Groundwater: 21.5'

Drill Rig: G-2400
Borehole Diameter: 7.0"
Logged By: S. Litalien



Boring:
B-5

| Depth (ft) | USCS Description | Symbol | Sample Type | Recovery (in) | Blows Per 6 Inches | SPT N-Value | Pocket Pen (TSF) | Moisture Content (%) | Dry Density (pcf) | Percent Passing the No. 200 Sieve | Liquid Limit | Plasticity Index | Remarks |
|------------|---|--------|-------------|---------------|--------------------|-------------|------------------|----------------------|-------------------|-----------------------------------|--------------|------------------|--|
| 30 | Silty Sand with Gravel (SM) - Brown, moist, very loose to very dense, fine to coarse rounded to subangular. Layers of higher gravel content throughout. <i>(continued)</i> | | | 18 | 17 17 25 | 42 | | | | | | | Higher gravel content from 25-31.5 feet BGS. |
| 35 | | | | 12 | 5 6 4 | 10 | | | | | | | |

Borehole Terminated at 38.0 Feet.

Latitude: 46.5214
Longitude: -114.70136

TEST BOREHOLE - STRATA.GDT - 1/19/23 12:06 - C:\USERS\MICHEL\IDROPBOX (STRATA)\CDP22068 - ITD DISTRICT 2 FACILITY UPGRADES\CDP22068 - POWELL YARD\LOGS\CD22068A LOGS.GPJ

Project: CD22068A - Powell Maintenance Building
 Client: Idaho Transportation Department
 Date Drilled: 11-15-2022
 Depth to Groundwater: N.E.

Drill Rig: G-2400
 Borehole Diameter: 7.0"
 Logged By: S. Litalien



Boring:
 B-8

TEST BOREHOLE - STRATA.GDT - 1/19/23 12:06 - C:\USERS\MICHEL\SDROBOX (STRATA)\CDP22068 - ITD DISTRICT 2 FACILITY UPGRADES\CDP22068 - POWELL YARD\LOGS\CD22068A.LOGS.GPJ

| Depth (ft) | USCS Description | Symbol | Sample Type | Recovery (in) | Blows Per 6 Inches | SPT N-Value | Pocket Pen (TSF) | Moisture Content (%) | Dry Density (pcf) | Percent Passing the No. 200 Sieve | Liquid Limit | Plasticity Index | Remarks |
|------------|---|--------|-------------|----------------|--------------------|-------------|------------------|----------------------|-------------------|-----------------------------------|--------------|------------------|---|
| 0 | <p>Fill - Poorly Graded Gravel with Silt and Sand (GP-GM) - Gray, moist, medium dense, fine rounded to subangular. Gravel surfacing.</p> <p>Silty Sand with Gravel (SM) - Brown, moist, loose to medium dense, fine to coarse rounded to subangular. Layers of higher gravel content.</p> | | | 18 | 8 7 10 | 17 | | | | | | | <p>Note: BGS = Below Ground Surface</p> |
| 18 | | | | 4 4 5 | 9 | 14.7 | | | | | | | |
| 18 | | | | 4 4 7 | 11 | | | | | | | | |
| 18 | | | | 9 10 13 | 23 | | | | | | | | |
| 18 | | | | 25 10 18 | 28 | 5.2 | | | | | | | |
| 18 | | | | | | | | | | | | | |
| 18 | | | | | 15 15 7 | 22 | | | | | | | Minimal recovery in Shelby tube. |

Borehole Terminated at 17.0 Feet.

Latitude: 46.52145
 Longitude: -114.7018

Project: CD22068A - Powell Maintenance Building
Client: Idaho Transportation Department
Date Drilled: 11-15-2022
Depth to Groundwater: N.E.

Drill Rig: G-2400
Borehole Diameter: 7.0"
Logged By: S. Litalien




Boring:
B-9

TEST BOREHOLE - STRATA.GDT - 1/19/23 12:06 - C:\USERS\MICHEL\DROPBOX (STRATA)\CDP22068 - ITD DISTRICT 2 FACILITY UPGRADES\CDP22068 - POWELL YARD\LOGS\CD22068A LOGS.GPJ





| Depth (ft) | USCS Description | Symbol | Sample Type | Recovery (in) | Blows Per 6 Inches | SPT N-Value | Pocket Pen (TSF) | Moisture Content (%) | Dry Density (pcf) | Percent Passing the No. 200 Sieve | Liquid Limit | Plasticity Index | Remarks |
|------------|--|--------|-------------|----------------|--------------------|-------------|------------------|----------------------|-------------------|-----------------------------------|--------------|------------------|--|
| 0 | Fill - Silty Sand with Gravel (SM) - Gray, moist, loose, fine rounded to subrounded. Gravel surfacing. Silty Sand with Gravel (SM) - Light brown to gray, moist, very loose to medium dense, fine to coarse subrounded to angular. Layers of higher gravel content. | SM | | 18 | 4 3 3 | 6 | | 16.3 | | | | | |
| 14 | | | | 2 2 2 | 4 | | | | | | | | |
| 5 | | SM | | 18 | 3 3 4 | 7 | | | | | | | |
| 10 | | | | 2 2 6 | 8 | | | | | | | | |
| 15 | Silty Sand (SM) - Brown, moist, medium dense. Fine to coarse gravel scattered throughout. | SM | | 18 | 9 4 1 | 5 | | | | | | | Higher gravel content from 15-16.5 feet BGS. |
| 20 | | | | 22 15 11 | 26 | | | | | | | | |
| 23.5 | | | | 13 | 2 5 6 | 11 | | 8.7 | 114.7 | 46 | 0 | 0 | |

Borehole Terminated at 23.5 Feet.

Latitude: 46.52162
 Longitude: -114.70171


| | | | |
|--|--------------------------------|--|-----------------------------------|
| Project: CD22068A - Powell Maintenance Building | |  | Boring: B-10 |
| Client: Idaho Transportation Department | Drill Rig: G-2400 | | |
| Date Drilled: 11-15-2022 | Borehole Diameter: 7.0" | | |
| Depth to Groundwater: N.E. | Logged By: S. Litalien | | |


TEST BOREHOLE - STRATA.GDT - 1/19/23 12:06 - C:\USERS\MICHEL\IDROBOX (STRATA)\CDP22068 - ITD DISTRICT 2 FACILITY UPGRADES\CDP22068 - POWELL YARD\LOGS\CD22068A.LOGS.GPJ

| Depth (ft) | USCS Description | Symbol | Sample Type | Recovery (in) | Blows Per 6 Inches | SPT N-Value | Pocket Pen (TSF) | Moisture Content (%) | Dry Density (pcf) | Percent Passing the No. 200 Sieve | Liquid Limit | Plasticity Index | Remarks |
|------------|---|---|---|---------------|--------------------|-------------|------------------|----------------------|-------------------|-----------------------------------|--------------|------------------|--|
| 0 | Fill - Silty Sand with Gravel (SM) - Brown to gray, moist, medium dense, fine to coarse rounded to subangular. Gravel surfacing. Silty Sand with Gravel (SM) - Brown, moist, very loose to dense, fine to coarse. Layers of higher gravel content. |  |  | 18 | 10 8 7 | 15 | | 14.5 | | | | | |
| | | | | 14 | 3 3 6 | 9 | | | | | | | |
| 5 | | | | 3 | 4 4 5 | 9 | | | | | | | |
| | | | | 18 | 2 3 4 | 7 | | | | | | | |
| 10 | | | | 18 | 3 2 2 | 4 | | | | | | | |
| 15 | | | | 18 | 33 27 18 | 45 | | | | | | | |
| | Silty Sand (SM) - Brown, moist to wet, very loose to loose. Fine to coarse gravel scattered throughout. |  |  | 18 | 1 1 1 | 2 | | 23.5 | | | | | Higher gravel content from 15-16.5 feet BGS. |
| 20 | | | | 18 | 2 3 7 | 10 | | | | | | | |
| 25 | | | | 18 | 2 3 7 | 10 | | | | | | | |

Borehole Terminated at 26.5 Feet.

 Latitude: 46.52177
 Longitude: -114.70142

| | | | |
|--|-------------------------------|--|-------------------------------------|
| Project: CD22068A - Powell Maintenance Building | |  | Test Pit: TP-1 |
| Client: Idaho Transportation Department | Backhoe: CAT 306 | | |
| Date Excavated: 11-15-2022 | Bucket Width: 18.0 | | |
| Depth to Groundwater: N.E. | Logged By: S. Litalien | | |

| Depth (ft) | USCS Description | Symbol | Sample Type | DCP Blows | DCP Value | Pocket Pen (TSF) | Moisture Content (%) | Dry Density (pcf) | Percent Passing the No. 200 Sieve | Liquid Limit | Plasticity Index | Remarks |
|------------|--|---|-------------------------------------|-----------|-----------|------------------|----------------------|-------------------|-----------------------------------|--------------|------------------|-------------------------------------|
| 0 | Fill - Silty Sand with Gravel (SM) - Gray, moist, fine to coarse rounded to subangular. Gravel surfacing. Silty Sand with Gravel (SM) - Brown, moist, fine to coarse rounded to subangular. Cobbles present throughout. |  | <input checked="" type="checkbox"/> | | | | 8.6 | | 13.9 | 0 | 0 | Note: BGS = Below Ground Surface |
| 5 | Terminated at 5.0 Feet. | | | | | | | | 32.4 | 0 | 0 | |

Latitude: 46.52169
 Longitude: -114.701353

TEST PIT - STRATA.GDT - 1/19/23 12:04 - C:\USERS\MICHEL\S\DROPBOX (STRATA)\CDP22068 - ITD DISTRICT 2 FACILITY UPGRADES\CDP22068 - POWELL YARD\LOGS\CD22068A LOGS.GPJ

Project: CD22068A - Powell Maintenance Building
Client: Idaho Transportation Department
Date Excavated: 11-15-2022
Depth to Groundwater: N.E.

Backhoe: CAT 306
Bucket Width: 18.0
Logged By: S. Litalien



Test Pit:
TP-2

| Depth (ft) | USCS Description | Symbol | Sample Type | DCP Blows | DCP Value | Pocket Pen (TSF) | Moisture Content (%) | Dry Density (pcf) | Percent Passing the No. 200 Sieve | Liquid Limit | Plasticity Index | Remarks |
|------------|--|--------|-------------|-----------|-----------|------------------|----------------------|-------------------|-----------------------------------|--------------|------------------|--|
| 0 | Fill - Poorly Graded Gravel with Silt and Sand (GP-GM) - Brown, moist, fine to coarse rounded to subangular. | GP-GM | | | | | | | | | | Note: BGS = Below Ground Surface Idaho T-8 R-Value = 50 |
| | Topsoil - Silt with Sand (ML) - Dark brown to black, moist. Roots and organics scattered throughout. Remnant topsoil. | ML | | | | 16.8 | | 38 | 0 | 0 | | |
| | Silty Sand with Gravel (SM) - Brown, moist, fine to coarse rounded to subangular. | SM | | | | | | | | | | |

Terminated at 5.0 Feet.

Latitude: 46.52138
 Longitude: -114.70087

TEST PIT - STRATA.GDT - 1/19/23 12:05 - C:\USERS\MICHEL\S\DROPBOX (STRATA)\CDP22068 - ITD DISTRICT 2 FACILITY UPGRADES\CDP22068 - POWELL YARD\LOGS\CD22068A LOGS.GPJ

Project: CD22068A - Powell Maintenance Building
Client: Idaho Transportation Department
Date Excavated: 11-15-2022
Depth to Groundwater: N.E.

Backhoe: CAT 306
Bucket Width: 18.0
Logged By: S. Litalien




Test Pit:
TP-3



| Depth (ft) | USCS Description | Symbol | Sample Type | DCP Blows | DCP Value | Pocket Pen (TSF) | Moisture Content (%) | Dry Density (pcf) | Percent Passing the No. 200 Sieve | Liquid Limit | Plasticity Index | Remarks |
|------------|--|--------|-------------|-----------|-----------|------------------|----------------------|-------------------|-----------------------------------|--------------|------------------|------------------------|
| 0 | Fill - Silty Sand with Gravel (SM) - Dark brown to black, moist, fine to coarse rounded to subangular. Derived from topsoil, organics and roots throughout. | | | | | | | | | | | Organic Content = 5.1% |
| 5 | Silty Sand with Gravel (SM) - Light brown, moist, fine to coarse rounded to subangular. | | BG | | | | | | | | | |

Terminated at 5.5 Feet.

Latitude: 46.5211
 Longitude: -114.70071

TEST PIT - STRATA.GDT - 1/19/23 12:05 - C:\USERS\LMICHEL\S\DROPBOX (STRATA)\CDP22068 - ITD DISTRICT 2 FACILITY UPGRADES\CDP22068 - POWELL YARD\LOGS\CD22068A LOGS.GPJ

| | | | |
|--|-------------------------------|--|-------------------------------------|
| Project: CD22068A - Powell Maintenance Building | |  | Test Pit: TP-4 |
| Client: Idaho Transportation Department | Backhoe: CAT 306 | | |
| Date Excavated: 11-15-2022 | Bucket Width: 18.0 | | |
| Depth to Groundwater: N.E. | Logged By: S. Litalien | | |

| Depth (ft) | USCS Description | Symbol | Sample Type | DCP Blows | DCP Value | Pocket Pen (TSF) | Moisture Content (%) | Dry Density (pcf) | Percent Passing the No. 200 Sieve | Liquid Limit | Plasticity Index | Remarks Note: BGS = Below Ground Surface |
|------------|--|---|---|-----------|-----------|------------------|----------------------|-------------------|-----------------------------------|--------------|------------------|--|
| 0 | Fill - Poorly Graded Gravel with Silt and Sand (GP-GM) - Moist, fine to coarse rounded to subangular. Boulders, asphalt fragments, and debris throughout. |  |  | | | | | | | | | Excavator refused at 4.5 feet BGS due to boulders. |

Terminated at 4.5 Feet.

Latitude: 46.52083
Longitude: -114.70164

TEST PIT - STRATA.GDT - 1/19/23 12:05 - C:\USERS\MICHEL\S\DROPBOX (STRATA)\CDP22068 - ITD DISTRICT 2 FACILITY UPGRADES\CDP22068 - POWELL YARD\LOGS\CD22068A LOGS.GPJ


Appendix B


Laboratory Test Results

SIEVE ANALYSIS ASTM D6913 (Method A)

Project: Powell Maintenance Building
 Project Number: CD22068A
 Client: Idaho Transportation Department
 Sample Number: 41454
 Sample Location: TP-1 @ 0-0.5'
 Sample Classification: Silty Sand with Gravel (SM)
 Date Tested: 12/06/22 By: D. Taylor
ASTM D4318 - Atterberg Limits
 LL = NV, PI = NP

| | | | | | | | |
|---------|--------|------|--------|--------|------|--|--|
| Cobbles | Gravel | | Sand | | | | |
| | Coarse | Fine | Coarse | Medium | Fine | | |



Reviewed By: 


 Luke Michels, P.E.
 Engineering Services Manager




SIEVE ANALYSIS ASTM D6913 (Method A)

Project: Powell Maintenance Building
 Project Number: CD22068A
 Client: Idaho Transportation Department
 Sample Number: 41453
 Sample Location: TP-1 @ 0.5-3'
 Sample Classification: Silty Sand with Gravel (SM)
 Date Tested: 12/06/22 By: D. Taylor
ASTM D4318 - Atterberg Limits
 LL = NV, PI = NP

| | | | | | |
|---------|--------|------|--------|--------|------|
| Cobbles | Gravel | | Sand | | |
| | Coarse | Fine | Coarse | Medium | Fine |




Reviewed By: 
 Luke Michels, P.E.
 Engineering Services Manager



SIEVE ANALYSIS ASTM D6913 (Method A)

Project: Powell Maintenance Building
 Client: Idaho Transportation Department
 Project Number: CD22068A
 Sample Number: BL221539
 Sample Location: TP-2 @ 2.5'-5'
 Sample Classification: Silty Sand with Gravel (SM)
 Moisture Content: 16.8%
 Date Tested: 12/2022 By: D. Bjorum




Reviewed By: Barry C. Miller
 Barry Miller, P.E., P.G.




SIEVE ANALYSIS ASTM D6913 (Method A)

Project: Powell Maintenance Building
 Project Number: CD22068A
 Client: Idaho Transportation Department
 Sample Number: 41455
 Sample Location: Bulk West of B-4
 Sample Classification: Well Graded Sand with Silt and Gravel (SW-SM)
 Date Tested: 12/06/22 By: D. Taylor
ASTM D4318 - Atterberg Limits
 LL = NV, PI = NP

| | | | | | | | |
|---------|--------|------|--------|--------|------|--|--|
| Cobbles | Gravel | | Sand | | | | |
| | Coarse | Fine | Coarse | Medium | Fine | | |




Reviewed By: 
 Luke Michels, P.E.
 Engineering Services Manager



SIEVE ANALYSIS ASTM D6913 (Method A)

Project: Powell Maintenance Building
 Project Number: CD22068A
 Client: Idaho Transportation Department
 Sample Number: BL221538
 Sample Location: B-9 @ 20'-22'
 Sample Classification: Silty Sand (SM)
 Moisture Content: 8.7%
 Date tested: 12/14/2022 By: D. Wheeler



Reviewed By: Barry Miller
 Barry Miller, P.E., P.G.




MOISTURE-DENSITY RELATIONSHIP CURVE AASHTO T180

Project: Powell Maintenance Building
 Client: Idaho Transportation Department
 Project Number: CD22068A
 Sample Number: 41453
 Sample Location: TP-1, 0.5-3'
 Sample Classification: Silty Sand with Gravel (SM)
 Date Sampled: 11/15/2022 - 11/16/2022
 Date Tested: 12/9/2022 Tested By: D. Taylor
 Soil Tempered: No
 Rammer Type: Manual

| GRADING ANALYSIS | | |
|------------------|-----------|-----------|
| SCREEN SIZE | % PASSING | AS TESTED |
| 6 inch | | |
| 3 inch | | |
| 2 inch | | |
| 3/4 inch | 91 | 100 |
| 3/8 inch | | |
| #4 screen | | |

Maximum Dry Density, pcf : 131.8
 Optimum Moisture Content, %: 7.4

Corrected Dry Density, pcf: 134.3
 Corrected Moisture Content, %: 6.8
 *Coarse Aggregate Correction, %: 9.1
 Bulk Specific Gravity (assumed): 2.65





Reviewed By: *John M... [Signature]*

DIRECT SHEAR ASTM D 3080

Project: Powell Maintenance Building
 Client: Idaho Transportation Department
 Sample Location: B-1A @ 4'-4.5'
 Sample Classification: Silty Sand with Gravel (SM)
 Moisture: 17.6%
 Dry Unit Weight: 104.3 pcf

Project Number: CD22068A
 Sample Number: BL221537
 Date Tested: 12/18/2022
 By: D. Bjorum



Reviewed By: Barry Miller
 Barry Miller, P.G., P.E.




R-VALUE Idaho T-8

Project: Powell Maintenance Building
 Client: Idaho Transportation Department
 Project Number: CD22068A
 Sample Number: BL221539
 Sample Location: TP-2 @ 2.5'-5.0'
 Sample Classification: Silty Sand with Gravel (SM)
 Date Tested: 12/7/2022
 Tested By: V. Barinaga

| R VALUE DATA | | | | |
|---------------------|------|---------|---------|---------|
| Percolation: | None | Point 1 | Point 2 | Point 3 |
| Exudation, PSI | | 83 | 206 | 401 |
| Dry Density, PCF | | 109.4 | 107.7 | 108.7 |
| Moisture Content, % | | 17.6 | 14.8 | 13.1 |
| Exp. Pressure, PSI | | 0.00 | 0.43 | 0.49 |

SOIL CONSTANTS

R-VALUE: 50



| GRADATION: AASHTO T-11, T27 | | |
|-----------------------------|-----------------------|---------------------|
| SCREEN SIZE | AS RECEIVED % PASSING | AS TESTED % PASSING |
| 4" | | |
| 3" | | |
| 2" | | |
| 1" | | |
| 3/4" | 100 | 100 |
| 1/2" | | |
| 3/8" | | |
| No. 4 | | |
| No. 8 | | |
| No. 16 | | |
| No. 30 | | |
| No. 50 | | |
| No. 100 | | |
| No. 200 | | |

Reviewed By: By C. Z.



Anatek Labs, Inc.

1282 Alturas Drive - Moscow, ID 83843 - (208) 883-2839 - Fax (208) 8829246 - email moscow@anateklabs.com
504 E Sprague Ste. D - Spokane, WA 99202 - (509) 838-3999 - fax (509) 838-4433 - email spokane@anateklabs.com

Client: Strata, Inc. - CdA
Address: 1016 W. Hayden Avenue
Hayden, ID 83835
Attn: Luke Michels


Work Order: WCK1006
Project: CD22068A
Reported: 12/22/2022 10:01

Analytical Results Report

Sample Location: B-5; 2.5-3'
Lab/Sample Number: WCK1006-01 **Collect Date:** 11/16/22 12:00
Date Received: 11/28/22 10:31 **Collected By:** Steve Litalien
Matrix: Soil

| Analyte | Result | Units | PQL | Analyzed | Analyst | Method | Qualifier |
|-------------------|--------|-----------|-------|----------------|---------|------------|-----------|
| Inorganics | | | | | | | |
| % Solids | 87.6 | % | 0.100 | 11/29/22 12:00 | IG | SM 2540 G | |
| Sulfate | 47.2 | mg/kg dry | 11.4 | 12/22/22 1:32 | BKP | EPA 300.0 | |
| pH | 8.54 | pH Units | 0.982 | 11/29/22 10:06 | ILG | EPA 9045D | |
| Resistivity | 828 | ohms-cm | 1.00 | 11/29/22 10:37 | ILG | ASTM G 57a | |

Authorized Signature,



Kathleen Sattler, Laboratory Manager

PQL Practical Quantitation Limit
ND Not Detected
MCL EPA's Maximum Contaminant Level
Dry Sample results reported on a dry weight basis
* Not a state-certified analyte

This report shall not be reproduced except in full, without the written approval of the laboratory
The results reported related only to the samples indicated.

Anatek Labs, Inc.

1282 Alturas Drive - Moscow, ID 83843 - (208) 883-2839 - Fax (208) 8829246 - email moscow@anateklabs.com
 504 E Sprague Ste. D - Spokane, WA 99202 - (509) 838-3999 - fax (509) 838-4433 - email spokane@anateklabs.com

Quality Control Data

Inorganics

| Analyte | Result | Qual | Reporting Limit | Units | Spike Level | Source Result | %REC | %REC Limits | RPD | RPD Limit |
|--|--------|------|-----------------|-----------|--|---------------|------|-------------|------|-----------|
| Batch: BCL0704 - Anions | | | | | | | | | | |
| Blank (BCL0704-BLK1) | | | | | | | | | | |
| Sulfate | ND | | 0.100 | mg/kg wet | | | | | | |
| | | | | | Prepared & Analyzed: 12/21/2022 | | | | | |
| LCS (BCL0704-BS1) | | | | | | | | | | |
| Sulfate | 4.32 | | 0.100 | mg/kg wet | 4.00 | | 108 | 90-110 | | |
| | | | | | Prepared & Analyzed: 12/21/2022 | | | | | |
| Matrix Spike (BCL0704-MS1) | | | | | | | | | | |
| Sulfate | 466 | | 10.4 | mg/kg dry | 417 | 29.3 | 105 | 90-110 | | |
| | | | | | Source: WCK0744-01 Prepared: 12/21/2022 Analyzed: 12/22/2022 | | | | | |
| Matrix Spike (BCL0704-MS2) | | | | | | | | | | |
| Sulfate | 472 | | 10.7 | mg/kg dry | 430 | 13.1 | 107 | 90-110 | | |
| | | | | | Source: WCK1055-01 Prepared: 12/21/2022 Analyzed: 12/22/2022 | | | | | |
| Matrix Spike Dup (BCL0704-MSD1) | | | | | | | | | | |
| Sulfate | 451 | | 10.4 | mg/kg dry | 417 | 29.3 | 101 | 90-110 | 3.37 | 25 |
| | | | | | Source: WCK0744-01 Prepared: 12/21/2022 Analyzed: 12/22/2022 | | | | | |
| Matrix Spike Dup (BCL0704-MSD2) | | | | | | | | | | |
| Sulfate | 445 | | 10.7 | mg/kg dry | 430 | 13.1 | 101 | 90-110 | 5.72 | 25 |
| | | | | | Source: WCK1055-01 Prepared: 12/21/2022 Analyzed: 12/22/2022 | | | | | |



Chain of Custody Record

Anatek Labs

1282 Alturas Drive, Moscow
504 E Sprague Ste D, Spokane

WCK1006



Due: 12/12/22

Company Name: STRATA Project Manager: Luke Michels
 Address: 1016 W. Hayden Ave. Project Name & #: CD22068A
 City: Hayden State: ID Zip: 83835 Purchase Order #:
 Phone: 208-772-2428 Sampler Name & Phone: Steve Litalien; 208-818-7535
 Email Address(es): lmicheles@stratageotech.com

Turn Around

Please refer to

www.anateklabs.com/pricing-lists

Normal Phone
 Next Day* Email
 2nd Day* *All rush order requests must
 Other* have prior approval

| Lab ID | Sample Identification | Sampling Date/Time | Matrix | List Analyses Requested | | | | | | | | | | |
|--------|-----------------------|--------------------|--------|-------------------------|---------------|--------------|------------------------|-------------------|--|--|--|--|--|--|
| | | | | # of Containers | Sample Volume | pH/ASTM 4972 | Resistivity ASTM G 187 | Sulfate EPA 300.0 | | | | | | |
| | B-5; 2.5'3' | 11-16-22; 1200 | Soil | 1 | 0.5 | X | X | X | | | | | | |

Note Special Instructions/Comments

Inspection Checklist

Received Intact? Y N
 Labels & Chains Agree? Y N
 Containers Sealed? Y N
 No VOC Head Space? Y N
 Cooler? Y N
 Ice/Ice Packs Present? Y N

Temperature (°C): 18.2° IR2

| | Printed Name | Signature | Company | Date | Time |
|-----------------|----------------|-----------|---------|----------|-------|
| Relinquished by | Steve Litalien | | STRATA | 11-28-22 | 10:30 |
| Received by | Brook... .. | | Anatek | 11-28-22 | 10:31 |
| Relinquished by | | | | | |
| Received by | | | | | |
| Relinquished by | | | | | |
| Received by | | | | | |

Number of Containers: 1 bag
 Shipped Via: bag
 Preservative: NH4+
 Date & Time: 11-28-22 10:33
 Inspected By: SM

Samples submitted to Anatek Labs may be subcontracted to other accredited labs if necessary. This message serves as notice of this possibility. Subcontracted analyses will be clearly noted on the analytical report.