Project:	Reviewer:
River;	
Project Purpose:	Date:
Project File Name:	
Additional Information:	Modeler:

	** Blank comment entries below indicate that the item was not reviewed.				
ltem	Comment	Action Needed (blank=none)	Response to Comment/ Resolution	Screen Shot Li	ink
Model Background Data					
Version of SMS/SRH-2D documented?					
Project vertical datum?					
Project horizontal datum?					
Documentation of techniques and procedures?					
Meta data included in model files?					
Topography					
Source/Date					
If Lidar data, has it been filtered to removed vegetation and structures?					
Stated Accuracy					
Datums verified					
Data type (Scatter set or 3D Raster image)					
Number of points / average spacing					
Bathymetry					
Source/Date					
Datums verified					
Additional Survey				I I	
Source/Date					
Datums verified					
Bridge/Culvert/Structure Data			*	+	
Source/Date					
Datums verified					
Copographic Data review			"	"	
Were multiple data sources merged to create a terrain map? If so, which sources?					-
Data consistency - Are the transitions between data sets smooth?					
Does final surface accurately represent site (are hydraulic controls represented)?					
Confirm breaklines used where necessary					
2D Mesh					
How many mesh elements?					
Are the number and size of mesh elements appropriate?					
What is the range of element sizes and is it appropriate for this project application?					

What is the length of the modeled reach?		
What are the approximate floodplain widths (upstream/downstream)?		
Is the upstream mesh limit sufficient?		
Is the downstream mesh limit sufficient?		
Are the lateral extents sufficient?		
Are key project features correctly represented?		
Are all slope features (channel banks, embankments, etc.) represented by at least 2 or more elements?		
Is mesh quality acceptable?		

### ADMINISTRATION OF THE PROPERTY OF THE PROP	Boundary Conditions				
### STATE OF THE PROPERTY OF T	Are unsteady or steady simulations performed?				
Special boundary. Performent principal growth special processing of the processing o	Do boundary conditions have descriptive names?				
Visional Residuo Visional Re	What is the source for the inflow data?				
Sign	Upstream Boundary - Verify correct inflow(s) amount, type, and location				
Section Standard Stan					
Accoration in Series Accoration in Series Accoration in Series Accoration in Accordance Accoration in Accordance	Downstream Boundary -				
Name and you do not you have not be large or you have? So the surprise promoted or the large you of shee? So the surprise perfection person of the large you have y	Are boundary conditions applied (mapped) to mesh correctly?				
Note the source and entired special and selection of the	Are monitoring lines used?				
What is the secure of malieral coverage and colones? On the substitute definition accord to the history of the mich domain And make all types convertly sugginar? And make all types convertly sugginar? Physical Structures ***********************************	Material Roughness				
So this manufacture state for the limits (at begand) is manufacture) An endered by responsed the relative pass controlly responsed to the relative	How many materials types are used?				
limins 2 Ane motival types correctly assigned? Ane the appropriate Meeting's is values used? And the appropriate Meeting's is values used? And the appropriate Meeting's is values used? ***********************************	What is the source of material coverage and values?				
Any the appropriate Manning's a values used? Mydratic Structures					
Hydraulic Structures Now many structure as or represented? What types?	Are material types correctly assigned?				
Note Process	Are the appropriate Manning's n-values used?				
Is the geometry beneath the bridge represented correctly? Is the geometry beneath the bridge represented as looks in the med. The concentration of the bridge represented as looks in the med. The concentration of the bridge represented as looks in the med. The concentration of the bridge represented as looks in the med. The colling eventure the world desire great the world of represent the asset general desire for rectangular zone between them. Concentration of the bridge of the span represented in the colling eventure the span desire great the span desired product of protect the span represented in the colling eventure data spans, the overlooping option should in the desired to concentration of the bridge of the span represented in the span data spans, the overlooping option should in the span represented in the span data spans, the overlooping option should in the span represented in the span represe	Hydraulic Structures				
is the geometry beneath the bridge represented correctly? For detailed hydraulics, gives should be represented as his less in the most. The disministion of the his children waveger disministions that are Pressure & are should be parallel and form rettrangular rough between them. Desired and should represent the average line-involved service of the same represented. Desired and should represent the average line-involved service of the same represented as exempt low child defendant of the bridge, or the span represented. Desired and parallel stress of the span represented. Desired and parallel stress of the span represented as the should be reviewed for stable. Desired and parallel stress of the span represented as the should be reviewed for stable. Culvert Culvert The menh elements should generally sign with the culvert and have element face that are boarded one to the other invests. Culvert Extra stable line placed at the culvert livert locations and should generally sign with the culvert most stable placed at the culvert livert locations and should generally sign which the culvert locations and should generally sign with the culvert locations and the livert locations and should generally sign with the culvert locations and the livert locations and the location should be set to the destruction. So the culvert Cars should be located at the culvert locations and the livert locations and the livert locations. It culvert cars should also sould at all culvert lovert locations and the livert locations. It is culvert cars should also set to the bottom elevation of the obstructions and culvert lovert locations and culvert locations and the livert locations and the livert locations and culvert	How many structures are represented? What types?				
For dealed hydraulics, pies should be represented as holes in the mech. The denomination of the hole should represent the average from recognized mechanisms that are considered on the parallel and for undergodized mechanisms. The celling devision should represent the average low found evaluation of the being devision should represent the average low found evaluation of the being or the open represented. The celling devision should represent the average low found evaluation of the long of the devision should perceived for should be received for should be parallel and the culter's twent books for an at YES culter 18. The most elements should generally align with the outer invert books for an at YES culter 18. The celling the received for the culter's twent books for an at YES culter 18. The received for the culter's twent books for an at YES culter 18. The found the found of the culter's twent books for an at YES culter 18. The clusters for the received for should be found to the time the cultions and the EYES elevation and the limit to book for the culter's twent books for an at YES culter 18. The clusters for the culter's twent books for an at YES culter 18. The clusters for the culter's twent books for an at YES culter 18. The clusters for the culter's twent books for the culter's twent	Bridge				
dimensions of the hole should represent the average dimensions that are Frequence & care subuls be parallel and from rectangular zone between them. The calling densities whold represent the next gold box chief delivation of the large generation should represent the next gold box chief delivation of the large generation should represent the next gold box chief delivation of the large generation should perspect the chief properties of	Is the geometry beneath the bridge represented correctly?				
The celling elevation should represent the average low chord elevation of the bridge, or the span representation. If the deck is evertage and a state of the span representation of the bridge, or the span representation. If the deck is overtagening the internal dad file should be reviewed for stable. With a file should be reviewed for stable. With a file with the culter and have element fixed that are located close to the culter invertion and should generally align with the culvert and have element fixed that are located close to the culter invert locations and should generally represent the width of the culvert invert locations and should generally represent the width of the culvert invert locations and should generally represent the width of the culvert invert locations and the Iff-8 elevations should be considered with the Demonstration of the culter invert locations and the Iff-8 elevations should be considered with the Demonstration of the culter invert locations and the Iff-8 elevations should be considered with the mesh elevations at the invert locations. Is culvert Correctly represented. Are obstructions used in the mode? The elevation of the obstruction are should align with the centerine of the obstruction, with the appropriated elevations and coefficients entered in the obstruction dialog. Other Structures are represented?					
bridge, or the span represented. If the upstrams MySE accreeds the deck elevation, the overtopping option should be selected and parameters defined. If the deck is overtopping, the Internal data file should be reviewed for stable WySE and follow. Culvert 8. Are should be placed at the culvert and have element faces that are located does to the culvert inverts. Culvert B. Are should be placed at the culvert inverts. Culvert B. Are should be placed at the culvert invert locations and should generally align with the culvert invert locations. If the deck is overtically represented the width of the culvert invert locations and should generally align with the culvert invert locations. If the deck is overtically represented to the culvert invert locations and the IMS deceased at the culvert invertically represented to the culvert invertications and the invertical representation of the obstructions are the invertications and the invertications and the invertications are the invertications and the invertications are the culture invertications and the invertications are should be set to the bottom elevation of the obstructions are should align with the centerine of the obstructions, with the appropriated elimentors and coefficients entered in the obstructions dialog. Other Structures What other structures are represented?					
be selected and parameters defined. If the deck is overlooping, the Internal dat file should be reviewed for stable WSEL and flow University of the Content of the Culter Inversity of the Culter In					
If the decks to overlooping, the internalia data file should be reviewed for stable Wists and flow Culvert Culvert The mesh denients should generally align with the culvert and have element faces that are located close to the culvert inverts Culvert BC arcs should be placed at culvert invert locations and should generally represent the width of the culvert invert locations and should generally represent the width of the culvert invert locations and the HYS elevations build be placed at the culvert invert locations and the HYS elevations build be consistent with the mesh elevations should be consistent with the mesh elevations should be consistent with the mesh elevations should be consistent with the mesh elevations at the invert locations. Is culvert correctly represented Cobstructions Are obstructions used in the model? The elevation of the obstruction are should be set to the bottom elevation of the obstruction. The obstruction is not coefficients entered in the obstruction, with the appropriate dimemstions and coefficients entered in the obstructions dialog. Chief Structures What other structures are represented? What other structures are represented?					
Culvert The mesh elements should generally align with the culvert inverts that are located close to the culvert liveres Culvert BC are should be placed at the culvert invert locations and should generally represent the width of the culvert invert locations and should generally represent the width of the culvert invert locations and should generally represent the width of the culvert invert locations and the IV's elevations should be located at the culvert invert locations and the IV's elevations should be consistent with the mesh elevations at the invert locations. Is culvert correctly represented Obstructions Are obstructions used in the model? The elevation of the obstruction are should be set to the bottom elevation of the obstruction. The elevation are should align with the centerline of the obstruction, with the appropriate dimentions and coefficients entered in the obstructions dialog. Other Structures What other structures are represented?	If the deck is overtopping, the Internal#.dat file should be reviewed for stable				
that are located close to the culvert inverts Liver B Cars Should be placed at the culvert invert locations and should generally represent the width of the culvert(s) Is the culvert modeled in the ZD mesh or as a HV-8 culvert? HY-8 Culvert BC arcs should be located at the culvert invert locations and the HY-8 elevations should be consistent with the mesh elevations at the invert locations and the HY-8 elevations should be consistent with the mesh elevations at the invert locations Is culvert correctly represented Obstructions Are obstructions used in the model? The elevation of the obstruction arc should align with the centerline of the obstruction, with the appropriate dimentions and coefficients enterred in the obstructions dialog. Other Structures What other structures are represented?					
generally represent the width of the culvert(s) Is the culvert modeled in the 2D mesh or as a HY-8 culvert? HY-8 Culvert BC arcs should be located at the culvert invert locations and the HY-8 elevations should be consistent with the mesh elevations at the invert locations. Is culvert correctly represented Obstructions Are obstructions used in the model? The elevation of the obstruction arc should be set to the bottom elevation of the obstruction arc should align with the centerline of the obstruction, with the appropriate dimentions and coefficients enterred in the obstructions dialog. Other Structures What other structures are represented?	that are located close to the culvert inverts				
HY-8 Culvert BC arcs should be located at the culvert invert locations and the HY-8 elevations should be consistent with the mesh elevations at the invert locations. Is culvert correctly represented Obstructions Are obstructions used in the model? The elevation of the obstruction arc should be set to the bottom elevation of the obstruction arc should be set to the bottom elevation of the obstruction arc should align with the centerline of the obstruction, with the appropriate dimentions and coefficients entered in the obstructions dialog. Other Structures What other structures are represented?					
elevations should be consistent with the mesh elevations at the invert locations. Is culvert correctly represented Obstructions Are obstructions used in the model? The elevation of the obstruction arc should be set to the bottom elevation of the obstruction. The obstruction arc should align with the centerline of the obstruction, with the appropriate dimentions and coefficients enterred in the obstructions dialog. Other Structures What other structures are represented?	Is the culvert modeled in the 2D mesh or as a HY-8 culvert?				
Are obstructions used in the model? The elevation of the obstruction arc should be set to the bottom elevation of the obstruction. The obstruction arc should align with the centerline of the obstruction, with the appropriate dimentions and coefficients enterred in the obstructions dialog. Other Structures What other structures are represented?					
Are obstructions used in the model? The elevation of the obstruction arc should be set to the bottom elevation of the obstruction. The obstruction arc should align with the centerline of the obstruction, with the appropriate dimentions and coefficients enterred in the obstructions dialog. Other Structures What other structures are represented?	Is culvert correctly represented				
The elevation of the obstruction arc should be set to the bottom elevation of the obstruction. The obstruction arc should align with the centerline of the obstruction, with the appropriate dimentions and coefficients enterred in the obstructions dialog. Other Structures What other structures are represented?	Obstructions				
obstruction. The obstruction arc should align with the centerline of the obstruction, with the appropriate dimentions and coefficients enterred in the obstructions dialog. Other Structures What other structures are represented?					
appropriate dimentions and coefficients enterred in the obstructions dialog. Other Structures What other structures are represented?					
What other structures are represented?					
	Other Structures				
Is structure correctly represented?	What other structures are represented?				
	Is structure correctly represented?				

Model Controls and Simulations			
How many simulations are included?			
Are they labeled appropriately and do they include the correct components.			
Review time step used for each simulation			
Review simulation times			
Turbulence model should be set to the Parabolic Method with a coefficient of 0.7			
Initial Condition used			

Model Results			
Are monitoring points used?			
Confirm model stability at monitoring points			
Confirm continuity at monitoring lines			
Confirm stable results through the domain			
Froude Number - Are results reasonable?			
Shear Stress			
Water Elevations			
Velocity			
Water Depth			
Additional Notes:			
Model Calibration			
Was calibration performed? If so, does the model data match the calibration data?			
If no calibration, were any sensitivity analyses performed?			
General Comments			