

Idaho Transportation Department  
Percent of MADT At Continuous Count Speed Sites

|  |                          |
|--|--------------------------|
| Site ID: 001330 001.300                  | Scheme ID: 6             |
| Location: #022 I-15 11.8 Mi. S. of Malad | County: ONEIDA           |
| Axle Factor Group: 1                     | Growth Factor Group: 1   |
| Seasonal Factor Group: 5                 | FHWA Functional Class: 1 |
|  | Speed Limit: 75          |

| SPEED    | 1997 Traffic Year |       |       |       |       |       |       |       |       |       |       |       |      |
|----------|-------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
|          | Jan               | Feb   | Mar   | Apr   | May   | Jun   | Jul   | Aug   | Sep   | Oct   | Nov   | Dec   | Avg  |
| 0>-30    | 0.2               | 0.1   | 0.1   | 0.2   | 0.2   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.0   | 0.1  |
| 30>-35   | 0.2               | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0  |
| 35>-40   | 0.4               | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0  |
| 40>-45   | 0.7               | 0.1   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.1   | 0.1  |
| 45>-50   | 0.9               | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.2   | 0.2  |
| 50>-55   | 1.5               | 0.5   | 0.4   | 0.4   | 0.4   | 0.4   | 0.4   | 0.4   | 0.5   | 0.5   | 0.4   | 0.6   | 0.5  |
| 55>-60   | 3.3               | 1.9   | 1.7   | 1.7   | 1.7   | 1.7   | 1.7   | 1.7   | 1.9   | 1.8   | 1.5   | 2.1   | 1.9  |
| 60>-65   | 8.1               | 6.1   | 5.9   | 5.9   | 5.7   | 5.7   | 5.4   | 5.3   | 5.9   | 5.7   | 5.0   | 5.8   | 5.9  |
| 65>-70   | 16.0              | 14.6  | 14.1  | 13.1  | 12.8  | 12.4  | 11.7  | 11.4  | 12.5  | 12.5  | 12.0  | 13.4  | 13.0 |
| 70>-75   | 24.9              | 25.5  | 25.1  | 26.1  | 24.8  | 24.9  | 24.3  | 23.9  | 24.4  | 24.7  | 25.1  | 25.5  | 24.9 |
| 75>-80   | 27.2              | 31.3  | 31.6  | 31.4  | 31.7  | 31.9  | 32.3  | 32.1  | 31.4  | 31.3  | 31.3  | 29.8  | 31.1 |
| 80>-85   | 11.6              | 14.3  | 15.6  | 14.1  | 15.2  | 16.0  | 16.6  | 17.5  | 15.2  | 15.4  | 16.5  | 15.9  | 15.3 |
| 85>-140  | 4.9               | 5.4   | 5.2   | 6.9   | 7.4   | 6.8   | 7.4   | 7.5   | 8.1   | 8.0   | 7.9   | 6.5   | 6.8  |
| AVG SPD  | 73.8              | 75.8  | 76.0  | 76.5  | 76.9  | 76.8  | 77.2  | 77.3  | 77.2  | 77.2  | 77.4  | 76.4  | 76.5 |
| 50% SPD  | 73.7              | 75.2  | 75.4  | 75.4  | 75.7  | 75.7  | 76.0  | 76.1  | 75.7  | 75.7  | 75.9  | 75.4  | 75.5 |
| 85% SPD  | 80.7              | 81.7  | 81.9  | 82.1  | 82.5  | 82.4  | 82.7  | 82.9  | 82.7  | 82.7  | 82.8  | 82.3  | 82.3 |
| %EXCD 55 | 96.1              | 99.2  | 99.3  | 99.2  | 99.3  | 99.4  | 99.4  | 99.4  | 99.3  | 99.3  | 99.4  | 99.0  | 99.0 |
| %EXCD 60 | 92.8              | 97.3  | 97.6  | 97.5  | 97.6  | 97.7  | 97.7  | 97.7  | 97.5  | 97.5  | 97.9  | 96.9  | 97.1 |
| %EXCD 65 | 84.7              | 91.1  | 91.6  | 91.6  | 91.9  | 92.1  | 92.3  | 92.4  | 91.6  | 91.8  | 92.8  | 91.1  | 91.2 |
| %EXCD 70 | 68.7              | 76.5  | 77.6  | 78.4  | 79.1  | 79.6  | 80.5  | 81.0  | 79.1  | 79.3  | 80.8  | 77.7  | 78.2 |
| %EXCD 75 | 43.8              | 51.1  | 52.4  | 52.3  | 54.3  | 54.7  | 56.3  | 57.1  | 54.7  | 54.6  | 55.7  | 52.2  | 53.3 |
| %EXCD 80 | 16.6              | 19.7  | 20.8  | 21.0  | 22.6  | 22.8  | 23.9  | 25.0  | 23.3  | 23.4  | 24.4  | 22.5  | 22.2 |
| %EXCD 85 | 4.9               | 5.4   | 5.2   | 6.9   | 7.4   | 6.8   | 7.4   | 7.5   | 8.1   | 8.0   | 7.9   | 6.5   | 6.8  |
|          | 5,375             | 5,985 | 6,977 | 6,728 | 6,830 | 8,480 | 9,827 | 9,845 | 7,681 | 7,043 | 6,855 | 6,546 |      |