

Idaho Transportation Department
Percent of MADT At Continuous Count Speed Sites

Site ID: 001540 140.380

Scheme ID: 6

Location: #023 US-95 4.1 Mi. N. of Council

County: ADAMS

Axle Factor Group: 2

Growth Factor Group: 1

Seasonal Factor Group: 6

FHWA Functional Class: 2

Speed Limit: 55

| SPEED | 1998 Traffic Year | | | | | | | | | | | | |
|----------|-------------------|-------|-------|-------|-------|-------|-------|-------|-----|-------|-------|-------|------|
| | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec | Avg |
| 0>-30 | 3.7 | 2.1 | 1.8 | 2.2 | 1.9 | 2.1 | 1.6 | 77.1 | . | 1.9 | 2.0 | 4.2 | 9.2 |
| 30>-35 | 2.8 | 1.0 | 0.9 | 0.9 | 0.8 | 0.9 | 0.8 | 0.6 | . | 0.9 | 1.2 | 3.0 | 1.2 |
| 35>-40 | 5.5 | 1.8 | 1.2 | 1.3 | 1.3 | 1.5 | 1.5 | 0.7 | . | 1.2 | 1.9 | 5.0 | 2.1 |
| 40>-45 | 9.1 | 3.8 | 3.0 | 2.8 | 3.9 | 4.7 | 4.9 | 1.1 | . | 3.9 | 4.8 | 7.7 | 4.5 |
| 45>-50 | 15.9 | 11.9 | 10.2 | 10.5 | 13.9 | 15.4 | 15.4 | 2.9 | . | 12.5 | 14.4 | 14.6 | 12.5 |
| 50>-55 | 25.8 | 27.7 | 27.5 | 28.0 | 30.6 | 31.4 | 33.4 | 5.9 | . | 29.7 | 30.1 | 26.6 | 27.0 |
| 55>-60 | 26.0 | 33.6 | 35.4 | 34.9 | 32.6 | 31.9 | 31.0 | 5.6 | . | 33.7 | 32.3 | 26.4 | 29.4 |
| 60>-65 | 9.2 | 14.6 | 15.8 | 15.2 | 12.2 | 9.8 | 9.1 | 2.1 | . | 12.8 | 10.6 | 9.8 | 11.0 |
| 65>-70 | 1.7 | 3.0 | 3.4 | 3.5 | 2.5 | 1.9 | 2.0 | 0.7 | . | 2.9 | 2.3 | 2.3 | 2.4 |
| 70>-75 | 0.2 | 0.4 | 0.5 | 0.5 | 0.3 | 0.3 | 0.3 | 0.3 | . | 0.3 | 0.3 | 0.3 | 0.3 |
| 75>-80 | 0.0 | 0.0 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.3 | . | 0.0 | 0.1 | 0.1 | 0.1 |
| 80>-85 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.3 | . | 0.0 | 0.0 | 0.1 | 0.1 |
| 85>-140 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 2.4 | . | 0.0 | 0.0 | 0.1 | 0.2 |
| AVG SPD | 50.5 | 54.0 | 54.6 | 54.4 | 53.6 | 53.0 | 53.1 | 25.4 | 0.0 | 53.9 | 53.1 | 50.9 | 50.6 |
| 50% SPD | 52.5 | 55.3 | 55.7 | 55.6 | 54.6 | 54.0 | 53.9 | . | . | 55.0 | 54.3 | 52.9 | 53.8 |
| 85% SPD | 59.3 | 61.1 | 61.5 | 61.4 | 60.0 | 59.5 | 59.4 | 52.2 | . | 60.5 | 59.7 | 59.5 | 59.8 |
| %EXCD 55 | 37.2 | 51.7 | 55.3 | 54.2 | 47.6 | 44.0 | 42.5 | 11.7 | . | 49.9 | 45.6 | 38.9 | 43.5 |
| %EXCD 60 | 11.2 | 18.1 | 19.9 | 19.3 | 15.0 | 12.1 | 11.4 | 6.1 | . | 16.2 | 13.3 | 12.6 | 14.1 |
| %EXCD 65 | 2.0 | 3.5 | 4.1 | 4.0 | 2.9 | 2.3 | 2.3 | 4.0 | . | 3.4 | 2.7 | 2.8 | 3.1 |
| %EXCD 70 | 0.3 | 0.4 | 0.6 | 0.6 | 0.4 | 0.4 | 0.4 | 3.3 | . | 0.4 | 0.4 | 0.5 | 0.7 |
| %EXCD 75 | 0.0 | 0.1 | 0.2 | 0.1 | 0.1 | 0.1 | 0.1 | 3.0 | . | 0.1 | 0.1 | 0.2 | 0.4 |
| %EXCD 80 | 0.0 | 0.0 | 0.0 | 0.1 | 0.0 | 0.0 | 0.0 | 2.7 | . | 0.1 | 0.0 | 0.1 | 0.3 |
| %EXCD 85 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 2.4 | . | 0.0 | 0.0 | 0.1 | 0.2 |
| | 1,027 | 1,217 | 1,241 | 1,319 | 1,534 | 1,849 | 2,168 | 1,811 | . | 1,481 | 1,416 | 1,103 | |