

Idaho Transportation Department  
Percent of MADT At Continuous Count Speed Sites

|  |                          |
|--|--------------------------|
| Site ID: 002230 135.950                                    | Scheme ID: 6             |
| Location: #028 SH-75 7.5 Mi. N. of Sun Valley Spur (Ketchu | County: BLAINE           |
| Axle Factor Group: 3                                       | Growth Factor Group: 2   |
| Seasonal Factor Group: 11                                  | FHWA Functional Class: 6 |
|  | Speed Limit: 55          |

| SPEED    | 1995 Traffic Year |      |      |      |      |       |       |       |       |       |      |      |      |
|----------|-------------------|------|------|------|------|-------|-------|-------|-------|-------|------|------|------|
|          | Jan               | Feb  | Mar  | Apr  | May  | Jun   | Jul   | Aug   | Sep   | Oct   | Nov  | Dec  | Avg  |
| 0>-30    | 3.3               | 1.7  | 1.5  | 1.5  | 1.3  | 0.7   | 0.4   | 0.4   | 0.6   | 0.8   | 1.1  | 2.9  | 1.3  |
| 30>-35   | 3.5               | 1.3  | 1.4  | 0.6  | 0.5  | 0.3   | 0.3   | 0.3   | 0.3   | 0.5   | 0.7  | 4.1  | 1.1  |
| 35>-40   | 8.6               | 3.3  | 3.3  | 0.9  | 1.0  | 0.7   | 0.7   | 0.7   | 0.7   | 0.8   | 1.2  | 9.9  | 2.6  |
| 40>-45   | 15.4              | 7.2  | 6.3  | 2.8  | 2.6  | 2.3   | 2.3   | 2.2   | 2.2   | 2.0   | 2.8  | 18.6 | 5.6  |
| 45>-50   | 20.2              | 13.1 | 11.5 | 5.3  | 6.5  | 6.3   | 7.2   | 6.3   | 6.1   | 5.9   | 6.2  | 20.4 | 9.6  |
| 50>-55   | 24.6              | 23.6 | 21.2 | 16.3 | 17.4 | 16.8  | 19.6  | 19.3  | 17.6  | 17.1  | 17.7 | 19.2 | 19.2 |
| 55>-60   | 16.8              | 27.2 | 26.7 | 30.2 | 30.5 | 34.0  | 37.7  | 34.3  | 33.3  | 31.9  | 30.1 | 13.2 | 28.8 |
| 60>-65   | 5.8               | 16.1 | 19.2 | 25.9 | 25.6 | 26.7  | 23.1  | 25.9  | 27.4  | 27.7  | 26.0 | 7.9  | 21.5 |
| 65>-70   | 1.4               | 4.4  | 6.6  | 10.7 | 9.8  | 8.8   | 6.6   | 7.6   | 8.4   | 9.4   | 9.8  | 2.7  | 7.2  |
| 70>-75   | 0.3               | 1.5  | 1.7  | 4.2  | 3.5  | 2.4   | 1.6   | 2.1   | 2.5   | 3.1   | 3.5  | 0.8  | 2.3  |
| 75>-80   | 0.1               | 0.4  | 0.5  | 1.1  | 1.0  | 0.7   | 0.4   | 0.5   | 0.6   | 0.6   | 0.8  | 0.1  | 0.6  |
| 80>-85   | 0.0               | 0.1  | 0.1  | 0.3  | 0.3  | 0.2   | 0.1   | 0.1   | 0.1   | 0.2   | 0.2  | 0.0  | 0.1  |
| 85>-140  | 0.0               | 0.1  | 0.1  | 0.2  | 0.2  | 0.1   | 0.0   | 0.1   | 0.1   | 0.1   | 0.1  | 0.0  | 0.1  |
| AVG SPD  | 48.5              | 53.8 | 54.8 | 58.2 | 57.9 | 58.0  | 57.2  | 57.7  | 58.0  | 58.1  | 57.8 | 48.3 | 55.7 |
| 50% SPD  | 49.8              | 54.9 | 55.9 | 58.7 | 58.4 | 58.4  | 57.6  | 58.0  | 58.4  | 58.6  | 58.4 | 48.5 | 56.8 |
| 85% SPD  | 57.8              | 62.3 | 63.4 | 65.7 | 64.9 | 64.5  | 63.6  | 64.1  | 64.4  | 64.7  | 64.9 | 58.7 | 63.9 |
| %EXCD 55 | 24.5              | 49.8 | 54.9 | 72.6 | 70.8 | 72.8  | 69.5  | 70.7  | 72.4  | 72.9  | 70.4 | 24.8 | 60.5 |
| %EXCD 60 | 7.7               | 22.6 | 28.2 | 42.4 | 40.3 | 38.9  | 31.8  | 36.4  | 39.1  | 41.0  | 40.3 | 11.6 | 31.7 |
| %EXCD 65 | 1.8               | 6.4  | 9.0  | 16.5 | 14.7 | 12.2  | 8.8   | 10.5  | 11.6  | 13.4  | 14.3 | 3.7  | 10.2 |
| %EXCD 70 | 0.4               | 2.0  | 2.4  | 5.9  | 4.9  | 3.4   | 2.2   | 2.8   | 3.3   | 3.9   | 4.5  | 1.0  | 3.1  |
| %EXCD 75 | 0.1               | 0.5  | 0.7  | 1.7  | 1.4  | 1.1   | 0.6   | 0.7   | 0.8   | 0.9   | 1.1  | 0.1  | 0.8  |
| %EXCD 80 | 0.0               | 0.2  | 0.2  | 0.6  | 0.4  | 0.3   | 0.1   | 0.2   | 0.2   | 0.2   | 0.3  | 0.1  | 0.2  |
| %EXCD 85 | 0.0               | 0.1  | 0.1  | 0.2  | 0.2  | 0.1   | 0.0   | 0.1   | 0.1   | 0.1   | 0.1  | 0.0  | 0.1  |
|          | 662               | 951  | 739  | 558  | 655  | 1,529 | 2,846 | 2,655 | 1,817 | 1,159 | 632  | 748  |      |