

Idaho Transportation Department  
Percent of MADT At Continuous Count Speed Sites

Site ID: 001540 022.720

Scheme ID: 6

Location: #038 US-95 3.6 Mi. S. of Jct SH-55 (Marsing)

County: OWYHEE

Axle Factor Group: 2

Growth Factor Group: 1

Seasonal Factor Group: 3

FHWA Functional Class: 2

Speed Limit: 65

| SPEED    | 1998 Traffic Year |       |       |       |       |       |       |       |       |       |       |       |      |
|----------|-------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
|          | Jan               | Feb   | Mar   | Apr   | May   | Jun   | Jul   | Aug   | Sep   | Oct   | Nov   | Dec   | Avg  |
| 0>-30    | 0.5               | 0.5   | 0.5   | 0.7   | 0.4   | 0.3   | 0.3   | 0.7   | 0.8   | 0.7   | 0.4   | 0.6   | 0.5  |
| 30>-35   | 0.2               | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.2   | 0.1  |
| 35>-40   | 0.5               | 0.4   | 0.2   | 0.2   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.2   | 0.4   | 0.2  |
| 40>-45   | 1.3               | 0.9   | 0.6   | 0.7   | 0.4   | 0.4   | 0.3   | 0.3   | 0.3   | 0.3   | 0.7   | 1.5   | 0.7  |
| 45>-50   | 4.2               | 3.4   | 2.5   | 2.6   | 1.5   | 1.3   | 1.3   | 1.1   | 1.3   | 1.4   | 2.4   | 3.5   | 2.2  |
| 50>-55   | 8.7               | 7.2   | 6.8   | 6.6   | 5.8   | 5.4   | 4.9   | 4.3   | 5.0   | 5.3   | 7.0   | 8.3   | 6.3  |
| 55>-60   | 17.4              | 16.4  | 17.3  | 17.0  | 16.3  | 16.6  | 15.4  | 13.5  | 13.9  | 14.1  | 14.8  | 15.5  | 15.7 |
| 60>-65   | 30.9              | 31.9  | 32.4  | 31.4  | 32.0  | 29.4  | 29.1  | 29.1  | 31.2  | 31.1  | 33.0  | 31.3  | 31.1 |
| 65>-70   | 24.2              | 26.7  | 27.2  | 27.2  | 29.7  | 31.2  | 31.7  | 32.0  | 30.3  | 29.4  | 26.3  | 25.0  | 28.4 |
| 70>-75   | 8.3               | 8.5   | 8.7   | 9.3   | 9.4   | 10.3  | 11.2  | 12.3  | 11.4  | 12.0  | 11.0  | 10.0  | 10.2 |
| 75>-80   | 2.8               | 2.8   | 2.7   | 2.9   | 3.1   | 3.5   | 3.9   | 4.3   | 3.6   | 3.5   | 2.9   | 2.6   | 3.2  |
| 80>-85   | 0.6               | 0.7   | 0.7   | 0.7   | 0.8   | 0.9   | 1.1   | 1.3   | 1.0   | 1.0   | 0.7   | 0.7   | 0.9  |
| 85>-140  | 0.4               | 0.5   | 0.4   | 0.4   | 0.4   | 0.4   | 0.5   | 1.0   | 1.0   | 1.0   | 0.6   | 0.4   | 0.6  |
| AVG SPD  | 62.2              | 62.9  | 63.1  | 63.1  | 63.8  | 64.2  | 64.6  | 65.0  | 64.5  | 64.5  | 63.6  | 62.6  | 63.7 |
| 50% SPD  | 62.8              | 63.3  | 63.4  | 63.5  | 64.0  | 64.4  | 64.7  | 65.1  | 64.6  | 64.5  | 63.7  | 63.2  | 63.9 |
| 85% SPD  | 69.4              | 69.5  | 69.5  | 69.7  | 69.8  | 70.1  | 70.8  | 71.6  | 70.9  | 71.1  | 70.1  | 69.7  | 70.0 |
| %EXCD 55 | 84.6              | 87.5  | 89.3  | 89.0  | 91.7  | 92.3  | 93.0  | 93.5  | 92.4  | 92.1  | 89.3  | 85.4  | 90.0 |
| %EXCD 60 | 67.1              | 71.1  | 72.0  | 72.0  | 75.4  | 75.7  | 77.6  | 79.9  | 78.5  | 78.0  | 74.5  | 70.0  | 74.3 |
| %EXCD 65 | 36.3              | 39.2  | 39.6  | 40.6  | 43.4  | 46.3  | 48.5  | 50.9  | 47.3  | 47.0  | 41.5  | 38.7  | 43.3 |
| %EXCD 70 | 12.1              | 12.5  | 12.4  | 13.4  | 13.7  | 15.1  | 16.7  | 18.8  | 17.0  | 17.5  | 15.2  | 13.6  | 14.8 |
| %EXCD 75 | 3.8               | 4.0   | 3.7   | 4.0   | 4.3   | 4.9   | 5.5   | 6.6   | 5.6   | 5.6   | 4.2   | 3.6   | 4.7  |
| %EXCD 80 | 1.0               | 1.2   | 1.0   | 1.1   | 1.2   | 1.4   | 1.6   | 2.2   | 2.0   | 2.1   | 1.3   | 1.0   | 1.4  |
| %EXCD 85 | 0.4               | 0.5   | 0.4   | 0.4   | 0.4   | 0.4   | 0.5   | 1.0   | 1.0   | 1.0   | 0.6   | 0.4   | 0.6  |
|          | 979               | 1,054 | 1,293 | 1,338 | 1,504 | 1,684 | 1,717 | 1,608 | 1,474 | 1,500 | 1,347 | 1,127 |      |