

Idaho Transportation Department
Percent of MADT At Continuous Count Speed Sites

Site ID: 002500 089.960

Scheme ID: 6

Location: #058 SH-28 0.1 Mile Southeast of Leadore

County: LEMHI

Axle Factor Group: 54

Growth Factor Group: 1

Seasonal Factor Group: 55

FHWA Functional Class: 6

Speed Limit: 35

| SPEED | 1999 Traffic Year | | | | | | | | | | | | |
|----------|-------------------|------|------|------|------|------|------|------|------|------|------|------|------|
| | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec | Avg |
| 0>-30 | 7.2 | 6.4 | 4.6 | 5.3 | 4.8 | 4.6 | 7.4 | 4.6 | 4.9 | 4.7 | 4.8 | 6.3 | 5.5 |
| 30>-35 | 11.0 | 10.2 | 10.0 | 11.3 | 10.8 | 11.6 | 12.8 | 11.7 | 12.9 | 11.7 | 10.5 | 11.9 | 11.4 |
| 35>-40 | 22.0 | 21.8 | 22.6 | 23.0 | 23.1 | 23.6 | 24.5 | 24.3 | 25.5 | 24.1 | 23.4 | 22.1 | 23.3 |
| 40>-45 | 24.1 | 24.8 | 25.7 | 24.9 | 25.3 | 24.9 | 24.2 | 25.7 | 25.3 | 26.1 | 25.3 | 25.3 | 25.1 |
| 45>-50 | 19.4 | 19.5 | 19.5 | 18.6 | 18.7 | 18.1 | 16.6 | 17.9 | 16.9 | 18.0 | 19.2 | 18.6 | 18.4 |
| 50>-55 | 10.3 | 10.7 | 10.9 | 10.2 | 10.5 | 10.2 | 8.7 | 9.8 | 9.2 | 9.6 | 10.4 | 9.7 | 10.0 |
| 55>-60 | 3.9 | 4.3 | 4.3 | 4.6 | 4.2 | 4.4 | 3.8 | 3.7 | 3.4 | 3.8 | 4.0 | 4.0 | 4.0 |
| 60>-65 | 1.3 | 1.6 | 1.5 | 1.4 | 1.5 | 1.5 | 1.2 | 1.5 | 1.3 | 1.3 | 1.4 | 1.4 | 1.4 |
| 65>-70 | 0.6 | 0.5 | 0.6 | 0.5 | 0.7 | 0.7 | 0.5 | 0.6 | 0.4 | 0.5 | 0.7 | 0.5 | 0.6 |
| 70>-75 | 0.2 | 0.1 | 0.1 | 0.2 | 0.2 | 0.1 | 0.1 | 0.1 | 0.1 | 0.2 | 0.1 | 0.1 | 0.1 |
| 75>-80 | 0.0 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.0 | 0.1 | 0.1 | 0.1 | 0.1 |
| 80>-85 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 85>-140 | 0.0 | 0.0 | 0.0 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| AVG SPD | 41.4 | 41.8 | 42.4 | 41.9 | 42.2 | 42.1 | 40.7 | 41.8 | 41.3 | 41.7 | 42.1 | 41.4 | 41.7 |
| 50% SPD | 42.0 | 42.3 | 42.5 | 42.1 | 42.2 | 42.0 | 41.1 | 41.8 | 41.3 | 41.8 | 42.2 | 41.9 | 42.0 |
| 85% SPD | 50.6 | 51.1 | 51.2 | 51.0 | 51.1 | 51.0 | 49.8 | 50.4 | 49.8 | 50.2 | 50.8 | 50.4 | 50.6 |
| %EXCD 55 | 5.9 | 6.6 | 6.7 | 6.8 | 6.8 | 6.9 | 5.8 | 6.0 | 5.3 | 5.9 | 6.3 | 6.1 | 6.3 |
| %EXCD 60 | 2.1 | 2.3 | 2.4 | 2.2 | 2.5 | 2.5 | 2.0 | 2.3 | 1.9 | 2.1 | 2.3 | 2.1 | 2.2 |
| %EXCD 65 | 0.8 | 0.7 | 0.9 | 0.8 | 1.0 | 1.0 | 0.8 | 0.8 | 0.7 | 0.8 | 0.9 | 0.7 | 0.8 |
| %EXCD 70 | 0.2 | 0.2 | 0.3 | 0.3 | 0.3 | 0.3 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 |
| %EXCD 75 | 0.0 | 0.1 | 0.1 | 0.2 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 |
| %EXCD 80 | 0.0 | 0.0 | 0.0 | 0.1 | 0.1 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| %EXCD 85 | 0.0 | 0.0 | 0.0 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| | 340 | 357 | 455 | 457 | 526 | 589 | 749 | 714 | 661 | 630 | 586 | 393 | |