

Monthly WIM Distribution for 09/2011

Site Names: 00079, Downey WIM
 County: Bannock (3)
 Funct. Class: R Principal Arterial - Interstate
 Location: I-15 3.2 Mi. S of Jct SH-40

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
Roadway	Num	13	3,217	1,329	80	427	98	6	35	841	93	14	15	152	160	0
	Flex	0.00	0.00	0.00	1.53	0.43	1.34	2.90	0.60	1.84	1.31	1.59	1.01	1.80	1.08	0.00
	Rigid	0.00	0.00	0.00	2.00	0.47	2.30	6.15	0.72	3.06	2.67	1.61	1.15	2.72	1.26	0.00
	GVW	4.2	3.6	6.0	31.0	18.5	39.5	59.0	30.6	59.4	64.3	52.8	55.6	72.6	21.8	0.0
S DIR	Num	5	986	622	34	121	13	0	14	364	56	7	8	84	58	0
	Flex	0.00	0.00	0.00	0.97	0.18	0.35	0.40	0.39	1.15	0.67	0.40	0.32	1.10	0.32	0.00
	Rigid	0.00	0.00	0.00	1.24	0.20	0.52	0.80	0.43	1.86	1.30	0.38	0.37	1.69	0.43	0.00
	GVW	4.2	3.2	5.1	25.6	18.5	22.7	126.0	24.6	49.7	52.1	37.5	39.6	55.8	14.8	0.0
N DIR	Num	8	2,231	707	47	306	85	6	22	478	37	7	7	68	103	0
	Flex	0.00	0.00	0.00	1.93	0.53	1.49	3.15	0.72	2.37	2.29	2.88	1.75	2.68	1.50	0.00
	Rigid	0.00	0.00	0.00	2.54	0.58	2.57	6.67	0.89	3.96	4.77	2.93	2.00	4.03	1.73	0.00
	GVW	4.2	3.8	6.8	34.6	18.5	41.9	63.7	33.9	66.8	83.2	70.7	72.5	93.3	25.7	0.0
S 1	Num	4	985	616	33	115	13	0	14	364	56	7	8	84	45	0
	Flex	0.00	0.00	0.00	0.97	0.19	0.35	0.40	0.39	1.15	0.67	0.40	0.32	1.10	0.41	0.00
	Rigid	0.00	0.00	0.00	1.25	0.21	0.52	0.80	0.43	1.86	1.30	0.38	0.37	1.69	0.55	0.00
	GVW	5.3	3.2	5.1	25.7	18.8	22.7	126.0	24.6	49.7	52.1	37.5	39.6	55.8	17.1	0.0
S 2	Num	1	1	5	1	5	0	0	0	0	0	0	0	0	13	0
	Flex	0.03	0.01	0.00	1.63	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00
	Rigid	0.03	0.01	0.00	1.66	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00
	GVW	7.7	7.9	6.1	39.3	12.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	6.6	0.0
N 2	Num	1	554	174	2	9	1	0	1	12	1	0	0	2	4	0
	Flex	0.00	0.00	0.00	1.65	0.16	0.24	1.57	0.08	0.32	0.64	12.75	0.97	0.65	0.15	0.00
	Rigid	0.00	0.00	0.00	2.03	0.16	0.33	2.70	0.09	0.46	1.25	12.12	0.99	1.22	0.18	0.00
	GVW	4.9	3.1	4.5	29.5	16.1	41.2	283.5	33.6	39.2	64.4	735.0	255.5	61.6	14.7	0.0
N 1	Num	7	1,677	533	44	297	84	5	21	466	36	7	7	66	99	0
	Flex	0.00	0.00	0.01	1.99	0.54	1.51	3.22	0.74	2.43	2.34	2.87	1.75	2.74	1.56	0.00
	Rigid	0.00	0.00	0.01	2.62	0.60	2.59	6.83	0.91	4.06	4.88	2.91	2.00	4.12	1.79	0.00
	GVW	4.3	4.1	7.5	35.2	18.6	42.1	64.3	34.2	67.5	83.8	70.0	71.7	94.3	26.2	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9