

Monthly WIM Distribution for 02/2011

Site Names: 00096, Rigby WIM
 County: Jefferson (26)
 Funct. Class: R Principal Arterial - Other
 Location: US-20 1.4 Mi. S of US-20B

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
Roadway	Num	5	13,169	5,127	82	446	44	2	51	552	91	2	4	105	89	0
	Flex	0.00	0.00	0.00	1.28	0.26	1.01	5.14	0.67	1.99	1.82	1.80	1.30	3.31	0.36	0.00
	Rigid	0.00	0.00	0.00	1.48	0.28	1.49	11.55	0.78	3.27	3.54	1.81	1.48	5.40	0.49	0.00
	GVW	3.5	3.2	5.2	27.5	15.6	32.6	89.5	32.4	60.5	64.8	60.2	61.6	87.9	15.3	0.0
SW DIR	Num	2	6,635	2,556	38	266	21	1	26	259	44	1	2	66	57	0
	Flex	0.00	0.00	0.00	1.21	0.26	0.94	7.81	0.46	2.37	1.75	1.89	1.56	3.92	0.36	0.00
	Rigid	0.00	0.00	0.00	1.39	0.28	1.42	18.22	0.55	3.94	3.36	1.89	1.86	6.32	0.47	0.00
	GVW	3.7	3.3	5.6	26.5	15.3	32.0	119.6	29.9	65.2	60.5	68.1	68.8	92.0	15.6	0.0
NE DIR	Num	3	6,534	2,571	44	181	23	1	26	293	47	1	2	39	32	0
	Flex	0.00	0.00	0.00	1.34	0.26	1.07	8.52	0.87	1.65	1.89	3.19	1.31	2.32	0.37	0.00
	Rigid	0.00	0.00	0.00	1.55	0.27	1.53	19.21	1.01	2.68	3.73	3.23	1.42	3.93	0.56	0.00
	GVW	3.4	3.1	4.8	28.4	16.0	32.6	128.6	34.7	56.3	69.0	99.1	69.8	80.7	14.6	0.0
SW 1	Num	2	4,871	1,879	33	232	19	1	22	234	38	1	2	57	52	0
	Flex	0.00	0.00	0.00	1.13	0.25	0.86	12.48	0.46	2.37	1.68	1.89	1.90	3.93	0.37	0.00
	Rigid	0.00	0.00	0.00	1.30	0.27	1.32	29.38	0.55	3.95	3.24	1.89	2.27	6.32	0.47	0.00
	GVW	4.2	3.3	5.8	26.3	15.2	31.9	175.7	29.9	65.6	59.4	67.1	78.6	92.4	15.8	0.0
SW 2	Num	1	1,764	678	5	33	2	0	3	26	6	0	0	10	5	0
	Flex	0.00	0.00	0.00	1.86	0.30	1.68	24.83	0.49	2.31	2.41	0.00	4.10	4.03	0.37	0.00
	Rigid	0.00	0.00	0.00	2.15	0.32	2.43	46.15	0.62	3.84	4.71	0.00	4.55	6.81	0.66	0.00
	GVW	10.2	3.1	5.0	29.5	15.7	38.7	372.7	29.3	61.7	64.5	0.0	362.2	89.5	13.7	0.0
NE 2	Num	1	1,632	584	3	18	2	0	2	23	5	0	0	7	8	0
	Flex	0.00	0.00	0.00	1.23	0.18	0.70	0.00	0.52	1.17	1.69	6.39	0.00	1.65	0.25	0.00
	Rigid	0.00	0.00	0.00	1.45	0.19	1.00	0.00	0.62	1.84	3.44	6.06	0.00	2.70	0.36	0.00
	GVW	5.0	3.0	4.6	30.0	15.0	31.5	0.0	33.9	52.5	71.7	373.8	0.0	67.6	5.7	0.0
NE 1	Num	2	4,902	1,987	40	163	21	1	23	271	43	1	2	32	24	0
	Flex	0.00	0.00	0.00	1.36	0.27	1.11	10.13	0.91	1.69	1.97	3.36	1.50	2.49	0.42	0.00
	Rigid	0.00	0.00	0.00	1.57	0.28	1.59	22.88	1.05	2.75	3.89	3.42	1.63	4.26	0.66	0.00
	GVW	3.2	3.1	4.9	28.4	16.2	33.0	154.0	35.0	56.6	70.2	98.2	77.4	83.3	17.6	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9