

## Monthly WIM Distribution for 03/2011

Site Names: 00096, Rigby WIM  
 County: Jefferson (26)  
 Funct. Class: R Principal Arterial - Other  
 Location: US-20 1.4 Mi. S of US-20B

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
<b>Roadway</b>	<b>Num</b>	7	13,750	5,205	86	365	74	6	50	620	143	3	4	98	54	0
	<b>Flex</b>	0.00	0.00	0.00	1.25	0.30	1.22	5.52	0.59	1.91	1.93	0.99	0.61	2.84	0.44	0.00
	<b>Rigid</b>	0.00	0.00	0.00	1.46	0.33	1.85	10.88	0.67	3.13	3.76	0.99	0.67	4.73	0.65	0.00
	<b>GVW</b>	3.5	3.1	5.1	27.6	16.3	34.4	88.2	32.2	59.3	68.1	51.3	51.0	84.8	17.0	0.0
<b>SW DIR</b>	<b>Num</b>	3	6,943	2,611	41	214	39	1	25	287	68	1	2	63	21	0
	<b>Flex</b>	0.00	0.00	0.00	1.63	0.31	0.93	12.06	0.46	2.58	2.71	1.06	0.64	3.63	0.54	0.00
	<b>Rigid</b>	0.00	0.00	0.00	1.92	0.34	1.40	26.93	0.55	4.33	5.35	1.09	0.74	6.05	0.83	0.00
	<b>GVW</b>	3.4	3.2	5.6	29.2	16.1	32.6	132.5	31.2	67.2	81.2	51.2	56.2	92.3	20.0	0.0
<b>NE DIR</b>	<b>Num</b>	4	6,808	2,594	45	151	35	5	25	333	75	2	2	36	33	0
	<b>Flex</b>	0.00	0.00	0.00	0.91	0.30	1.55	7.12	0.71	1.32	1.22	1.07	0.75	1.45	0.39	0.00
	<b>Rigid</b>	0.00	0.00	0.00	1.05	0.31	2.36	13.47	0.79	2.09	2.30	1.04	0.78	2.45	0.55	0.00
	<b>GVW</b>	3.8	3.1	4.5	26.0	16.7	36.5	106.4	33.0	52.4	56.1	58.9	61.3	71.3	15.3	0.0
<b>SW 1</b>	<b>Num</b>	2	5,043	1,939	36	179	35	1	22	258	58	1	2	54	17	0
	<b>Flex</b>	0.00	0.00	0.00	1.41	0.31	0.86	13.05	0.47	2.48	2.57	1.02	0.65	3.35	0.53	0.00
	<b>Rigid</b>	0.00	0.00	0.00	1.67	0.33	1.32	29.17	0.57	4.17	5.07	1.04	0.77	5.53	0.81	0.00
	<b>GVW</b>	3.5	3.2	5.8	28.4	16.1	32.3	143.0	31.4	66.7	80.3	49.9	56.9	91.2	19.9	0.0
<b>SW 2</b>	<b>Num</b>	0	1,899	672	6	35	4	0	3	30	11	0	0	9	4	0
	<b>Flex</b>	0.00	0.00	0.00	3.10	0.31	1.48	0.00	0.63	3.45	3.53	0.00	1.56	5.69	0.86	0.00
	<b>Rigid</b>	0.00	0.00	0.00	3.80	0.34	2.07	0.00	0.80	5.72	7.07	0.00	1.64	10.09	1.45	0.00
	<b>GVW</b>	8.9	3.1	5.2	33.3	16.0	35.0	0.0	33.4	71.0	85.3	0.0	156.6	98.1	18.1	0.0
<b>NE 2</b>	<b>Num</b>	1	1,710	581	4	18	2	0	2	29	10	0	0	6	7	0
	<b>Flex</b>	0.00	0.00	0.00	1.22	0.25	1.22	19.25	0.77	1.21	1.06	0.00	5.40	1.52	0.22	0.00
	<b>Rigid</b>	0.00	0.00	0.00	1.35	0.26	1.99	38.40	0.82	1.93	2.02	0.00	5.63	2.55	0.29	0.00
	<b>GVW</b>	5.4	3.0	4.5	26.3	16.1	34.6	567.0	42.7	52.1	52.3	0.0	430.5	66.6	7.4	0.0
<b>NE 1</b>	<b>Num</b>	4	5,098	2,013	41	133	33	4	23	304	65	2	2	30	26	0
	<b>Flex</b>	0.00	0.00	0.00	0.89	0.30	1.58	7.29	0.72	1.33	1.27	1.07	0.70	1.46	0.44	0.00
	<b>Rigid</b>	0.00	0.00	0.00	1.03	0.32	2.41	13.66	0.80	2.11	2.38	1.04	0.73	2.49	0.63	0.00
	<b>GVW</b>	3.7	3.1	4.5	26.0	16.8	37.0	106.8	33.1	52.4	56.9	58.1	58.1	71.9	17.4	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9