

Monthly WIM Distribution for 04/2011

Site Names: 00096, Rigby WIM
 County: Jefferson (26)
 Funct. Class: R Principal Arterial - Other
 Location: US-20 1.4 Mi. S of US-20B

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
Roadway	Num	13	14,347	5,487	88	378	95	5	51	688	167	5	5	97	56	0
	Flex	0.00	0.00	0.00	1.15	0.31	1.25	4.10	0.54	1.76	1.72	0.87	0.72	2.17	0.62	0.00
	Rigid	0.00	0.00	0.00	1.32	0.33	2.07	8.45	0.64	2.90	3.37	0.88	0.79	3.74	0.88	0.00
	GVW	3.3	3.1	5.1	27.0	17.1	34.0	71.7	31.7	58.3	67.0	46.1	54.1	80.7	20.0	0.0
SW DIR	Num	5	7,220	2,767	42	193	48	1	26	319	79	2	2	62	21	0
	Flex	0.00	0.00	0.00	1.14	0.27	1.24	4.65	0.37	2.17	2.26	0.55	0.47	2.46	0.60	0.00
	Rigid	0.00	0.00	0.00	1.32	0.29	2.08	9.96	0.45	3.63	4.50	0.57	0.53	4.18	0.87	0.00
	GVW	3.1	3.2	5.4	26.9	16.4	34.9	88.9	30.1	63.4	79.5	45.8	53.1	82.9	20.1	0.0
NE DIR	Num	8	7,126	2,720	46	186	46	4	25	370	88	3	3	35	35	0
	Flex	0.00	0.00	0.00	1.16	0.35	1.26	5.20	0.71	1.40	1.23	1.30	1.00	1.67	0.64	0.00
	Rigid	0.00	0.00	0.00	1.32	0.38	2.05	10.81	0.82	2.27	2.34	1.30	1.08	3.01	0.89	0.00
	GVW	3.5	3.1	4.7	27.1	17.7	33.1	78.1	33.0	53.8	55.6	60.4	58.7	77.1	19.8	0.0
SW 1	Num	4	5,142	2,047	36	157	44	1	23	282	66	2	2	53	16	0
	Flex	0.00	0.00	0.00	0.98	0.27	1.23	5.34	0.38	2.10	2.06	0.51	0.47	2.20	0.58	0.00
	Rigid	0.00	0.00	0.00	1.13	0.28	2.10	11.33	0.47	3.51	4.11	0.54	0.54	3.73	0.84	0.00
	GVW	3.1	3.2	5.5	25.9	16.4	34.9	109.0	30.8	63.2	77.9	45.0	52.5	81.4	20.9	0.0
SW 2	Num	1	2,078	719	6	36	5	0	3	37	13	0	0	9	5	0
	Flex	0.00	0.00	0.00	2.19	0.30	1.33	0.00	0.44	2.71	3.29	2.06	2.36	4.23	0.74	0.00
	Rigid	0.00	0.00	0.00	2.64	0.33	1.96	0.00	0.52	4.49	6.52	1.98	2.53	7.47	1.17	0.00
	GVW	5.6	3.1	5.0	33.2	16.2	36.4	0.0	31.0	64.9	87.8	132.0	317.6	91.5	17.0	0.0
NE 2	Num	1	1,836	619	5	18	3	1	1	33	13	0	0	6	6	0
	Flex	0.00	0.00	0.00	1.27	0.32	0.79	8.65	1.77	1.12	0.83	25.96	4.47	1.70	0.35	0.00
	Rigid	0.00	0.00	0.00	1.47	0.34	1.23	17.09	2.07	1.75	1.56	28.09	4.72	2.91	0.47	0.00
	GVW	5.4	3.0	4.5	28.2	16.8	30.6	122.1	51.1	49.9	51.7	472.5	279.1	70.2	9.2	0.0
NE 1	Num	7	5,291	2,102	41	168	43	3	24	336	74	3	3	29	29	0
	Flex	0.00	0.00	0.00	1.15	0.35	1.30	5.46	0.71	1.43	1.31	1.20	1.05	1.69	0.70	0.00
	Rigid	0.00	0.00	0.00	1.30	0.38	2.12	11.39	0.82	2.32	2.50	1.19	1.14	3.10	0.98	0.00
	GVW	3.5	3.1	4.8	26.9	17.8	33.4	77.6	33.4	54.3	56.5	58.5	61.7	78.1	22.0	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9