

Monthly WIM Distribution for 05/2011

Site Names: 00096, Rigby WIM
 County: Jefferson (26)
 Funct. Class: R Principal Arterial - Other
 Location: US-20 1.4 Mi. S of US-20B

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
Roadway	Num	34	14,570	5,677	94	416	97	7	54	676	113	3	7	88	74	0
	Flex	0.00	0.00	0.00	1.21	0.34	1.01	2.11	0.53	1.66	1.57	0.79	0.82	1.87	0.88	0.00
	Rigid	0.00	0.00	0.00	1.43	0.36	1.65	4.49	0.64	2.72	3.09	0.78	0.93	3.21	1.14	0.00
	GVW	3.6	3.1	5.1	28.0	17.8	32.9	69.8	31.2	58.8	66.9	49.0	54.9	78.1	22.4	0.0
SW DIR	Num	13	7,309	2,847	44	209	44	1	27	321	56	2	4	55	27	0
	Flex	0.00	0.00	0.00	1.19	0.30	0.89	4.26	0.41	1.92	1.87	0.57	0.53	1.90	0.73	0.00
	Rigid	0.00	0.00	0.00	1.38	0.32	1.44	9.43	0.51	3.17	3.68	0.55	0.62	3.21	1.02	0.00
	GVW	3.3	3.1	5.4	27.4	17.0	31.6	124.7	29.8	61.3	72.3	49.8	49.2	73.4	18.1	0.0
NE DIR	Num	21	7,262	2,830	50	207	53	6	27	355	57	2	3	33	48	0
	Flex	0.00	0.00	0.00	1.23	0.39	1.10	2.11	0.65	1.43	1.27	1.23	1.18	1.88	0.97	0.00
	Rigid	0.00	0.00	0.00	1.47	0.41	1.83	4.46	0.76	2.31	2.50	1.22	1.30	3.36	1.24	0.00
	GVW	3.8	3.0	4.9	28.4	18.7	34.0	65.7	32.4	56.5	61.5	61.7	62.7	85.8	24.7	0.0
SW 1	Num	11	5,193	2,118	38	177	40	1	24	285	48	2	3	47	20	0
	Flex	0.00	0.00	0.00	1.09	0.29	0.86	4.10	0.41	1.91	1.75	0.52	0.52	1.80	0.70	0.00
	Rigid	0.00	0.00	0.00	1.25	0.31	1.39	9.18	0.51	3.16	3.45	0.50	0.62	3.02	1.01	0.00
	GVW	3.4	3.2	5.6	26.9	17.0	31.7	121.1	30.0	61.6	70.5	49.5	50.0	72.8	19.3	0.0
SW 2	Num	2	2,116	729	6	33	5	0	3	36	8	0	0	8	6	0
	Flex	0.00	0.00	0.00	1.87	0.33	1.13	0.00	0.47	2.03	2.65	0.00	3.10	2.80	0.86	0.00
	Rigid	0.00	0.00	0.00	2.28	0.35	1.75	0.00	0.55	3.29	5.22	0.00	3.29	5.06	1.13	0.00
	GVW	4.2	3.0	4.9	30.2	16.7	30.6	0.0	30.6	59.1	82.5	0.0	196.9	78.6	14.2	0.0
NE 2	Num	2	1,913	660	6	23	3	1	2	39	8	0	0	6	7	0
	Flex	0.00	0.00	0.00	1.21	0.33	0.58	3.80	0.68	1.22	0.79	0.00	8.40	2.31	0.60	0.00
	Rigid	0.00	0.00	0.00	1.40	0.35	0.91	9.46	0.72	1.91	1.55	0.00	8.81	3.90	0.75	0.00
	GVW	3.8	3.0	4.6	29.0	17.5	26.5	160.3	43.1	53.6	51.5	0.0	486.5	86.5	14.7	0.0
NE 1	Num	20	5,348	2,169	44	183	49	5	24	316	50	1	3	28	41	0
	Flex	0.00	0.00	0.00	1.24	0.39	1.13	2.31	0.67	1.46	1.36	1.36	1.17	1.83	1.04	0.00
	Rigid	0.00	0.00	0.00	1.49	0.42	1.88	4.84	0.78	2.36	2.67	1.34	1.29	3.32	1.33	0.00
	GVW	3.8	3.0	5.0	28.3	18.9	34.4	70.3	32.7	56.9	63.2	67.5	62.1	85.7	26.3	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9