

Monthly WIM Distribution for 06/2011

Site Names: 00096, Rigby WIM
 County: Jefferson (26)
 Funct. Class: R Principal Arterial - Other
 Location: US-20 1.4 Mi. S of US-20B

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
Roadway	Num	80	15,460	6,352	104	563	167	14	63	631	114	3	6	75	133	0
	Flex	0.00	0.00	0.00	1.22	0.34	1.09	1.54	0.55	1.64	1.45	0.87	0.66	1.70	0.92	0.00
	Rigid	0.00	0.00	0.00	1.50	0.37	1.84	3.36	0.67	2.69	2.86	0.84	0.72	3.00	1.08	0.00
	GVW	3.7	3.1	5.4	29.5	18.0	35.2	59.0	31.7	58.6	66.0	52.9	54.4	79.1	22.1	0.0
SW DIR	Num	30	7,718	3,159	48	267	63	2	32	321	64	1	3	45	44	0
	Flex	0.00	0.00	0.00	1.17	0.30	0.69	2.80	0.38	1.79	1.30	0.94	0.51	1.71	0.76	0.00
	Rigid	0.00	0.00	0.00	1.40	0.32	1.11	5.72	0.47	2.97	2.55	0.93	0.58	2.89	0.92	0.00
	GVW	3.5	3.1	5.6	28.7	17.4	31.4	98.5	30.1	60.5	62.9	61.7	49.9	74.6	21.0	0.0
NE DIR	Num	50	7,743	3,194	56	296	104	12	32	310	51	1	3	31	89	0
	Flex	0.00	0.00	0.00	1.26	0.39	1.33	1.66	0.72	1.48	1.64	1.34	0.83	1.67	1.01	0.00
	Rigid	0.00	0.00	0.00	1.58	0.42	2.28	3.66	0.87	2.40	3.24	1.30	0.89	3.18	1.17	0.00
	GVW	3.9	3.1	5.1	30.2	18.7	37.6	60.7	33.0	56.6	69.7	77.8	62.5	85.2	22.7	0.0
SW 1	Num	27	5,373	2,326	40	234	56	2	28	281	54	1	3	40	38	0
	Flex	0.00	0.00	0.00	1.08	0.30	0.72	2.87	0.39	1.82	1.26	0.94	0.54	1.61	0.81	0.00
	Rigid	0.00	0.00	0.00	1.28	0.32	1.16	5.90	0.49	3.03	2.49	0.93	0.62	2.76	0.98	0.00
	GVW	3.5	3.2	5.9	28.1	17.4	31.8	92.2	30.5	61.1	62.7	60.2	52.1	73.9	21.8	0.0
SW 2	Num	3	2,345	833	8	33	7	0	4	39	10	0	0	5	6	0
	Flex	0.00	0.00	0.00	1.62	0.31	0.50	2.89	0.30	1.57	1.54	0.00	1.80	3.05	0.53	0.00
	Rigid	0.00	0.00	0.00	1.96	0.34	0.71	5.10	0.36	2.52	3.02	0.00	1.99	4.94	0.69	0.00
	GVW	3.7	3.0	4.7	31.0	16.8	27.8	123.7	26.5	56.0	63.3	0.0	201.6	91.0	16.1	0.0
NE 2	Num	5	2,209	790	6	32	6	1	3	36	7	0	0	4	10	0
	Flex	0.00	0.00	0.00	0.96	0.25	0.66	4.96	0.59	1.04	0.84	0.00	5.24	2.08	0.93	0.00
	Rigid	0.00	0.00	0.00	1.13	0.26	1.00	11.65	0.67	1.62	1.69	0.00	5.42	4.16	1.11	0.00
	GVW	3.7	3.0	4.6	29.3	16.9	30.4	125.6	30.4	50.3	58.3	0.0	504.0	84.4	14.8	0.0
NE 1	Num	45	5,533	2,404	50	264	98	11	29	274	44	1	3	27	78	0
	Flex	0.00	0.00	0.00	1.30	0.40	1.38	1.71	0.74	1.54	1.77	1.25	0.84	1.71	1.02	0.00
	Rigid	0.00	0.00	0.00	1.65	0.44	2.37	3.77	0.90	2.50	3.50	1.20	0.90	3.25	1.18	0.00
	GVW	3.9	3.1	5.3	30.4	18.9	38.2	61.5	33.7	57.5	71.5	70.3	62.0	86.5	23.8	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9