

Monthly WIM Distribution for 10/2011

Site Names: 00096, Rigby WIM
 County: Jefferson (26)
 Funct. Class: R Principal Arterial - Other
 Location: US-20 1.4 Mi. S of US-20B

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
Roadway	Num	21	14,637	5,956	98	411	87	6	58	689	114	4	6	99	87	0
	Flex	0.00	0.00	0.00	0.97	0.26	0.89	2.10	0.52	1.35	1.34	0.73	0.78	1.90	0.51	0.00
	Rigid	0.00	0.00	0.00	1.13	0.27	1.37	4.36	0.60	2.14	2.63	0.71	0.85	3.03	0.69	0.00
	GVW	3.8	3.1	4.8	26.5	17.1	30.8	66.1	29.9	54.5	60.7	42.8	54.9	76.0	18.8	0.0
SW DIR	Num	8	7,390	3,049	47	184	41	1	29	333	59	2	3	60	37	0
	Flex	0.00	0.00	0.00	0.87	0.26	0.58	3.62	0.39	1.42	0.93	0.71	0.77	2.20	0.54	0.00
	Rigid	0.00	0.00	0.00	0.99	0.28	0.83	7.96	0.47	2.23	1.78	0.70	0.86	3.21	0.73	0.00
	GVW	3.5	3.1	4.9	25.1	17.3	27.7	74.6	27.7	56.1	51.7	45.4	53.5	78.7	20.4	0.0
NE DIR	Num	13	7,248	2,906	51	227	47	5	29	356	55	2	3	40	50	0
	Flex	0.00	0.00	0.00	1.07	0.26	1.15	2.50	0.65	1.29	1.80	1.05	0.82	1.45	0.51	0.00
	Rigid	0.00	0.00	0.00	1.26	0.27	1.85	5.36	0.74	2.06	3.56	1.02	0.87	2.80	0.69	0.00
	GVW	3.9	3.1	4.8	27.8	17.0	33.5	71.0	32.0	53.0	70.5	59.6	61.0	71.6	17.8	0.0
SW 1	Num	6	5,348	2,272	40	155	36	1	25	299	52	2	3	54	31	0
	Flex	0.00	0.00	0.00	0.78	0.25	0.51	4.54	0.39	1.36	0.82	0.70	0.77	2.15	0.52	0.00
	Rigid	0.00	0.00	0.00	0.88	0.26	0.73	9.95	0.47	2.15	1.60	0.69	0.86	3.14	0.71	0.00
	GVW	3.6	3.1	5.0	24.3	17.3	27.4	93.7	27.7	55.8	50.8	44.4	52.1	78.2	20.7	0.0
SW 2	Num	2	2,042	777	7	29	5	0	4	34	8	0	0	6	6	0
	Flex	0.00	0.00	0.00	1.40	0.32	1.17	11.27	0.43	1.95	1.74	0.00	0.00	2.92	0.65	0.00
	Rigid	0.00	0.00	0.00	1.66	0.34	1.60	17.96	0.49	2.98	3.23	0.00	0.00	4.42	0.87	0.00
	GVW	4.3	3.0	4.6	29.0	17.6	30.2	304.5	28.9	59.0	58.1	0.0	0.0	84.9	17.9	0.0
NE 2	Num	2	1,904	694	4	23	4	0	2	36	7	0	0	8	8	0
	Flex	0.00	0.00	0.00	1.50	0.21	1.20	10.85	0.58	1.15	1.22	0.00	4.94	1.13	0.09	0.00
	Rigid	0.00	0.00	0.00	1.74	0.22	1.88	26.40	0.64	1.81	2.39	0.00	5.03	2.01	0.11	0.00
	GVW	3.5	3.0	4.5	31.3	16.0	33.8	437.5	38.7	51.0	63.6	0.0	423.5	59.1	9.3	0.0
NE 1	Num	11	5,344	2,212	46	204	43	5	28	321	48	1	3	32	42	0
	Flex	0.00	0.00	0.00	1.04	0.26	1.15	2.64	0.66	1.31	1.90	1.21	0.81	1.58	0.59	0.00
	Rigid	0.00	0.00	0.00	1.23	0.28	1.85	5.66	0.75	2.09	3.77	1.18	0.86	3.13	0.80	0.00
	GVW	4.0	3.1	4.8	27.6	17.1	33.6	72.5	32.1	53.2	72.1	68.2	60.1	74.8	19.4	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9