

## Monthly WIM Distribution for 04/2011

Site Names: 00115, Wolf Lodge WIM  
 County: Kootenai (28)  
 Funct. Class: R Principal Arterial - Interstate  
 Location: I-90 1.3 Mi. E of Jct SH-97

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
<b>Roadway</b>	<b>Num</b>	5	5,341	2,590	61	462	26	2	36	1,297	210	12	31	84	48	0
	<b>Flex</b>	0.00	0.00	0.00	1.42	0.18	0.96	2.90	0.71	2.70	1.90	2.65	1.50	2.56	1.31	0.00
	<b>Rigid</b>	0.00	0.00	0.00	1.71	0.19	1.54	6.44	0.81	4.50	3.96	2.70	1.72	4.69	1.82	0.00
	<b>GVW</b>	4.0	3.4	6.2	30.0	15.9	35.0	63.9	34.0	73.2	78.4	64.6	68.9	93.0	35.3	0.0
<b>W DIR</b>	<b>Num</b>	3	2,690	1,285	29	245	12	1	18	617	102	6	17	47	24	0
	<b>Flex</b>	0.00	0.00	0.00	1.46	0.17	0.87	3.64	0.66	2.60	3.01	2.58	1.05	2.36	1.34	0.00
	<b>Rigid</b>	0.00	0.00	0.00	1.79	0.18	1.42	7.07	0.74	4.35	6.40	2.65	1.23	4.65	1.90	0.00
	<b>GVW</b>	4.3	3.4	6.1	30.1	16.0	33.7	80.3	32.7	71.6	99.0	64.4	62.8	89.0	37.1	0.0
<b>E DIR</b>	<b>Num</b>	2	2,651	1,305	31	217	14	1	18	680	108	6	15	38	24	0
	<b>Flex</b>	0.01	0.00	0.00	1.37	0.19	1.04	5.51	0.76	2.78	0.86	3.02	1.99	2.81	1.30	0.00
	<b>Rigid</b>	0.00	0.00	0.00	1.63	0.20	1.65	12.39	0.87	4.64	1.66	3.06	2.26	4.78	1.78	0.00
	<b>GVW</b>	4.9	3.4	6.2	29.8	15.8	36.1	110.8	34.9	74.7	59.0	70.5	75.2	97.6	33.5	0.0
<b>W 1</b>	<b>Num</b>	1	2,107	986	27	239	11	1	17	587	96	6	16	44	21	0
	<b>Flex</b>	0.00	0.00	0.00	1.54	0.17	0.95	4.99	0.68	2.71	3.17	2.79	1.08	2.48	1.48	0.00
	<b>Rigid</b>	0.00	0.00	0.00	1.90	0.18	1.55	9.56	0.77	4.53	6.73	2.87	1.27	4.90	2.11	0.00
	<b>GVW</b>	7.2	3.5	6.8	30.7	16.1	35.3	95.0	33.4	72.8	101.0	66.0	63.7	91.0	39.5	0.0
<b>W 2</b>	<b>Num</b>	1	584	300	2	6	1	0	1	30	6	1	1	3	3	0
	<b>Flex</b>	0.00	0.00	0.00	0.39	0.22	0.27	2.79	0.69	0.48	0.60	1.48	0.54	0.60	0.21	0.00
	<b>Rigid</b>	0.00	0.00	0.00	0.47	0.23	0.34	5.16	0.69	0.74	1.24	1.41	0.58	1.26	0.27	0.00
	<b>GVW</b>	4.4	3.0	4.1	27.2	15.4	46.4	383.2	42.8	46.8	66.4	112.5	84.3	64.9	20.5	0.0
<b>E 2</b>	<b>Num</b>	1	584	301	2	6	1	0	1	31	9	0	1	2	3	0
	<b>Flex</b>	0.00	0.00	0.00	1.02	0.73	0.33	0.00	0.29	0.57	0.13	2.26	0.42	0.59	1.04	0.00
	<b>Rigid</b>	0.00	0.00	0.00	1.26	0.82	0.46	0.00	0.32	0.88	0.23	2.12	0.44	1.10	1.29	0.00
	<b>GVW</b>	9.6	3.0	4.1	27.2	17.4	38.3	0.0	52.9	49.1	35.8	210.0	60.5	81.7	14.8	0.0
<b>E 1</b>	<b>Num</b>	2	2,067	1,004	30	211	13	1	17	649	100	6	13	36	21	0
	<b>Flex</b>	0.01	0.00	0.00	1.40	0.17	1.08	6.28	0.79	2.89	0.92	3.14	2.16	2.91	1.34	0.00
	<b>Rigid</b>	0.01	0.00	0.00	1.67	0.18	1.72	14.15	0.90	4.82	1.78	3.19	2.45	4.95	1.86	0.00
	<b>GVW</b>	5.7	3.6	6.8	30.3	15.7	36.1	122.7	35.2	75.9	61.0	71.4	78.7	98.9	36.2	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9