

## Monthly WIM Distribution for 06/2011

Site Names: 00115, Wolf Lodge WIM  
 County: Kootenai (28)  
 Funct. Class: R Principal Arterial - Interstate  
 Location: I-90 1.3 Mi. E of Jct SH-97

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
<b>Roadway</b>	<b>Num</b>	17	6,629	3,017	80	1,000	82	14	65	1,283	130	9	36	81	130	0
	<b>Flex</b>	0.00	0.00	0.00	1.76	0.22	1.76	2.63	0.65	3.12	2.25	2.95	1.93	3.18	1.09	0.00
	<b>Rigid</b>	0.00	0.00	0.00	2.21	0.24	3.17	6.25	0.75	5.27	4.72	3.08	2.31	5.57	1.46	0.00
	<b>GVW</b>	3.6	3.8	6.5	31.5	16.6	39.8	69.2	29.3	75.9	82.8	66.4	74.4	96.5	26.5	0.0
<b>W DIR</b>	<b>Num</b>	12	3,353	1,433	41	583	40	10	37	631	65	4	20	38	69	0
	<b>Flex</b>	0.00	0.00	0.01	2.02	0.26	3.05	3.12	0.57	3.34	2.89	2.99	1.65	3.01	1.14	0.00
	<b>Rigid</b>	0.00	0.00	0.01	2.61	0.28	5.61	7.36	0.67	5.71	6.20	3.11	2.04	5.50	1.55	0.00
	<b>GVW</b>	3.6	4.0	6.5	31.8	16.7	47.6	71.5	27.6	76.4	90.4	66.4	71.5	90.3	27.0	0.0
<b>E DIR</b>	<b>Num</b>	5	3,276	1,584	39	417	42	4	28	652	65	4	16	43	62	0
	<b>Flex</b>	0.00	0.00	0.00	1.48	0.17	0.53	3.26	0.75	2.91	1.60	3.19	2.26	3.34	1.04	0.00
	<b>Rigid</b>	0.00	0.00	0.00	1.78	0.18	0.84	7.62	0.86	4.85	3.24	3.32	2.62	5.68	1.37	0.00
	<b>GVW</b>	3.7	3.7	6.4	31.1	16.4	32.3	89.8	31.3	75.3	75.2	72.1	77.2	102.0	25.5	0.0
<b>W 1</b>	<b>Num</b>	7	2,481	999	38	574	37	10	36	598	61	4	19	37	60	0
	<b>Flex</b>	0.00	0.00	0.01	2.14	0.25	3.29	3.24	0.58	3.50	3.06	3.14	1.72	3.11	1.29	0.00
	<b>Rigid</b>	0.00	0.00	0.01	2.77	0.27	6.05	7.63	0.68	5.99	6.55	3.28	2.13	5.69	1.76	0.00
	<b>GVW</b>	3.8	4.3	7.6	32.6	16.7	49.3	72.1	27.7	78.2	92.5	68.0	72.3	91.4	29.8	0.0
<b>W 2</b>	<b>Num</b>	6	872	435	3	9	3	0	1	33	4	0	1	2	9	0
	<b>Flex</b>	0.00	0.00	0.00	0.28	0.57	0.34	1.39	0.10	0.42	0.49	3.57	0.35	0.50	0.18	0.00
	<b>Rigid</b>	0.00	0.00	0.00	0.32	0.63	0.54	2.68	0.10	0.63	1.09	3.41	0.37	0.95	0.21	0.00
	<b>GVW</b>	3.4	3.0	4.0	22.4	17.2	30.3	143.5	25.8	44.4	56.3	224.0	69.3	63.2	8.9	0.0
<b>E 2</b>	<b>Num</b>	1	853	434	3	10	4	0	1	33	4	0	1	2	9	0
	<b>Flex</b>	0.00	0.00	0.00	0.33	0.41	0.08	1.10	0.22	0.51	0.20	2.34	0.35	0.71	0.10	0.00
	<b>Rigid</b>	0.00	0.00	0.00	0.40	0.44	0.10	2.30	0.25	0.77	0.37	2.19	0.38	1.30	0.11	0.00
	<b>GVW</b>	4.0	3.0	4.1	22.7	17.1	21.5	178.5	45.1	47.7	42.2	224.0	66.9	84.3	9.4	0.0
<b>E 1</b>	<b>Num</b>	4	2,423	1,151	37	407	38	4	27	618	61	4	15	41	53	0
	<b>Flex</b>	0.00	0.00	0.01	1.56	0.17	0.58	3.76	0.77	3.04	1.70	3.26	2.43	3.50	1.19	0.00
	<b>Rigid</b>	0.00	0.00	0.01	1.88	0.18	0.92	8.66	0.88	5.07	3.44	3.40	2.83	5.94	1.58	0.00
	<b>GVW</b>	3.5	3.9	7.3	31.7	16.4	33.4	90.5	31.6	76.8	77.4	71.6	80.6	103.9	28.1	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9