

## Monthly WIM Distribution for 09/2011

Site Names: 00117, Cotterel WIM  
 County: Cassia (16)  
 Funct. Class: R Principal Arterial - Interstate  
 Location: I-84 3.7 Mi. SE of Jct SH-81

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
<b>Roadway</b>	<b>Num</b>	19	2,425	1,151	67	543	68	9	36	2,069	121	29	38	214	453	0
	<b>Flex</b>	0.01	0.00	0.00	1.32	0.24	0.78	1.51	0.60	2.46	1.96	2.39	2.07	2.79	0.35	0.00
	<b>Rigid</b>	0.01	0.00	0.00	1.69	0.24	1.29	3.18	0.78	4.16	3.95	2.40	2.51	3.65	0.48	0.00
	<b>GVW</b>	5.1	4.1	6.2	31.4	17.9	34.1	54.4	31.0	72.1	82.9	64.8	74.6	90.3	26.4	0.0
<b>NW DIR</b>	<b>Num</b>	6	1,159	428	34	397	27	3	24	1,171	67	14	24	114	136	0
	<b>Flex</b>	0.01	0.00	0.01	1.86	0.24	1.02	3.61	0.68	2.96	2.52	3.55	2.87	4.16	0.56	0.00
	<b>Rigid</b>	0.01	0.00	0.01	2.40	0.25	1.76	7.76	0.92	5.12	5.03	3.61	3.55	5.35	0.80	0.00
	<b>GVW</b>	5.5	5.0	7.1	33.3	17.7	36.7	76.5	31.5	75.5	84.5	74.3	85.5	103.4	22.4	0.0
<b>SE DIR</b>	<b>Num</b>	13	1,265	723	33	146	41	6	12	897	54	15	14	100	317	0
	<b>Flex</b>	0.01	0.00	0.00	0.75	0.22	0.62	1.26	0.44	1.80	1.28	1.29	0.70	1.24	0.26	0.00
	<b>Rigid</b>	0.01	0.00	0.00	0.95	0.22	0.98	2.66	0.51	2.92	2.64	1.26	0.74	1.76	0.34	0.00
	<b>GVW</b>	4.9	3.3	5.7	29.3	18.5	32.4	50.3	30.0	67.7	81.3	55.9	56.2	75.4	28.1	0.0
<b>NW 1</b>	<b>Num</b>	5	1,002	351	33	395	27	3	24	1,167	67	14	24	113	133	0
	<b>Flex</b>	0.01	0.00	0.01	1.92	0.24	1.02	3.61	0.68	2.97	2.53	3.59	2.89	4.19	0.57	0.00
	<b>Rigid</b>	0.01	0.00	0.01	2.47	0.26	1.77	7.76	0.92	5.13	5.04	3.65	3.57	5.38	0.82	0.00
	<b>GVW</b>	5.6	5.3	7.6	33.8	17.7	36.7	76.5	31.7	75.7	84.6	74.7	85.9	103.7	22.8	0.0
<b>NW 2</b>	<b>Num</b>	0	157	82	1	3	0	0	0	5	1	0	0	1	4	0
	<b>Flex</b>	0.01	0.00	0.00	0.51	0.08	0.10	0.00	0.09	0.73	0.85	0.82	1.47	0.69	0.03	0.00
	<b>Rigid</b>	0.01	0.00	0.00	0.56	0.08	0.11	0.00	0.15	1.08	1.48	0.77	1.49	1.18	0.04	0.00
	<b>GVW</b>	18.9	3.7	7.1	51.7	36.5	54.2	0.0	115.5	92.2	133.9	175.9	325.5	131.4	7.6	0.0
<b>SE 2</b>	<b>Num</b>	1	184	101	2	5	2	0	0	19	2	1	2	5	20	0
	<b>Flex</b>	0.00	0.00	0.00	0.55	0.10	0.21	0.25	0.89	1.10	1.65	2.85	0.61	1.01	0.07	0.00
	<b>Rigid</b>	0.00	0.00	0.00	0.68	0.09	0.31	0.50	1.10	1.70	3.35	2.74	0.63	1.46	0.08	0.00
	<b>GVW</b>	5.0	3.1	4.4	41.2	23.1	30.8	70.0	78.7	64.9	155.9	206.1	77.2	84.4	10.5	0.0
<b>SE 1</b>	<b>Num</b>	12	1,081	622	31	141	39	6	12	878	52	15	13	95	297	0
	<b>Flex</b>	0.01	0.00	0.00	0.77	0.22	0.64	1.26	0.44	1.82	1.30	1.31	0.74	1.28	0.28	0.00
	<b>Rigid</b>	0.01	0.00	0.00	0.98	0.22	1.01	2.66	0.52	2.95	2.68	1.28	0.78	1.81	0.36	0.00
	<b>GVW</b>	5.0	3.4	5.9	29.5	18.6	33.0	49.7	30.0	68.0	81.4	56.1	57.1	75.9	29.3	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9