

Monthly WIM Distribution for 01/2011

Site Names: 00128, Black Canyon WIM
 County: Payette (38)
 Funct. Class: R Principal Arterial - Interstate
 Location: I-84 2.2 Mi. SE of Black Canyon IC

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
Roadway	Num	3	7,926	3,326	70	460	51	2	64	2,507	322	158	70	370	45	0
	Flex	0.00	0.00	0.00	1.00	0.20	0.67	1.62	0.88	2.48	1.69	2.71	1.68	2.64	1.69	0.00
	Rigid	0.00	0.00	0.00	1.23	0.21	1.11	3.47	1.03	4.17	3.47	2.73	1.87	4.01	2.52	0.00
	GVW	3.5	3.3	5.9	27.4	16.2	30.8	68.7	37.5	71.7	79.4	68.4	72.6	86.2	45.7	0.0
NW DIR	Num	1	3,318	1,242	8	53	3	0	4	136	20	8	5	22	6	0
	Flex	0.00	0.00	0.00	0.55	0.07	0.42	3.77	0.41	1.15	0.77	1.50	0.78	1.01	0.58	0.00
	Rigid	0.00	0.00	0.00	0.70	0.07	0.63	7.73	0.43	1.83	1.55	1.48	0.81	1.50	0.74	0.00
	GVW	6.8	3.1	5.0	23.7	13.9	26.9	235.1	31.7	57.9	61.5	58.3	58.4	67.0	22.9	0.0
SE DIR	Num	2	4,608	2,083	63	408	48	2	60	2,371	302	151	65	349	39	0
	Flex	0.00	0.00	0.00	1.07	0.21	0.69	1.81	0.91	2.56	1.75	2.77	1.75	2.74	1.86	0.00
	Rigid	0.00	0.00	0.00	1.30	0.23	1.13	3.88	1.07	4.30	3.60	2.80	1.95	4.16	2.80	0.00
	GVW	4.1	3.4	6.5	27.8	16.5	31.0	73.3	38.1	72.4	80.6	69.0	73.7	87.4	49.1	0.0
NW 1	Num	0	1,698	615	4	38	1	0	2	65	10	4	2	9	3	0
	Flex	0.00	0.00	0.00	0.78	0.07	0.94	3.77	0.77	1.54	1.25	2.20	1.05	1.23	0.87	0.00
	Rigid	0.00	0.00	0.00	1.02	0.07	1.44	7.73	0.83	2.46	2.56	2.19	1.11	1.96	1.19	0.00
	GVW	9.0	3.2	5.6	28.1	13.6	43.3	235.1	38.3	61.5	74.7	65.5	65.2	65.5	28.5	0.0
NW 2	Num	0	1,620	628	3	15	1	0	2	71	11	4	3	13	3	0
	Flex	0.00	0.00	0.00	0.32	0.09	0.15	0.00	0.23	0.79	0.36	0.86	0.56	0.91	0.32	0.00
	Rigid	0.00	0.00	0.00	0.38	0.09	0.21	0.00	0.25	1.24	0.68	0.82	0.57	1.28	0.39	0.00
	GVW	10.5	3.0	4.4	21.1	14.7	24.5	0.0	29.6	54.6	50.3	55.5	55.4	68.7	15.0	0.0
SE 2	Num	1	2,279	988	31	248	20	1	27	1,168	151	77	35	169	21	0
	Flex	0.00	0.00	0.00	1.05	0.18	0.82	2.97	1.24	2.58	2.13	3.24	1.99	2.07	1.94	0.00
	Rigid	0.00	0.00	0.00	1.27	0.19	1.36	6.12	1.44	4.36	4.42	3.28	2.22	3.37	3.08	0.00
	GVW	5.5	3.7	7.2	28.2	15.7	32.8	135.6	40.8	72.5	87.7	73.1	77.4	77.7	52.1	0.0
SE 1	Num	1	2,329	1,095	32	160	28	1	34	1,203	152	74	30	180	19	0
	Flex	0.00	0.00	0.00	1.08	0.27	0.59	2.79	0.64	2.53	1.38	2.28	1.45	3.37	1.79	0.00
	Rigid	0.00	0.00	0.00	1.32	0.29	0.96	6.09	0.76	4.25	2.79	2.29	1.62	4.92	2.56	0.00
	GVW	5.7	3.1	5.9	27.3	17.7	29.7	100.0	35.6	72.3	73.6	64.6	68.8	96.4	45.4	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9