

Monthly WIM Distribution for 02/2011

Site Names: 00128, Black Canyon WIM
 County: Payette (38)
 Funct. Class: R Principal Arterial - Interstate
 Location: I-84 2.2 Mi. SE of Black Canyon IC

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
Roadway	Num	4	8,317	3,304	83	543	49	2	64	2,580	273	166	65	263	54	0
	Flex	0.00	0.00	0.00	1.13	0.19	0.73	2.80	0.90	2.55	1.77	2.91	1.80	2.81	1.64	0.00
	Rigid	0.00	0.00	0.00	1.39	0.19	1.22	5.63	1.09	4.30	3.62	2.95	2.02	4.45	2.35	0.00
	GVW	3.0	3.4	6.0	28.5	16.0	31.2	90.2	37.4	72.1	81.0	69.1	73.6	91.1	43.9	0.0
NW DIR	Num	1	3,666	1,331	7	44	3	0	4	129	15	7	4	16	5	0
	Flex	0.00	0.00	0.00	0.39	0.10	0.34	6.17	0.29	0.83	0.65	0.86	0.65	0.87	0.46	0.00
	Rigid	0.00	0.00	0.00	0.50	0.11	0.54	11.67	0.32	1.31	1.30	0.83	0.69	1.34	0.63	0.00
	GVW	5.4	3.1	4.8	23.1	14.5	26.1	209.1	27.1	53.4	60.0	50.4	57.4	65.8	20.7	0.0
SE DIR	Num	3	4,651	1,973	75	499	46	2	61	2,451	258	159	62	247	48	0
	Flex	0.00	0.00	0.00	1.21	0.19	0.76	3.01	0.93	2.64	1.84	3.00	1.86	2.94	1.78	0.00
	Rigid	0.00	0.00	0.00	1.47	0.20	1.27	6.05	1.13	4.46	3.75	3.05	2.10	4.65	2.56	0.00
	GVW	3.1	3.6	6.8	29.0	16.2	31.7	88.8	37.9	73.1	82.2	69.9	74.5	92.6	46.5	0.0
NW 1	Num	0	1,858	662	4	30	2	0	2	62	8	3	2	8	3	0
	Flex	0.00	0.00	0.00	0.63	0.12	0.54	6.17	0.58	1.13	0.97	1.41	1.19	1.16	0.68	0.00
	Rigid	0.00	0.00	0.00	0.86	0.13	0.89	11.67	0.63	1.78	1.93	1.36	1.28	1.85	0.84	0.00
	GVW	14.0	3.1	5.4	27.3	14.5	28.9	209.1	39.0	57.2	68.2	59.7	82.1	69.0	21.7	0.0
NW 2	Num	1	1,809	669	4	14	2	0	2	68	7	4	2	8	3	0
	Flex	0.00	0.00	0.00	0.24	0.06	0.10	0.00	0.20	0.56	0.34	0.46	0.56	0.64	0.44	0.00
	Rigid	0.00	0.00	0.00	0.30	0.06	0.14	0.00	0.23	0.89	0.68	0.43	0.58	0.97	0.88	0.00
	GVW	6.5	3.0	4.2	20.0	14.1	21.7	0.0	31.3	49.9	51.4	46.6	63.7	63.3	17.8	0.0
SE 2	Num	1	2,475	969	38	320	20	2	28	1,227	132	82	33	122	31	0
	Flex	0.00	0.00	0.01	1.18	0.16	0.91	2.98	1.14	2.63	2.21	3.46	2.13	3.06	1.84	0.00
	Rigid	0.00	0.00	0.01	1.44	0.16	1.54	6.00	1.33	4.43	4.55	3.51	2.40	4.98	2.66	0.00
	GVW	5.2	4.0	7.4	29.3	15.5	33.5	82.3	39.0	73.2	89.3	74.4	78.8	94.3	47.5	0.0
SE 1	Num	2	2,176	1,004	37	180	26	0	33	1,224	127	77	28	126	18	0
	Flex	0.00	0.00	0.00	1.22	0.26	0.63	3.95	0.75	2.65	1.45	2.51	1.57	2.83	1.69	0.00
	Rigid	0.00	0.00	0.00	1.49	0.27	1.05	8.44	0.95	4.48	2.92	2.56	1.76	4.37	2.43	0.00
	GVW	3.2	3.2	6.1	28.2	17.3	30.2	143.5	36.8	73.0	74.6	65.1	70.6	90.6	44.2	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9