

Monthly WIM Distribution for 03/2011

Site Names: 00128, Black Canyon WIM
 County: Payette (38)
 Funct. Class: R Principal Arterial - Interstate
 Location: I-84 2.2 Mi. SE of Black Canyon IC

| | | MC | CAR | PU | BUS | 2D | SU 3 | SU 4+ | ST 4- | ST 5 | ST 6+ | MT 5- | MT 6 | MT 7+ | OFFSCAL | UNCLS |
|----------------|--------------|------|-------|-------|------|------|------|-------|-------|-------|-------|-------|------|-------|---------|-------|
| Roadway | Num | 6 | 9,614 | 3,510 | 92 | 784 | 56 | 2 | 67 | 2,809 | 301 | 173 | 67 | 273 | 89 | 0 |
| | Flex | 0.00 | 0.00 | 0.00 | 1.17 | 0.18 | 0.65 | 2.76 | 0.90 | 2.58 | 1.85 | 2.89 | 1.89 | 2.86 | 1.15 | 0.00 |
| | Rigid | 0.00 | 0.00 | 0.00 | 1.44 | 0.19 | 1.08 | 5.47 | 1.07 | 4.34 | 3.79 | 2.93 | 2.14 | 4.51 | 1.59 | 0.00 |
| | GVW | 3.4 | 3.5 | 6.1 | 28.7 | 16.6 | 30.6 | 68.3 | 35.8 | 72.7 | 82.7 | 69.5 | 74.8 | 91.8 | 34.2 | 0.0 |
| NW DIR | Num | 2 | 4,307 | 1,490 | 9 | 42 | 3 | 0 | 4 | 149 | 19 | 8 | 4 | 15 | 10 | 0 |
| | Flex | 0.00 | 0.00 | 0.00 | 0.30 | 0.09 | 0.16 | 3.70 | 0.21 | 0.61 | 0.47 | 0.67 | 0.43 | 0.65 | 0.34 | 0.00 |
| | Rigid | 0.00 | 0.00 | 0.00 | 0.36 | 0.09 | 0.24 | 6.84 | 0.22 | 0.96 | 0.93 | 0.63 | 0.45 | 1.02 | 0.46 | 0.00 |
| | GVW | 3.9 | 3.1 | 4.6 | 21.6 | 14.8 | 20.7 | 152.1 | 24.7 | 50.4 | 58.3 | 49.1 | 49.6 | 63.8 | 18.4 | 0.0 |
| SE DIR | Num | 4 | 5,307 | 2,020 | 84 | 742 | 54 | 2 | 64 | 2,661 | 282 | 165 | 63 | 258 | 80 | 0 |
| | Flex | 0.00 | 0.00 | 0.00 | 1.26 | 0.19 | 0.68 | 3.45 | 0.94 | 2.69 | 1.95 | 3.00 | 1.99 | 2.99 | 1.26 | 0.00 |
| | Rigid | 0.00 | 0.00 | 0.00 | 1.55 | 0.20 | 1.12 | 6.83 | 1.12 | 4.53 | 3.99 | 3.04 | 2.25 | 4.72 | 1.74 | 0.00 |
| | GVW | 3.6 | 3.9 | 7.1 | 29.4 | 16.7 | 30.9 | 73.6 | 36.5 | 74.0 | 84.4 | 70.5 | 76.3 | 93.5 | 36.1 | 0.0 |
| NW 1 | Num | 1 | 2,233 | 758 | 5 | 28 | 2 | 0 | 2 | 72 | 10 | 4 | 2 | 6 | 6 | 0 |
| | Flex | 0.00 | 0.00 | 0.00 | 0.39 | 0.10 | 0.23 | 3.70 | 0.28 | 0.74 | 0.65 | 0.94 | 0.78 | 0.94 | 0.53 | 0.00 |
| | Rigid | 0.00 | 0.00 | 0.00 | 0.47 | 0.11 | 0.35 | 6.84 | 0.29 | 1.17 | 1.29 | 0.90 | 0.83 | 1.56 | 0.76 | 0.00 |
| | GVW | 4.4 | 3.1 | 5.2 | 24.5 | 15.1 | 26.6 | 152.1 | 27.0 | 51.8 | 64.4 | 54.5 | 67.5 | 66.9 | 22.1 | 0.0 |
| NW 2 | Num | 1 | 2,074 | 732 | 4 | 14 | 2 | 0 | 2 | 77 | 10 | 5 | 2 | 9 | 4 | 0 |
| | Flex | 0.00 | 0.00 | 0.00 | 0.22 | 0.06 | 0.11 | 0.00 | 0.14 | 0.49 | 0.28 | 0.48 | 0.33 | 0.50 | 0.13 | 0.00 |
| | Rigid | 0.00 | 0.00 | 0.00 | 0.27 | 0.05 | 0.15 | 0.00 | 0.15 | 0.76 | 0.55 | 0.46 | 0.34 | 0.75 | 0.16 | 0.00 |
| | GVW | 4.8 | 3.0 | 4.1 | 20.0 | 14.1 | 20.1 | 0.0 | 24.7 | 48.9 | 51.2 | 46.8 | 55.2 | 61.7 | 13.6 | 0.0 |
| SE 2 | Num | 2 | 2,699 | 924 | 43 | 528 | 22 | 2 | 34 | 1,275 | 142 | 83 | 34 | 126 | 58 | 0 |
| | Flex | 0.00 | 0.00 | 0.01 | 1.31 | 0.17 | 0.88 | 4.05 | 1.15 | 2.72 | 2.37 | 3.56 | 2.38 | 3.27 | 1.26 | 0.00 |
| | Rigid | 0.00 | 0.00 | 0.01 | 1.60 | 0.18 | 1.48 | 8.01 | 1.37 | 4.59 | 4.90 | 3.61 | 2.71 | 5.23 | 1.72 | 0.00 |
| | GVW | 4.7 | 4.4 | 7.8 | 30.2 | 16.4 | 33.6 | 85.9 | 37.6 | 74.3 | 91.3 | 75.2 | 80.9 | 96.7 | 34.6 | 0.0 |
| SE 1 | Num | 3 | 2,607 | 1,096 | 41 | 214 | 31 | 0 | 30 | 1,386 | 140 | 82 | 29 | 132 | 21 | 0 |
| | Flex | 0.00 | 0.00 | 0.00 | 1.20 | 0.24 | 0.54 | 8.88 | 0.70 | 2.66 | 1.51 | 2.44 | 1.50 | 2.72 | 1.31 | 0.00 |
| | Rigid | 0.00 | 0.00 | 0.00 | 1.49 | 0.26 | 0.87 | 18.07 | 0.83 | 4.47 | 3.06 | 2.46 | 1.68 | 4.22 | 1.90 | 0.00 |
| | GVW | 4.1 | 3.3 | 6.5 | 28.5 | 17.3 | 28.9 | 280.1 | 34.9 | 73.6 | 77.3 | 65.6 | 69.8 | 90.1 | 40.4 | 0.0 |

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9