

Monthly WIM Distribution for 04/2011

Site Names: 00128, Black Canyon WIM
 County: Payette (38)
 Funct. Class: R Principal Arterial - Interstate
 Location: I-84 2.2 Mi. SE of Black Canyon IC

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
Roadway	Num	14	10,125	3,487	101	1,111	61	2	81	2,687	280	124	62	315	166	0
	Flex	0.00	0.00	0.00	1.39	0.18	0.85	4.39	0.84	2.76	2.07	3.39	2.10	3.21	0.80	0.00
	Rigid	0.00	0.00	0.00	1.70	0.19	1.43	11.55	0.99	4.66	4.23	3.47	2.44	4.80	1.08	0.00
	GVW	3.3	3.7	6.1	29.3	16.9	32.2	72.0	32.7	73.9	84.0	71.6	76.4	93.6	25.2	0.0
NW DIR	Num	5	4,522	1,540	10	54	5	0	3	144	15	5	5	19	15	0
	Flex	0.00	0.00	0.00	0.25	0.08	0.11	2.74	0.13	0.54	0.41	0.61	0.42	0.57	0.44	0.00
	Rigid	0.00	0.00	0.00	0.29	0.08	0.15	5.28	0.14	0.84	0.79	0.58	0.44	0.82	0.53	0.00
	GVW	3.2	3.1	4.6	20.6	15.0	18.8	269.5	21.2	48.6	55.4	47.2	50.0	62.0	13.7	0.0
SE DIR	Num	9	5,602	1,947	92	1,058	57	2	78	2,543	265	119	58	296	150	0
	Flex	0.00	0.00	0.01	1.50	0.19	0.91	4.69	0.87	2.88	2.17	3.51	2.22	3.37	0.83	0.00
	Rigid	0.00	0.00	0.01	1.84	0.20	1.54	12.38	1.02	4.88	4.42	3.60	2.57	5.05	1.13	0.00
	GVW	3.3	4.2	7.3	30.1	17.0	33.4	74.3	33.1	75.4	85.7	72.8	78.0	95.5	26.3	0.0
NW 1	Num	2	2,312	776	5	38	3	0	1	77	9	3	3	8	8	0
	Flex	0.00	0.00	0.00	0.36	0.09	0.14	2.64	0.32	0.69	0.52	0.93	0.54	0.82	0.51	0.00
	Rigid	0.00	0.00	0.00	0.43	0.10	0.20	5.18	0.33	1.08	0.99	0.89	0.57	1.22	0.64	0.00
	GVW	4.1	3.1	5.1	22.2	15.2	19.3	252.0	37.7	51.4	58.0	55.9	55.8	68.4	15.7	0.0
NW 2	Num	3	2,211	765	5	16	2	0	2	67	7	2	2	11	7	0
	Flex	0.00	0.00	0.00	0.15	0.05	0.07	0.00	0.07	0.36	0.23	0.37	0.35	0.40	0.52	0.00
	Rigid	0.00	0.00	0.00	0.18	0.05	0.09	0.00	0.07	0.56	0.45	0.35	0.36	0.56	0.63	0.00
	GVW	3.1	3.0	4.1	18.7	14.3	19.5	0.0	21.5	45.3	47.1	49.0	58.3	57.0	12.0	0.0
SE 2	Num	3	2,707	752	49	782	25	1	45	1,242	131	61	31	143	124	0
	Flex	0.00	0.00	0.01	1.68	0.18	1.09	7.40	1.02	3.08	2.82	4.07	2.70	3.78	0.73	0.00
	Rigid	0.00	0.00	0.01	2.06	0.19	1.89	19.64	1.22	5.27	5.76	4.16	3.20	5.78	0.98	0.00
	GVW	3.7	5.1	8.2	31.4	16.8	35.8	116.1	33.2	77.1	93.8	77.7	85.1	99.0	24.0	0.0
SE 1	Num	6	2,895	1,195	43	275	32	1	34	1,302	134	58	27	154	27	0
	Flex	0.00	0.00	0.00	1.30	0.22	0.77	2.34	0.65	2.69	1.53	2.93	1.66	3.00	1.35	0.00
	Rigid	0.00	0.00	0.00	1.59	0.23	1.27	5.07	0.74	4.50	3.12	3.02	1.86	4.39	1.92	0.00
	GVW	2.9	3.4	6.7	28.4	17.4	31.5	98.2	32.6	73.7	77.7	67.6	70.1	92.1	36.9	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9