

Monthly WIM Distribution for 05/2011

Site Names: 00128, Black Canyon WIM
 County: Payette (38)
 Funct. Class: R Principal Arterial - Interstate
 Location: I-84 2.2 Mi. SE of Black Canyon IC

Roadway	Num	461	23	10,187	3,170	111	1,495	75	10	110	2,589	261	87	55	310
	Flex	0.38	0.00	0.00	0.00	1.76	0.22	1.01	2.90	0.85	3.17	2.51	3.59	2.57	3.71
	Rigid	0.50	0.00	0.00	0.00	2.18	0.23	1.72	5.74	1.06	5.43	5.15	3.71	3.12	5.39
	GVW	17.1	3.3	4.0	6.0	29.8	16.9	34.4	68.5	31.8	76.3	85.9	72.0	80.7	96.2
NW DIR	Num	26	7	4,622	1,537	10	51	6	1	4	130	13	4	3	16
	Flex	0.21	0.00	0.00	0.00	0.22	0.10	0.11	0.80	0.11	0.41	0.31	0.51	0.37	0.43
	Rigid	0.25	0.00	0.00	0.00	0.27	0.10	0.15	1.48	0.12	0.63	0.62	0.48	0.39	0.61
	GVW	11.0	3.4	3.1	4.6	20.1	14.8	20.8	61.2	21.9	45.6	52.8	46.0	51.2	57.1
SE DIR	Num	434	16	5,565	1,633	100	1,444	69	9	107	2,459	248	84	52	294
	Flex	0.39	0.00	0.00	0.01	1.92	0.22	1.09	3.23	0.88	3.31	2.63	3.73	2.71	3.88
	Rigid	0.52	0.00	0.00	0.01	2.37	0.24	1.86	6.40	1.10	5.68	5.39	3.85	3.29	5.65
	GVW	17.5	3.3	4.8	7.4	30.8	17.0	35.7	72.2	32.1	77.9	87.7	73.2	82.8	98.2
NW 1	Num	15	4	2,403	784	6	36	4	1	2	70	8	2	2	6
	Flex	0.35	0.00	0.00	0.00	0.30	0.11	0.13	0.80	0.15	0.52	0.43	0.88	0.57	0.73
	Rigid	0.41	0.00	0.00	0.00	0.37	0.12	0.18	1.48	0.16	0.81	0.86	0.83	0.59	1.06
	GVW	12.6	3.7	3.1	5.2	21.1	15.0	21.9	61.2	23.6	48.3	58.6	64.2	62.5	66.3
NW 2	Num	12	3	2,219	753	4	15	2	0	2	60	6	2	2	10
	Flex	0.04	0.00	0.00	0.00	0.16	0.05	0.10	0.00	0.08	0.27	0.17	0.47	0.23	0.28
	Rigid	0.05	0.00	0.00	0.00	0.20	0.05	0.14	0.00	0.09	0.41	0.33	0.44	0.24	0.40
	GVW	8.9	3.2	3.0	4.0	18.6	14.1	25.2	0.0	23.2	42.5	45.2	61.0	52.2	52.4
SE 2	Num	395	3	2,579	434	53	1,101	31	8	69	1,250	126	43	29	143
	Flex	0.33	0.00	0.01	0.01	2.51	0.22	1.57	3.86	0.97	4.02	3.74	5.06	3.49	4.81
	Rigid	0.44	0.00	0.01	0.01	3.16	0.24	2.79	7.61	1.24	7.00	7.70	5.28	4.38	7.11
	GVW	16.2	3.3	6.2	8.5	33.3	16.9	40.1	84.2	31.1	82.8	98.1	81.8	91.4	103.7
SE 1	Num	40	12	2,986	1,199	48	343	38	1	38	1,209	122	41	23	152
	Flex	1.01	0.00	0.00	0.00	1.26	0.22	0.68	5.09	0.71	2.58	1.47	2.34	1.68	3.03
	Rigid	1.36	0.00	0.00	0.00	1.51	0.23	1.09	10.35	0.84	4.32	3.00	2.37	1.87	4.32
	GVW	30.0	3.4	3.5	6.9	28.1	17.3	31.8	113.3	34.0	72.8	76.9	64.3	70.8	93.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9