

Monthly WIM Distribution for 08/2011

Site Names: 00128, Black Canyon WIM
 County: Payette (38)
 Funct. Class: R Principal Arterial - Interstate
 Location: I-84 2.2 Mi. SE of Black Canyon IC

Roadway	Num	1,110	57	11,123	3,513	142	1,839	262	17	122	2,517	307	69	46	306
	Flex	0.49	0.00	0.00	0.00	1.64	0.27	1.64	2.17	0.73	2.42	1.95	2.79	2.10	2.75
	Rigid	0.57	0.00	0.00	0.00	2.20	0.29	2.89	4.49	0.88	4.10	3.91	2.85	2.61	3.93
	GVW	17.3	4.1	4.0	5.7	31.0	17.8	41.2	60.2	29.2	71.2	82.1	67.3	75.8	90.1
NW DIR	Num	59	18	5,475	1,806	13	56	23	2	3	124	19	2	2	16
	Flex	0.48	0.00	0.00	0.00	0.17	0.18	0.11	0.24	0.09	0.25	0.23	0.37	0.26	0.29
	Rigid	0.56	0.00	0.00	0.00	0.20	0.20	0.16	0.46	0.10	0.39	0.45	0.35	0.27	0.42
	GVW	12.3	3.8	3.1	4.5	20.5	15.7	22.7	40.1	21.7	41.2	51.5	46.2	47.7	53.6
SE DIR	Num	1,051	39	5,648	1,707	128	1,783	239	16	118	2,393	288	66	44	290
	Flex	0.49	0.00	0.00	0.00	1.79	0.28	1.78	2.46	0.75	2.53	2.07	2.89	2.20	2.88
	Rigid	0.57	0.00	0.00	0.00	2.41	0.29	3.15	5.13	0.91	4.30	4.14	2.95	2.74	4.12
	GVW	17.6	4.3	4.9	6.9	32.1	17.8	43.0	64.2	29.5	72.8	84.1	68.3	77.4	92.0
NW 1	Num	37	11	2,746	910	8	42	20	2	2	56	8	1	1	4
	Flex	0.74	0.00	0.00	0.00	0.22	0.22	0.12	0.28	0.13	0.35	0.33	0.70	0.46	0.47
	Rigid	0.87	0.00	0.00	0.00	0.27	0.24	0.18	0.54	0.13	0.53	0.65	0.66	0.49	0.70
	GVW	15.0	4.2	3.2	5.1	21.6	15.9	23.7	44.7	25.3	44.3	54.0	66.9	68.2	63.6
NW 2	Num	22	7	2,728	897	5	15	3	0	2	67	11	1	1	12
	Flex	0.03	0.00	0.00	0.00	0.10	0.07	0.05	0.00	0.07	0.18	0.16	0.24	0.13	0.23
	Rigid	0.04	0.00	0.00	0.00	0.12	0.07	0.06	0.00	0.09	0.27	0.32	0.23	0.14	0.33
	GVW	7.7	3.4	3.0	3.9	19.0	14.9	17.1	0.0	22.5	38.8	49.9	55.0	39.3	51.3
SE 2	Num	950	11	2,398	270	73	1,449	175	10	84	1,150	128	32	25	126
	Flex	0.45	0.01	0.01	0.01	2.55	0.29	2.26	3.65	0.77	3.55	3.26	4.40	3.14	4.33
	Rigid	0.52	0.01	0.01	0.01	3.53	0.31	4.02	7.79	0.95	6.16	6.50	4.55	4.04	6.26
	GVW	16.7	5.0	7.0	8.6	36.1	17.7	47.7	69.9	29.0	80.3	92.9	79.2	89.8	103.5
SE 1	Num	101	28	3,250	1,437	56	334	65	6	35	1,243	160	34	19	164
	Flex	0.89	0.00	0.00	0.00	0.79	0.23	0.51	0.95	0.71	1.59	1.11	1.46	1.01	1.78
	Rigid	1.05	0.00	0.00	0.00	0.94	0.24	0.78	1.97	0.81	2.57	2.25	1.44	1.09	2.50
	GVW	25.9	4.0	3.4	6.6	26.8	18.5	30.3	51.2	30.5	65.8	77.0	57.6	61.7	83.3

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9