

## Monthly WIM Distribution for 09/2011

Site Names: 00128, Black Canyon WIM  
 County: Payette (38)  
 Funct. Class: R Principal Arterial - Interstate  
 Location: I-84 2.2 Mi. SE of Black Canyon IC

<b>Roadway</b>	<b>Num</b>	676	43	10,305	3,354	122	1,589	140	9	109	2,641	250	55	47	327
	<b>Flex</b>	0.36	0.00	0.00	0.00	1.58	0.24	1.28	2.57	0.72	2.48	2.09	2.96	2.10	2.86
	<b>Rigid</b>	0.43	0.00	0.00	0.00	2.01	0.26	2.23	5.68	0.85	4.19	4.12	3.06	2.59	3.99
	<b>GVW</b>	16.6	3.7	3.9	5.8	28.9	17.4	36.5	61.8	29.0	70.8	79.5	67.2	75.2	89.1
<b>NW DIR</b>	<b>Num</b>	45	16	4,904	1,608	14	82	16	1	4	153	14	2	3	21
	<b>Flex</b>	0.28	0.00	0.00	0.00	0.32	0.10	0.21	1.07	0.21	0.46	0.38	0.76	0.41	0.55
	<b>Rigid</b>	0.32	0.00	0.00	0.00	0.40	0.11	0.32	1.92	0.24	0.71	0.73	0.71	0.44	0.80
	<b>GVW</b>	11.9	3.5	3.1	4.9	22.0	14.8	24.6	57.9	27.7	46.3	59.5	57.9	48.9	60.4
<b>SE DIR</b>	<b>Num</b>	632	28	5,401	1,746	108	1,507	125	8	106	2,487	236	54	44	306
	<b>Flex</b>	0.36	0.00	0.00	0.00	1.73	0.25	1.41	2.83	0.74	2.61	2.19	3.03	2.20	3.01
	<b>Rigid</b>	0.44	0.00	0.00	0.00	2.21	0.26	2.47	6.23	0.87	4.41	4.33	3.14	2.72	4.21
	<b>GVW</b>	16.9	3.8	4.7	6.7	29.8	17.5	37.9	64.5	29.2	72.3	81.2	67.7	76.4	91.1
<b>NW 1</b>	<b>Num</b>	27	8	2,466	788	8	63	13	1	2	69	7	1	2	8
	<b>Flex</b>	0.44	0.00	0.00	0.00	0.42	0.12	0.23	1.71	0.35	0.66	0.58	1.50	0.94	0.84
	<b>Rigid</b>	0.51	0.00	0.00	0.00	0.52	0.12	0.35	3.07	0.43	1.03	1.14	1.42	1.00	1.31
	<b>GVW</b>	14.4	3.6	3.2	5.5	23.8	14.7	25.7	87.9	32.1	49.9	64.9	96.6	85.7	64.5
<b>NW 2</b>	<b>Num</b>	18	8	2,438	819	6	19	3	0	1	85	7	1	2	13
	<b>Flex</b>	0.04	0.00	0.00	0.00	0.19	0.05	0.18	0.89	0.15	0.29	0.21	0.45	0.33	0.42
	<b>Rigid</b>	0.05	0.00	0.00	0.00	0.23	0.05	0.25	1.84	0.17	0.44	0.41	0.42	0.35	0.58
	<b>GVW</b>	8.1	3.3	3.0	4.2	18.4	15.0	25.6	241.5	34.1	43.3	52.2	55.0	61.3	58.5
<b>SE 2</b>	<b>Num</b>	560	6	2,411	379	59	1,225	76	6	74	1,220	113	26	25	147
	<b>Flex</b>	0.32	0.01	0.01	0.01	2.54	0.25	1.96	4.34	0.83	3.70	3.61	4.58	3.17	4.24
	<b>Rigid</b>	0.39	0.01	0.01	0.01	3.33	0.27	3.51	10.06	1.00	6.41	7.15	4.81	4.03	6.10
	<b>GVW</b>	15.8	4.9	6.5	8.6	33.3	17.3	43.5	68.1	28.9	80.6	95.6	78.0	89.4	100.0
<b>SE 1</b>	<b>Num</b>	72	21	2,990	1,367	49	282	49	3	32	1,267	123	27	19	159
	<b>Flex</b>	0.71	0.00	0.00	0.00	0.76	0.24	0.55	1.63	0.52	1.56	0.88	1.54	0.94	1.88
	<b>Rigid</b>	0.87	0.00	0.00	0.00	0.87	0.24	0.84	3.68	0.57	2.48	1.71	1.53	1.01	2.48
	<b>GVW</b>	25.6	3.6	3.2	6.2	25.4	18.8	29.0	63.8	29.5	64.4	67.8	57.4	59.9	82.8

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9