

Idaho Transportation Department

Monthly WIM Distribution for Jan-2017

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	2,147	1,518	36	77	23	2	24	117	75	2	1	69	0
	Flex	.00	.00	.00	.23	.14	.39	.15	.18	.30	.49	.17	.26	.41	0.00
	Rigid	.00	.00	.00	.26	.14	.56	.33	.22	.49	.98	.16	.26	.64	0.00
	GVW	3.3	3.4	5.8	22.4	16.0	30.4	35.8	25.2	41.7	66.2	36.3	41.5	58.3	0.0
N	Num	1	1,049	752	19	39	11	2	11	47	46	1	1	35	0
	Flex	.00	.00	.00	.24	.12	.34	.20	.29	.39	.51	.31	.83	.24	0.00
	Rigid	.00	.00	.00	.26	.11	.45	.42	.34	.65	1.01	.29	.83	.36	0.00
	GVW	1.7	3.4	5.8	22.8	15.9	28.8	37.6	26.9	44.7	68.5	42.2	62.8	44.0	0.0
S	Num	1	1,098	766	18	38	12	1	12	71	29	2	1	34	0
	Flex	.00	.00	.00	.22	.16	.42	.04	.12	.25	.44	.13	.12	.59	0.00
	Rigid	.00	.00	.00	.26	.16	.64	.14	.14	.37	.90	.13	.12	.93	0.00
	GVW	3.3	3.4	5.8	21.9	16.2	32.0	31.4	24.3	39.6	61.7	34.4	34.7	73.7	0.0
N Lane1	Num	1	1,049	752	19	39	11	2	11	47	46	1	1	35	0
	Flex	.00	.00	.00	.24	.12	.34	.20	.29	.39	.51	.31	.83	.24	0.00
	Rigid	.00	.00	.00	.26	.11	.45	.42	.34	.65	1.01	.29	.83	.36	0.00
	GVW	1.7	3.4	5.8	22.8	15.9	28.8	37.6	26.9	44.7	68.5	42.2	62.8	44.0	0.0
S Lane1	Num	1	1,098	766	18	38	12	1	12	71	29	2	1	34	0
	Flex	.00	.00	.00	.22	.16	.42	.04	.12	.25	.44	.13	.12	.59	0.00
	Rigid	.00	.00	.00	.26	.16	.64	.14	.14	.37	.90	.13	.12	.93	0.00
	GVW	3.3	3.4	5.8	21.9	16.2	32.0	31.4	24.3	39.6	61.7	34.4	34.7	73.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2017

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9