

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	22	3,550	2,318	40	210	89	13	32	170	104	4	2	82	0
	Flex	.00	.00	.00	.40	.17	.32	.21	.32	.45	.49	.38	.24	.75	0.00
	Rigid	.00	.00	.00	.48	.17	.51	.55	.35	.75	1.09	.36	.25	1.23	0.00
	GVW	3.0	3.5	6.2	22.5	16.9	28.4	45.0	28.3	45.1	66.4	42.3	41.8	65.8	0.0
N	Num	11	1,801	1,138	19	105	39	5	16	84	67	2	1	41	0
	Flex	.00	.00	.00	.28	.14	.34	.13	.26	.36	.37	.54	.21	.54	0.00
	Rigid	.00	.00	.00	.31	.14	.52	.41	.28	.56	.83	.51	.20	.90	0.00
	GVW	2.8	3.5	6.1	21.6	16.6	28.0	42.4	28.3	42.8	63.0	47.8	38.2	55.3	0.0
S	Num	10	1,748	1,181	20	104	50	8	16	86	38	2	2	41	0
	Flex	.00	.00	.00	.43	.20	.31	.24	.34	.55	.68	.15	.39	1.00	0.00
	Rigid	.00	.00	.00	.54	.20	.49	.63	.39	.94	1.49	.14	.41	1.59	0.00
	GVW	3.3	3.6	6.2	22.8	17.3	28.8	46.4	28.1	47.6	70.1	34.8	48.7	77.3	0.0
N Lane1	Num	11	1,801	1,138	19	105	39	5	16	84	67	2	1	41	0
	Flex	.00	.00	.00	.28	.14	.34	.13	.26	.36	.37	.54	.21	.54	0.00
	Rigid	.00	.00	.00	.31	.14	.52	.41	.28	.56	.83	.51	.20	.90	0.00
	GVW	2.8	3.5	6.1	21.6	16.6	28.0	42.4	28.3	42.8	63.0	47.8	38.2	55.3	0.0
S Lane1	Num	10	1,748	1,181	20	104	50	8	16	86	38	2	2	41	0
	Flex	.00	.00	.00	.43	.20	.31	.24	.34	.55	.68	.15	.39	1.00	0.00
	Rigid	.00	.00	.00	.54	.20	.49	.63	.39	.94	1.49	.14	.41	1.59	0.00
	GVW	3.3	3.6	6.2	22.8	17.3	28.8	46.4	28.1	47.6	70.1	34.8	48.7	77.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9