

Idaho Transportation Department

Monthly WIM Distribution for Aug-2017

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	20	3,657	2,382	40	197	98	13	33	197	124	3	2	85	0
	Flex	.00	.00	.00	.32	.14	.32	.19	.35	.48	.44	.33	.21	.69	0.00
	Rigid	.00	.00	.00	.36	.14	.51	.55	.40	.81	.97	.32	.22	1.15	0.00
	GVW	3.2	3.5	6.1	22.4	16.4	28.3	45.6	27.7	45.7	66.6	39.5	39.7	65.7	0.0
N	Num	11	1,863	1,186	20	96	45	4	16	96	73	2	1	41	0
	Flex	.00	.00	.00	.26	.12	.28	.14	.25	.31	.29	.47	.17	.44	0.00
	Rigid	.00	.00	.00	.28	.11	.41	.41	.26	.49	.65	.46	.17	.70	0.00
	GVW	3.0	3.4	6.0	21.9	16.1	26.2	42.2	27.6	41.5	60.4	42.7	33.3	52.3	0.0
S	Num	10	1,794	1,195	21	101	53	9	17	101	51	2	2	43	0
	Flex	.00	.00	.00	.36	.16	.36	.21	.44	.63	.64	.14	.22	.95	0.00
	Rigid	.00	.00	.00	.42	.16	.61	.60	.52	1.10	1.42	.13	.23	1.60	0.00
	GVW	3.5	3.6	6.2	22.7	16.6	30.0	46.7	27.7	49.7	74.1	35.6	40.5	79.1	0.0
N Lane1	Num	11	1,863	1,186	20	96	45	4	16	96	73	2	1	41	0
	Flex	.00	.00	.00	.26	.12	.28	.14	.25	.31	.29	.47	.17	.44	0.00
	Rigid	.00	.00	.00	.28	.11	.41	.41	.26	.49	.65	.46	.17	.70	0.00
	GVW	3.0	3.4	6.0	21.9	16.1	26.2	42.2	27.6	41.5	60.4	42.7	33.3	52.3	0.0
S Lane1	Num	10	1,794	1,195	21	101	53	9	17	101	51	2	2	43	0
	Flex	.00	.00	.00	.36	.16	.36	.21	.44	.63	.64	.14	.22	.95	0.00
	Rigid	.00	.00	.00	.42	.16	.61	.60	.52	1.10	1.42	.13	.23	1.60	0.00
	GVW	3.5	3.6	6.2	22.7	16.6	30.0	46.7	27.7	49.7	74.1	35.6	40.5	79.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Aug-2017

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9