

# Idaho Transportation Department

## Monthly WIM Distribution for Nov-2017

Site names: 00129  
 County: Jerome  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	2,897	2,026	32	122	43	2	29	202	133	2	2	103	0
	Flex	.00	.00	.00	.20	.09	.33	.16	.17	.33	.34	.31	.08	.54	0.00
	Rigid	.00	.00	.00	.21	.09	.52	.44	.19	.52	.74	.29	.09	.85	0.00
	GVW	5.0	3.4	6.0	19.6	16.1	28.7	43.0	27.3	41.3	62.5	39.6	36.7	63.0	0.0
N	Num	1	1,444	1,000	16	55	21	1	15	93	81	1	1	46	0
	Flex	.00	.00	.00	.16	.08	.24	.10	.17	.25	.26	.37	.20	.27	0.00
	Rigid	.00	.00	.00	.17	.08	.35	.33	.19	.40	.56	.35	.19	.39	0.00
	GVW	5.2	3.4	5.9	19.4	15.6	26.5	37.5	27.4	39.5	58.3	42.2	39.3	47.5	0.0
S	Num	2	1,453	1,026	16	66	23	2	15	110	52	1	1	57	0
	Flex	.00	.00	.00	.24	.10	.42	.17	.17	.40	.45	.20	.07	.77	0.00
	Rigid	.00	.00	.00	.26	.10	.70	.47	.19	.63	1.00	.19	.08	1.24	0.00
	GVW	2.9	3.5	6.1	19.8	16.5	30.8	43.9	27.2	42.9	68.4	37.2	36.7	75.9	0.0
N Lane1	Num	1	1,444	1,000	16	55	21	1	15	93	81	1	1	46	0
	Flex	.00	.00	.00	.16	.08	.24	.10	.17	.25	.26	.37	.20	.27	0.00
	Rigid	.00	.00	.00	.17	.08	.35	.33	.19	.40	.56	.35	.19	.39	0.00
	GVW	5.2	3.4	5.9	19.4	15.6	26.5	37.5	27.4	39.5	58.3	42.2	39.3	47.5	0.0
S Lane1	Num	2	1,453	1,026	16	66	23	2	15	110	52	1	1	57	0
	Flex	.00	.00	.00	.24	.10	.42	.17	.17	.40	.45	.20	.07	.77	0.00
	Rigid	.00	.00	.00	.26	.10	.70	.47	.19	.63	1.00	.19	.08	1.24	0.00
	GVW	2.9	3.5	6.1	19.8	16.5	30.8	43.9	27.2	42.9	68.4	37.2	36.7	75.9	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Nov-2017

Site names: 00129  
 County: Jerome  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9