

Idaho Transportation Department

Monthly WIM Distribution for Dec-2018

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	2,821	1,857	39	98	27	2	25	148	76	2	2	50	0
	Flex	.00	.00	.00	.18	.07	.34	.35	.21	.32	.46	.19	.21	.45	0.00
	Rigid	.00	.00	.00	.20	.07	.50	.62	.24	.50	1.04	.18	.21	.71	0.00
	GVW	3.3	3.4	5.8	20.1	15.2	29.9	44.9	27.6	40.5	70.4	37.1	39.1	56.2	0.0
N	Num	1	1,420	929	22	56	14	1	13	63	46	1	1	26	0
	Flex	.00	.00	.00	.21	.07	.31	.39	.24	.32	.47	.31	.21	.35	0.00
	Rigid	.00	.00	.00	.23	.07	.44	.71	.26	.53	1.07	.29	.21	.56	0.00
	GVW	2.9	3.4	5.8	20.8	15.0	28.6	46.4	28.9	40.3	70.7	43.7	42.5	49.5	0.0
S	Num	1	1,401	928	18	43	13	2	12	84	30	2	1	25	0
	Flex	.00	.00	.00	.15	.07	.39	.31	.17	.32	.45	.12	.19	.56	0.00
	Rigid	.00	.00	.00	.18	.07	.58	.55	.20	.48	1.01	.12	.20	.87	0.00
	GVW	3.7	3.5	5.8	19.5	15.4	31.4	44.2	26.6	40.6	69.6	33.1	35.0	63.0	0.0
N Lane1	Num	1	1,420	929	22	56	14	1	13	63	46	1	1	26	0
	Flex	.00	.00	.00	.21	.07	.31	.39	.24	.32	.47	.31	.21	.35	0.00
	Rigid	.00	.00	.00	.23	.07	.44	.71	.26	.53	1.07	.29	.21	.56	0.00
	GVW	2.9	3.4	5.8	20.8	15.0	28.6	46.4	28.9	40.3	70.7	43.7	42.5	49.5	0.0
S Lane1	Num	1	1,401	928	18	43	13	2	12	84	30	2	1	25	0
	Flex	.00	.00	.00	.15	.07	.39	.31	.17	.32	.45	.12	.19	.56	0.00
	Rigid	.00	.00	.00	.18	.07	.58	.55	.20	.48	1.01	.12	.20	.87	0.00
	GVW	3.7	3.5	5.8	19.5	15.4	31.4	44.2	26.6	40.6	69.6	33.1	35.0	63.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2018

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9