

Idaho Transportation Department

Monthly WIM Distribution for Jan-2019

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	2,699	1,684	36	115	22	2	25	133	89	2	1	54	0
	Flex	.00	.00	.00	.25	.12	.33	.17	.34	.40	.48	.18	.18	.55	0.00
	Rigid	.00	.00	.00	.28	.13	.50	.40	.42	.66	1.08	.17	.20	.88	0.00
	GVW	1.3	3.6	5.8	21.0	16.1	28.9	40.0	28.4	42.2	70.1	34.9	33.5	59.3	0.0
N	Num	3	1,321	798	19	73	11	1	13	58	49	1	1	27	0
	Flex	.00	.00	.00	.30	.14	.42	.20	.46	.50	.54	.26	1.31	.47	0.00
	Rigid	.00	.00	.00	.34	.15	.67	.50	.57	.87	1.21	.24	1.50	.80	0.00
	GVW	1.0	3.7	5.8	20.9	16.5	29.9	41.0	29.9	43.0	69.1	36.1	44.3	53.0	0.0
S	Num	1	1,378	886	17	42	12	2	12	76	39	2	1	27	0
	Flex	.00	.00	.00	.19	.09	.29	.16	.14	.32	.40	.14	.08	.62	0.00
	Rigid	.00	.00	.00	.22	.09	.43	.37	.16	.49	.91	.14	.08	.96	0.00
	GVW	2.0	3.5	5.8	20.9	15.6	29.3	38.6	25.4	41.5	70.7	33.8	33.8	65.9	0.0
N Lane1	Num	3	1,321	798	19	73	11	1	13	58	49	1	1	27	0
	Flex	.00	.00	.00	.30	.14	.42	.20	.46	.50	.54	.26	1.31	.47	0.00
	Rigid	.00	.00	.00	.34	.15	.67	.50	.57	.87	1.21	.24	1.50	.80	0.00
	GVW	1.0	3.7	5.8	20.9	16.5	29.9	41.0	29.9	43.0	69.1	36.1	44.3	53.0	0.0
S Lane1	Num	1	1,378	886	17	42	12	2	12	76	39	2	1	27	0
	Flex	.00	.00	.00	.19	.09	.29	.16	.14	.32	.40	.14	.08	.62	0.00
	Rigid	.00	.00	.00	.22	.09	.43	.37	.16	.49	.91	.14	.08	.96	0.00
	GVW	2.0	3.5	5.8	20.9	15.6	29.3	38.6	25.4	41.5	70.7	33.8	33.8	65.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2019

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9