

Idaho Transportation Department

Monthly WIM Distribution for Feb-2019

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	2,564	1,684	41	100	24	1	25	119	76	1	1	42	0
	Flex	.00	.00	.00	.33	.12	.42	.17	.59	.35	.54	.16	.10	.51	0.00
	Rigid	.00	.00	.00	.43	.12	.64	.32	.81	.60	1.24	.15	.11	.92	0.00
	GVW	1.2	3.6	5.8	24.5	16.3	30.3	38.2	29.6	41.4	71.8	33.6	37.4	58.9	0.0
N	Num	3	1,284	815	20	59	12	1	13	49	41	1	1	19	0
	Flex	.00	.00	.00	.44	.14	.53	.23	.82	.48	.66	.33	.07	.59	0.00
	Rigid	.00	.00	.00	.57	.15	.81	.56	1.12	.87	1.54	.31	.09	1.16	0.00
	GVW	1.2	3.7	5.8	25.5	17.0	32.1	42.6	32.7	43.2	73.7	37.3	33.8	59.1	0.0
S	Num	0	1,280	868	21	41	12	1	12	71	36	1	1	24	0
	Flex	0.00	.00	.00	.23	.09	.36	.14	.11	.26	.41	.12	.10	.45	0.00
	Rigid	0.00	.00	.00	.29	.09	.55	.28	.12	.41	.90	.12	.10	.71	0.00
	GVW	0.0	3.5	5.8	23.7	15.4	29.9	37.7	23.8	40.2	69.3	33.1	37.6	58.6	0.0
N Lane1	Num	3	1,284	815	20	59	12	1	13	49	41	1	1	19	0
	Flex	.00	.00	.00	.44	.14	.53	.23	.82	.48	.66	.33	.07	.59	0.00
	Rigid	.00	.00	.00	.57	.15	.81	.56	1.12	.87	1.54	.31	.09	1.16	0.00
	GVW	1.2	3.7	5.8	25.5	17.0	32.1	42.6	32.7	43.2	73.7	37.3	33.8	59.1	0.0
S Lane1	Num	0	1,280	868	21	41	12	1	12	71	36	1	1	24	0
	Flex	0.00	.00	.00	.23	.09	.36	.14	.11	.26	.41	.12	.10	.45	0.00
	Rigid	0.00	.00	.00	.29	.09	.55	.28	.12	.41	.90	.12	.10	.71	0.00
	GVW	0.0	3.5	5.8	23.7	15.4	29.9	37.7	23.8	40.2	69.3	33.1	37.6	58.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2019

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9