

Idaho Transportation Department

Monthly WIM Distribution for Jun-2019

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	12	3,505	2,421	43	159	36	5	36	197	143	2	2	95	0
	Flex	.00	.00	.00	.24	.10	.36	.31	.22	.42	.49	.28	.09	.61	0.00
	Rigid	.00	.00	.00	.28	.10	.54	.55	.26	.73	1.12	.26	.10	1.20	0.00
	GVW	1.6	3.4	5.9	20.2	16.2	29.4	43.8	28.2	42.8	65.7	36.1	36.2	69.8	0.0
N	Num	6	1,766	1,219	23	77	17	2	15	95	81	2	1	47	0
	Flex	.00	.00	.00	.24	.10	.39	.27	.30	.52	.48	.34	.15	.48	0.00
	Rigid	.00	.00	.00	.29	.10	.61	.44	.39	.97	1.16	.32	.17	1.07	0.00
	GVW	1.5	3.4	5.8	20.0	16.3	29.6	42.4	28.8	44.7	67.1	39.6	32.8	64.3	0.0
S	Num	6	1,739	1,202	20	82	19	4	21	101	61	2	1	47	0
	Flex	.00	.00	.00	.23	.11	.32	.33	.16	.33	.48	.14	.08	.75	0.00
	Rigid	.00	.00	.00	.26	.10	.49	.59	.17	.52	1.02	.13	.08	1.30	0.00
	GVW	1.6	3.5	6.0	20.2	16.2	29.1	44.3	27.8	41.4	62.8	31.8	36.8	73.7	0.0
N Lane1	Num	6	1,766	1,219	23	77	17	2	15	95	81	2	1	47	0
	Flex	.00	.00	.00	.24	.10	.39	.27	.30	.52	.48	.34	.15	.48	0.00
	Rigid	.00	.00	.00	.29	.10	.61	.44	.39	.97	1.16	.32	.17	1.07	0.00
	GVW	1.5	3.4	5.8	20.0	16.3	29.6	42.4	28.8	44.7	67.1	39.6	32.8	64.3	0.0
S Lane1	Num	6	1,739	1,202	20	82	19	4	21	101	61	2	1	47	0
	Flex	.00	.00	.00	.23	.11	.32	.33	.16	.33	.48	.14	.08	.75	0.00
	Rigid	.00	.00	.00	.26	.10	.49	.59	.17	.52	1.02	.13	.08	1.30	0.00
	GVW	1.6	3.5	6.0	20.2	16.2	29.1	44.3	27.8	41.4	62.8	31.8	36.8	73.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2019

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9