

Idaho Transportation Department

Monthly WIM Distribution for Aug-2019

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	14	3,483	2,062	48	246	57	8	44	166	78	2	2	83	0
	Flex	.00	.00	.00	.66	.36	.46	.21	.72	.41	.41	.50	.47	.83	0.00
	Rigid	.00	.00	.00	.77	.42	.80	.53	.86	.71	.95	.48	.53	1.28	0.00
	GVW	2.0	3.8	6.1	20.5	17.2	30.1	42.1	27.5	41.3	61.2	38.9	41.9	66.0	0.0
N	Num	8	1,683	834	28	162	25	5	22	67	40	1	2	31	0
	Flex	.00	.00	.00	.95	.57	.41	.49	1.11	.52	.43	.33	.95	.53	0.00
	Rigid	.00	.00	.00	1.12	.69	.68	1.14	1.35	.94	1.02	.32	1.10	.96	0.00
	GVW	2.4	4.0	6.0	20.4	18.1	26.8	45.0	26.6	40.1	55.7	32.8	48.5	52.7	0.0
S	Num	6	1,799	1,228	19	84	33	5	22	99	38	1	1	52	0
	Flex	.00	.00	.00	.22	.11	.48	.17	.19	.35	.39	.44	.09	1.02	0.00
	Rigid	.00	.00	.00	.24	.12	.87	.43	.21	.55	.89	.42	.10	1.53	0.00
	GVW	1.8	3.5	6.1	20.5	16.3	32.2	42.6	28.0	41.6	66.0	39.8	37.8	74.7	0.0
N Lane1	Num	8	1,683	834	28	162	25	5	22	67	40	1	2	31	0
	Flex	.00	.00	.00	.95	.57	.41	.49	1.11	.52	.43	.33	.95	.53	0.00
	Rigid	.00	.00	.00	1.12	.69	.68	1.14	1.35	.94	1.02	.32	1.10	.96	0.00
	GVW	2.4	4.0	6.0	20.4	18.1	26.8	45.0	26.6	40.1	55.7	32.8	48.5	52.7	0.0
S Lane1	Num	6	1,799	1,228	19	84	33	5	22	99	38	1	1	52	0
	Flex	.00	.00	.00	.22	.11	.48	.17	.19	.35	.39	.44	.09	1.02	0.00
	Rigid	.00	.00	.00	.24	.12	.87	.43	.21	.55	.89	.42	.10	1.53	0.00
	GVW	1.8	3.5	6.1	20.5	16.3	32.2	42.6	28.0	41.6	66.0	39.8	37.8	74.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Aug-2019

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9