

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2019

Site names: 00129  
 County: Jerome  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	12	3,143	1,727	68	310	112	7	54	146	73	2	2	62	0
	Flex	.00	.00	.00	1.07	.24	.91	.18	1.05	.55	.58	1.21	.76	.91	0.00
	Rigid	.00	.00	.00	1.28	.29	1.74	.58	1.27	.89	1.28	1.31	.99	1.43	0.00
	GVW	3.8	4.0	6.3	23.1	16.6	36.9	43.3	30.2	43.5	66.5	43.8	42.6	71.5	0.0
N	Num	9	1,390	544	47	223	39	6	29	56	31	1	1	8	0
	Flex	.00	.00	.01	1.39	.32	.63	.30	1.74	.82	.60	1.72	1.25	.71	0.00
	Rigid	.01	.00	.01	1.67	.39	.98	.95	2.13	1.30	1.25	1.98	1.55	1.34	0.00
	GVW	4.4	4.7	6.6	23.8	16.9	27.9	43.4	31.5	43.1	55.5	41.9	47.9	58.3	0.0
S	Num	4	1,753	1,182	21	87	73	3	26	90	42	1	1	54	0
	Flex	.00	.00	.00	.24	.11	1.01	.15	.20	.40	.57	.68	.17	.96	0.00
	Rigid	.00	.00	.00	.28	.11	2.05	.50	.21	.66	1.29	.67	.18	1.47	0.00
	GVW	2.4	3.5	6.2	21.3	16.7	40.5	45.1	28.9	43.7	73.6	43.0	38.3	74.0	0.0
N Lane1	Num	9	1,390	544	47	223	39	6	29	56	31	1	1	8	0
	Flex	.00	.00	.01	1.39	.32	.63	.30	1.74	.82	.60	1.72	1.25	.71	0.00
	Rigid	.01	.00	.01	1.67	.39	.98	.95	2.13	1.30	1.25	1.98	1.55	1.34	0.00
	GVW	4.4	4.7	6.6	23.8	16.9	27.9	43.4	31.5	43.1	55.5	41.9	47.9	58.3	0.0
S Lane1	Num	4	1,753	1,182	21	87	73	3	26	90	42	1	1	54	0
	Flex	.00	.00	.00	.24	.11	1.01	.15	.20	.40	.57	.68	.17	.96	0.00
	Rigid	.00	.00	.00	.28	.11	2.05	.50	.21	.66	1.29	.67	.18	1.47	0.00
	GVW	2.4	3.5	6.2	21.3	16.7	40.5	45.1	28.9	43.7	73.6	43.0	38.3	74.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2019

Site names: 00129  
 County: Jerome  
 Funct Class: R Principal Arterial - Other  
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9