

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2015

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	3,124	1,630	19	137	26	2	17	81	20	0	1	5	0
	Flex	.00	.00	.00	.56	.26	.62	.85	.43	.82	.69	0.00	3.34	.62	0.00
	Rigid	.00	.00	.00	.61	.27	1.00	1.42	.49	1.46	1.62	0.00	3.47	1.46	0.00
	GVW	5.5	3.2	6.1	23.7	17.0	33.6	55.9	29.6	52.8	76.9	0.0	85.0	75.0	0.0
E	Num	1	1,595	836	9	66	14	1	9	40	13	0	0	4	0
	Flex	.00	.00	.00	.52	.35	.82	.70	.34	.94	.77	0.00	0.00	.47	0.00
	Rigid	.00	.00	.00	.57	.37	1.35	.97	.40	1.70	1.87	0.00	0.00	1.22	0.00
	GVW	5.7	3.1	6.0	22.9	17.5	37.5	50.9	29.1	55.6	84.3	0.0	0.0	67.1	0.0
W	Num	2	1,530	794	9	71	12	2	9	41	7	0	1	2	0
	Flex	.00	.00	.00	.60	.19	.52	1.05	.60	.71	.53	0.00	3.34	.92	0.00
	Rigid	.00	.00	.00	.65	.19	.82	1.79	.68	1.23	1.07	0.00	3.47	1.96	0.00
	GVW	5.1	3.3	6.2	24.3	16.6	30.5	59.1	31.7	50.5	58.7	0.0	85.0	88.1	0.0
E Lane1	Num	1	1,595	836	9	66	14	1	9	40	13	0	0	4	0
	Flex	.00	.00	.00	.52	.35	.82	.70	.34	.94	.77	0.00	0.00	.47	0.00
	Rigid	.00	.00	.00	.57	.37	1.35	.97	.40	1.70	1.87	0.00	0.00	1.22	0.00
	GVW	5.7	3.1	6.0	22.9	17.5	37.5	50.9	29.1	55.6	84.3	0.0	0.0	67.1	0.0
W Lane1	Num	2	1,530	794	9	71	12	2	9	41	7	0	1	2	0
	Flex	.00	.00	.00	.60	.19	.52	1.05	.60	.71	.53	0.00	3.34	.92	0.00
	Rigid	.00	.00	.00	.65	.19	.82	1.79	.68	1.23	1.07	0.00	3.47	1.96	0.00
	GVW	5.1	3.3	6.2	24.3	16.6	30.5	59.1	31.7	50.5	58.7	0.0	85.0	88.1	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2015

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9