

Idaho Transportation Department

Monthly WIM Distribution for Apr-2015

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	7	3,014	1,688	22	166	31	2	18	76	13	1	1	4	0
	Flex	.00	.00	.00	.71	.21	.51	.55	.42	.76	.67	.39	.38	1.21	0.00
	Rigid	.00	.00	.00	.76	.21	.85	1.32	.48	1.34	1.51	.37	.42	2.28	0.00
	GVW	4.7	3.2	6.1	24.6	17.6	31.2	55.1	28.5	52.5	72.9	45.9	53.9	85.1	0.0
E	Num	4	1,532	873	9	70	15	2	10	35	8	1	1	3	0
	Flex	.00	.00	.00	.41	.20	.46	.32	.27	.85	.75	.39	.38	.82	0.00
	Rigid	.00	.00	.00	.44	.21	.73	.87	.31	1.53	1.78	.37	.42	1.84	0.00
	GVW	4.9	3.1	6.0	21.1	16.8	31.1	50.2	26.7	55.6	80.4	45.9	53.9	78.2	0.0
W	Num	3	1,482	815	13	96	16	1	9	41	5	0	0	2	0
	Flex	.00	.00	.00	.87	.21	.55	.66	.58	.67	.52	0.00	0.00	2.42	0.00
	Rigid	.00	.00	.00	.93	.22	.94	1.48	.67	1.18	.98	0.00	0.00	3.59	0.00
	GVW	4.1	3.4	6.3	26.0	18.1	31.0	56.6	30.2	49.9	55.6	0.0	0.0	98.4	0.0
E Lane1	Num	4	1,532	873	9	70	15	2	10	35	8	1	1	3	0
	Flex	.00	.00	.00	.41	.20	.46	.32	.27	.85	.75	.39	.38	.82	0.00
	Rigid	.00	.00	.00	.44	.21	.73	.87	.31	1.53	1.78	.37	.42	1.84	0.00
	GVW	4.9	3.1	6.0	21.1	16.8	31.1	50.2	26.7	55.6	80.4	45.9	53.9	78.2	0.0
W Lane1	Num	3	1,482	815	13	96	16	1	9	41	5	0	0	2	0
	Flex	.00	.00	.00	.87	.21	.55	.66	.58	.67	.52	0.00	0.00	2.42	0.00
	Rigid	.00	.00	.00	.93	.22	.94	1.48	.67	1.18	.98	0.00	0.00	3.59	0.00
	GVW	4.1	3.4	6.3	26.0	18.1	31.0	56.6	30.2	49.9	55.6	0.0	0.0	98.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2015

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9