

Idaho Transportation Department

Monthly WIM Distribution for Feb-2017

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	2,469	1,537	17	195	16	1	16	68	27	0	1	10	0
	Flex	.00	.00	.00	.49	.14	.53	.51	.39	.73	.98	0.00	1.28	1.20	0.00
	Rigid	.00	.00	.00	.53	.15	.85	1.49	.43	1.28	2.20	0.00	1.55	2.06	0.00
	GVW	3.0	3.4	6.0	22.3	14.4	30.6	57.9	27.6	48.6	78.4	0.0	78.7	70.5	0.0
E	Num	1	1,094	744	9	110	8	1	9	35	16	0	1	6	0
	Flex	.00	.00	.00	.60	.16	.79	.59	.43	.97	1.13	0.00	1.28	1.11	0.00
	Rigid	.00	.00	.00	.66	.17	1.30	2.24	.45	1.69	2.49	0.00	1.55	1.88	0.00
	GVW	2.5	3.3	5.9	23.5	14.8	34.8	67.6	27.9	52.6	80.5	0.0	78.7	62.9	0.0
W	Num	2	1,375	864	8	90	8	1	9	36	12	0	0	5	0
	Flex	.00	.00	.00	.43	.13	.29	.38	.37	.58	.79	0.00	0.00	1.12	0.00
	Rigid	.00	.00	.00	.47	.13	.42	.73	.43	1.04	1.85	0.00	0.00	2.03	0.00
	GVW	3.1	3.5	6.3	21.5	14.1	26.9	46.0	29.3	46.4	75.8	0.0	0.0	75.7	0.0
E Lane1	Num	1	1,094	744	9	110	8	1	9	35	16	0	1	6	0
	Flex	.00	.00	.00	.60	.16	.79	.59	.43	.97	1.13	0.00	1.28	1.11	0.00
	Rigid	.00	.00	.00	.66	.17	1.30	2.24	.45	1.69	2.49	0.00	1.55	1.88	0.00
	GVW	2.5	3.3	5.9	23.5	14.8	34.8	67.6	27.9	52.6	80.5	0.0	78.7	62.9	0.0
W Lane1	Num	2	1,375	864	8	90	8	1	9	36	12	0	0	5	0
	Flex	.00	.00	.00	.43	.13	.29	.38	.37	.58	.79	0.00	0.00	1.12	0.00
	Rigid	.00	.00	.00	.47	.13	.42	.73	.43	1.04	1.85	0.00	0.00	2.03	0.00
	GVW	3.1	3.5	6.3	21.5	14.1	26.9	46.0	29.3	46.4	75.8	0.0	0.0	75.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2017

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9