

Idaho Transportation Department

Monthly WIM Distribution for Mar-2017

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	3,852	2,271	20	264	25	2	23	89	36	1	1	18	0
	Flex	.00	.00	.00	.60	.15	.54	.46	.41	.84	.94	.07	4.93	1.34	0.00
	Rigid	.00	.00	.00	.65	.15	.88	1.55	.47	1.47	2.23	.07	5.86	2.39	0.00
	GVW	2.7	3.4	6.2	24.0	15.4	31.5	58.4	29.9	51.4	81.5	21.1	91.6	72.9	0.0
E	Num	1	1,807	1,132	9	136	12	2	13	42	18	0	1	10	0
	Flex	.00	.00	.00	.47	.15	.77	.41	.44	1.03	1.23	0.00	.97	.93	0.00
	Rigid	.00	.00	.00	.49	.16	1.27	1.52	.51	1.79	2.95	0.00	1.02	1.72	0.00
	GVW	.6	3.3	6.1	22.6	15.3	35.1	63.1	30.1	53.8	91.9	0.0	66.9	60.2	0.0
W	Num	2	2,045	1,139	11	128	13	1	13	47	17	1	1	8	0
	Flex	.00	.00	.00	.68	.14	.32	.39	.40	.66	.65	.07	8.89	1.91	0.00
	Rigid	.00	.00	.00	.75	.14	.51	1.23	.48	1.18	1.52	.07	10.70	3.28	0.00
	GVW	4.0	3.5	6.3	24.8	15.6	27.9	49.4	29.4	49.2	70.4	21.1	116.3	91.0	0.0
E Lane1	Num	1	1,807	1,132	9	136	12	2	13	42	18	0	1	10	0
	Flex	.00	.00	.00	.47	.15	.77	.41	.44	1.03	1.23	0.00	.97	.93	0.00
	Rigid	.00	.00	.00	.49	.16	1.27	1.52	.51	1.79	2.95	0.00	1.02	1.72	0.00
	GVW	.6	3.3	6.1	22.6	15.3	35.1	63.1	30.1	53.8	91.9	0.0	66.9	60.2	0.0
W Lane1	Num	2	2,045	1,139	11	128	13	1	13	47	17	1	1	8	0
	Flex	.00	.00	.00	.68	.14	.32	.39	.40	.66	.65	.07	8.89	1.91	0.00
	Rigid	.00	.00	.00	.75	.14	.51	1.23	.48	1.18	1.52	.07	10.70	3.28	0.00
	GVW	4.0	3.5	6.3	24.8	15.6	27.9	49.4	29.4	49.2	70.4	21.1	116.3	91.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2017

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9