

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2017

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,691	1,296	14	88	27	2	18	69	21	1	1	27	0
	Flex	.00	.00	.00	.28	.15	.37	.22	.19	.42	.35	.99	.00	.63	0.00
	Rigid	.00	.00	.00	.31	.15	.66	.58	.24	.76	.80	.95	.01	.97	0.00
	GVW	1.9	2.8	5.1	19.8	15.5	26.4	45.5	23.5	39.0	50.2	46.0	18.6	51.1	0.0
E	Num	2	689	614	6	36	12	1	10	34	11	1	1	13	0
	Flex	.00	.00	.00	.30	.15	.48	.31	.20	.52	.40	.17	.00	.72	0.00
	Rigid	.00	.00	.00	.31	.15	.78	1.02	.24	.93	.93	.16	.01	1.08	0.00
	GVW	1.2	2.7	4.9	19.9	15.9	25.9	53.0	24.9	38.5	50.7	27.2	18.6	53.9	0.0
W	Num	2	1,048	733	8	52	16	1	8	37	10	1	0	14	0
	Flex	.00	.00	.00	.25	.14	.36	.19	.18	.35	.27	1.02	0.00	.73	0.00
	Rigid	.00	.00	.00	.29	.15	.68	.51	.23	.63	.61	.98	0.00	1.15	0.00
	GVW	3.1	2.9	5.3	19.4	15.4	27.7	43.1	22.7	39.6	48.3	48.2	0.0	52.6	0.0
E Lane1	Num	2	689	614	6	36	12	1	10	34	11	1	1	13	0
	Flex	.00	.00	.00	.30	.15	.48	.31	.20	.52	.40	.17	.00	.72	0.00
	Rigid	.00	.00	.00	.31	.15	.78	1.02	.24	.93	.93	.16	.01	1.08	0.00
	GVW	1.2	2.7	4.9	19.9	15.9	25.9	53.0	24.9	38.5	50.7	27.2	18.6	53.9	0.0
W Lane1	Num	2	1,048	733	8	52	16	1	8	37	10	1	0	14	0
	Flex	.00	.00	.00	.25	.14	.36	.19	.18	.35	.27	1.02	0.00	.73	0.00
	Rigid	.00	.00	.00	.29	.15	.68	.51	.23	.63	.61	.98	0.00	1.15	0.00
	GVW	3.1	2.9	5.3	19.4	15.4	27.7	43.1	22.7	39.6	48.3	48.2	0.0	52.6	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2017

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9