

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2017

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	2,281	1,754	18	105	24	2	18	86	34	2	1	25	0
	Flex	.00	.00	.00	.39	.16	.35	.30	.29	.39	.34	.84	.18	.57	0.00
	Rigid	.00	.00	.00	.46	.16	.58	.82	.36	.68	.80	.80	.18	.94	0.00
	GVW	2.4	3.1	5.5	22.4	15.7	25.8	45.9	24.4	39.8	51.7	51.6	30.8	52.4	0.0
E	Num	2	864	800	8	41	11	1	10	39	16	1	1	13	0
	Flex	.00	.00	.00	.33	.11	.40	.45	.29	.39	.30	.78	.10	.35	0.00
	Rigid	.00	.00	.00	.40	.11	.64	1.06	.34	.68	.76	.75	.10	.61	0.00
	GVW	1.3	2.8	4.9	20.8	15.7	25.4	45.5	25.5	37.5	55.0	48.8	29.7	44.7	0.0
W	Num	2	1,417	954	10	64	13	2	8	47	18	1	1	12	0
	Flex	.00	.00	.00	.40	.19	.30	.18	.37	.38	.39	.54	.49	.88	0.00
	Rigid	.00	.00	.00	.46	.20	.55	.62	.46	.68	.87	.51	.49	1.42	0.00
	GVW	3.6	3.3	5.9	22.5	15.7	26.1	46.1	25.1	41.5	48.7	49.1	44.3	63.6	0.0
E Lane1	Num	2	864	800	8	41	11	1	10	39	16	1	1	13	0
	Flex	.00	.00	.00	.33	.11	.40	.45	.29	.39	.30	.78	.10	.35	0.00
	Rigid	.00	.00	.00	.40	.11	.64	1.06	.34	.68	.76	.75	.10	.61	0.00
	GVW	1.3	2.8	4.9	20.8	15.7	25.4	45.5	25.5	37.5	55.0	48.8	29.7	44.7	0.0
W Lane1	Num	2	1,417	954	10	64	13	2	8	47	18	1	1	12	0
	Flex	.00	.00	.00	.40	.19	.30	.18	.37	.38	.39	.54	.49	.88	0.00
	Rigid	.00	.00	.00	.46	.20	.55	.62	.46	.68	.87	.51	.49	1.42	0.00
	GVW	3.6	3.3	5.9	22.5	15.7	26.1	46.1	25.1	41.5	48.7	49.1	44.3	63.6	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2017

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9