

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2017

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	2,725	1,800	19	114	32	2	19	80	18	1	1	13	0
	Flex	.00	.00	.00	.36	.12	.30	.19	.33	.45	.36	1.00	.80	.79	0.00
	Rigid	.00	.00	.00	.38	.12	.51	.68	.39	.79	.82	.95	.82	1.40	0.00
	GVW	1.6	3.2	5.7	21.0	15.9	26.8	46.3	26.4	43.8	56.9	53.5	52.7	66.4	0.0
E	Num	2	1,204	892	9	41	17	1	10	37	9	1	1	8	0
	Flex	.00	.00	.00	.20	.09	.18	.15	.14	.39	.30	1.29	.08	.28	0.00
	Rigid	.00	.00	.00	.22	.09	.30	.59	.17	.71	.73	1.22	.08	.47	0.00
	GVW	1.1	2.9	5.1	18.9	15.5	23.3	38.3	23.5	41.1	56.6	61.4	32.6	45.8	0.0
W	Num	3	1,521	908	11	73	17	1	9	43	9	1	1	6	0
	Flex	.00	.00	.00	.47	.13	.39	.17	.57	.49	.42	.58	1.24	1.30	0.00
	Rigid	.00	.00	.00	.50	.14	.70	.57	.65	.84	.91	.56	1.26	2.20	0.00
	GVW	2.3	3.4	6.2	22.6	16.0	29.2	46.8	29.9	45.7	55.3	43.8	62.2	82.6	0.0
E Lane1	Num	2	1,204	892	9	41	17	1	10	37	9	1	1	8	0
	Flex	.00	.00	.00	.20	.09	.18	.15	.14	.39	.30	1.29	.08	.28	0.00
	Rigid	.00	.00	.00	.22	.09	.30	.59	.17	.71	.73	1.22	.08	.47	0.00
	GVW	1.1	2.9	5.1	18.9	15.5	23.3	38.3	23.5	41.1	56.6	61.4	32.6	45.8	0.0
W Lane1	Num	3	1,521	908	11	73	17	1	9	43	9	1	1	6	0
	Flex	.00	.00	.00	.47	.13	.39	.17	.57	.49	.42	.58	1.24	1.30	0.00
	Rigid	.00	.00	.00	.50	.14	.70	.57	.65	.84	.91	.56	1.26	2.20	0.00
	GVW	2.3	3.4	6.2	22.6	16.0	29.2	46.8	29.9	45.7	55.3	43.8	62.2	82.6	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2017

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9