

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2017

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	3,045	1,876	21	96	33	1	22	87	28	0	1	7	0
	Flex	.00	.00	.00	.35	.13	.21	.29	.25	.29	.19	0.00	1.28	.59	0.00
	Rigid	.00	.00	.00	.38	.13	.32	.49	.29	.48	.40	0.00	1.34	1.09	0.00
	GVW	1.6	3.1	5.5	20.5	15.8	24.7	39.9	26.5	40.9	49.9	0.0	59.9	67.8	0.0
E	Num	2	1,550	1,002	10	33	16	1	10	41	15	0	1	4	0
	Flex	.00	.00	.00	.08	.06	.08	.09	.07	.15	.14	0.00	.07	.25	0.00
	Rigid	.00	.00	.00	.09	.06	.12	.12	.08	.26	.31	0.00	.07	.41	0.00
	GVW	1.5	2.8	5.0	15.5	14.9	20.6	30.2	20.9	36.7	49.8	0.0	32.1	57.2	0.0
W	Num	2	1,495	874	11	63	18	1	12	46	13	0	1	3	0
	Flex	.00	.00	.00	.57	.17	.31	.61	.41	.41	.27	0.00	1.75	1.15	0.00
	Rigid	.00	.00	.00	.63	.16	.48	1.18	.48	.67	.54	0.00	1.84	2.10	0.00
	GVW	1.5	3.4	6.1	24.8	16.2	27.9	57.6	31.4	44.4	51.7	0.0	68.1	84.6	0.0
E Lane1	Num	2	1,550	1,002	10	33	16	1	10	41	15	0	1	4	0
	Flex	.00	.00	.00	.08	.06	.08	.09	.07	.15	.14	0.00	.07	.25	0.00
	Rigid	.00	.00	.00	.09	.06	.12	.12	.08	.26	.31	0.00	.07	.41	0.00
	GVW	1.5	2.8	5.0	15.5	14.9	20.6	30.2	20.9	36.7	49.8	0.0	32.1	57.2	0.0
W Lane1	Num	2	1,495	874	11	63	18	1	12	46	13	0	1	3	0
	Flex	.00	.00	.00	.57	.17	.31	.61	.41	.41	.27	0.00	1.75	1.15	0.00
	Rigid	.00	.00	.00	.63	.16	.48	1.18	.48	.67	.54	0.00	1.84	2.10	0.00
	GVW	1.5	3.4	6.1	24.8	16.2	27.9	57.6	31.4	44.4	51.7	0.0	68.1	84.6	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2017

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9