

Idaho Transportation Department

Monthly WIM Distribution for Nov-2017

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	2,851	1,739	17	80	33	1	21	82	59	2	1	9	0
	Flex	.00	.00	.00	.24	.15	.25	.24	.16	.31	.19	.44	.51	.43	0.00
	Rigid	.00	.00	.00	.24	.15	.39	.70	.17	.53	.41	.41	.53	.71	0.00
	GVW	3.0	3.1	5.4	18.5	16.0	25.0	46.6	24.1	42.1	52.2	44.1	32.7	58.5	0.0
E	Num	2	1,444	923	8	26	17	1	9	42	30	1	1	6	0
	Flex	.00	.00	.00	.07	.09	.10	.08	.06	.15	.15	.72	.03	.23	0.00
	Rigid	.00	.00	.00	.07	.09	.15	.15	.06	.26	.33	.67	.03	.35	0.00
	GVW	2.5	2.8	4.9	14.6	15.4	21.4	33.0	19.5	37.3	52.4	53.4	20.2	51.9	0.0
W	Num	2	1,406	815	11	54	16	1	13	40	34	1	1	4	0
	Flex	.00	.00	.00	.39	.18	.40	.36	.26	.47	.26	.16	1.93	.85	0.00
	Rigid	.00	.00	.00	.41	.18	.64	.99	.29	.81	.51	.15	2.00	1.45	0.00
	GVW	3.0	3.4	6.0	22.5	16.2	28.8	53.6	27.9	46.8	49.1	34.8	66.2	69.5	0.0
E Lane1	Num	2	1,444	923	8	26	17	1	9	42	30	1	1	6	0
	Flex	.00	.00	.00	.07	.09	.10	.08	.06	.15	.15	.72	.03	.23	0.00
	Rigid	.00	.00	.00	.07	.09	.15	.15	.06	.26	.33	.67	.03	.35	0.00
	GVW	2.5	2.8	4.9	14.6	15.4	21.4	33.0	19.5	37.3	52.4	53.4	20.2	51.9	0.0
W Lane1	Num	2	1,406	815	11	54	16	1	13	40	34	1	1	4	0
	Flex	.00	.00	.00	.39	.18	.40	.36	.26	.47	.26	.16	1.93	.85	0.00
	Rigid	.00	.00	.00	.41	.18	.64	.99	.29	.81	.51	.15	2.00	1.45	0.00
	GVW	3.0	3.4	6.0	22.5	16.2	28.8	53.6	27.9	46.8	49.1	34.8	66.2	69.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2017

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9