

Idaho Transportation Department

Monthly WIM Distribution for Jan-2020

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	3,004	1,836	20	128	20	2	15	78	20	0	1	19	0
	Flex	.00	.00	.00	.23	.12	.40	.17	.25	.48	.60	0.00	.16	.72	0.00
	Rigid	.00	.00	.00	.25	.12	.56	.33	.26	.82	1.28	0.00	.17	1.12	0.00
	GVW	1.9	3.6	5.9	20.5	14.7	29.0	38.2	27.8	45.8	67.5	0.0	37.6	62.1	0.0
E	Num	1	1,530	945	9	94	10	2	9	37	11	0	1	10	0
	Flex	.00	.00	.00	.31	.12	.62	.23	.36	.72	.85	0.00	.16	.68	0.00
	Rigid	.00	.00	.00	.34	.13	.87	.45	.38	1.20	1.88	0.00	.16	1.17	0.00
	GVW	2.7	4.1	6.6	22.1	14.6	34.6	39.4	30.9	52.5	81.0	0.0	31.6	55.3	0.0
W	Num	1	1,474	891	11	34	11	1	7	41	9	0	1	9	0
	Flex	.00	.00	.00	.16	.09	.22	.10	.19	.27	.32	0.00	.13	.70	0.00
	Rigid	.00	.00	.00	.16	.09	.28	.19	.21	.46	.62	0.00	.14	1.01	0.00
	GVW	1.6	3.0	5.3	18.9	15.2	24.3	37.3	26.5	39.6	52.3	0.0	39.6	68.5	0.0
E Lane1	Num	1	1,530	945	9	94	10	2	9	37	11	0	1	10	0
	Flex	.00	.00	.00	.31	.12	.62	.23	.36	.72	.85	0.00	.16	.68	0.00
	Rigid	.00	.00	.00	.34	.13	.87	.45	.38	1.20	1.88	0.00	.16	1.17	0.00
	GVW	2.7	4.1	6.6	22.1	14.6	34.6	39.4	30.9	52.5	81.0	0.0	31.6	55.3	0.0
W Lane1	Num	1	1,474	891	11	34	11	1	7	41	9	0	1	9	0
	Flex	.00	.00	.00	.16	.09	.22	.10	.19	.27	.32	0.00	.13	.70	0.00
	Rigid	.00	.00	.00	.16	.09	.28	.19	.21	.46	.62	0.00	.14	1.01	0.00
	GVW	1.6	3.0	5.3	18.9	15.2	24.3	37.3	26.5	39.6	52.3	0.0	39.6	68.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2020

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9