

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2020

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	2,983	1,782	19	144	17	2	15	76	22	1	1	10	0
	Flex	.00	.00	.00	.24	.11	.36	.62	.23	.47	.53	1.43	.20	.65	0.00
	Rigid	.00	.00	.00	.26	.11	.50	1.08	.27	.80	1.19	1.37	.22	1.06	0.00
	GVW	1.3	3.6	5.9	20.5	14.9	26.7	52.2	28.4	45.8	67.9	61.4	46.0	62.0	0.0
E	Num	1	1,503	912	9	105	10	1	9	34	12	0	0	6	0
	Flex	.00	.00	.00	.28	.11	.61	.71	.26	.71	.82	0.00	0.00	.57	0.00
	Rigid	.00	.00	.00	.31	.11	.86	1.19	.28	1.23	1.89	0.00	0.00	.98	0.00
	GVW	1.2	4.1	6.6	21.6	14.6	34.1	53.5	28.6	52.8	87.9	0.0	0.0	58.0	0.0
W	Num	1	1,480	870	10	40	9	2	6	41	11	1	1	4	0
	Flex	.00	.00	.00	.18	.10	.21	.17	.21	.27	.24	1.43	.20	.79	0.00
	Rigid	.00	.00	.00	.19	.09	.28	.48	.25	.45	.44	1.37	.22	1.21	0.00
	GVW	1.2	3.0	5.3	19.2	16.0	22.8	44.1	28.1	40.2	44.4	61.4	46.0	69.3	0.0
E Lane1	Num	1	1,503	912	9	105	10	1	9	34	12	0	0	6	0
	Flex	.00	.00	.00	.28	.11	.61	.71	.26	.71	.82	0.00	0.00	.57	0.00
	Rigid	.00	.00	.00	.31	.11	.86	1.19	.28	1.23	1.89	0.00	0.00	.98	0.00
	GVW	1.2	4.1	6.6	21.6	14.6	34.1	53.5	28.6	52.8	87.9	0.0	0.0	58.0	0.0
W Lane1	Num	1	1,480	870	10	40	9	2	6	41	11	1	1	4	0
	Flex	.00	.00	.00	.18	.10	.21	.17	.21	.27	.24	1.43	.20	.79	0.00
	Rigid	.00	.00	.00	.19	.09	.28	.48	.25	.45	.44	1.37	.22	1.21	0.00
	GVW	1.2	3.0	5.3	19.2	16.0	22.8	44.1	28.1	40.2	44.4	61.4	46.0	69.3	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2020

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9