

Idaho Transportation Department

Monthly WIM Distribution for Sep-2022

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	5	3,834	1,965	2	68	39	8	45	101	29	9	2	15	0
	Flex	.00	.00	.00	.76	.45	.59	.40	.31	.67	.55	4.55	2.09	1.46	0.00
	Rigid	.00	.00	.00	1.18	.47	.99	1.12	.34	1.24	1.31	4.95	4.27	2.19	0.00
	GVW	1.3	2.4	4.2	33.3	17.7	31.1	48.7	21.9	46.9	58.5	69.1	68.0	68.0	0.0
E	Num	5	1,974	1,016	1	34	22	6	23	50	14	4	1	9	0
	Flex	.00	.00	.00	1.13	.45	.56	.61	.35	.66	.61	.77	1.09	1.05	0.00
	Rigid	.00	.00	.00	1.85	.47	.92	1.43	.38	1.24	1.52	.76	1.33	1.55	0.00
	GVW	.8	2.3	4.1	39.4	18.1	32.4	57.3	21.9	46.6	66.2	44.6	45.7	64.6	0.0
W	Num	2	1,861	948	1	34	17	6	22	51	15	5	1	7	0
	Flex	.00	.00	.01	.69	.45	.64	.33	.28	.67	.49	8.18	2.19	2.10	0.00
	Rigid	.00	.00	.01	1.10	.47	1.11	.99	.31	1.24	1.10	8.97	4.53	3.19	0.00
	GVW	2.4	2.4	4.3	31.6	17.4	29.6	45.2	22.1	47.1	52.2	92.9	73.5	72.6	0.0
E Lane1	Num	5	1,974	1,016	1	34	22	6	23	50	14	4	1	9	0
	Flex	.00	.00	.00	1.13	.45	.56	.61	.35	.66	.61	.77	1.09	1.05	0.00
	Rigid	.00	.00	.00	1.85	.47	.92	1.43	.38	1.24	1.52	.76	1.33	1.55	0.00
	GVW	.8	2.3	4.1	39.4	18.1	32.4	57.3	21.9	46.6	66.2	44.6	45.7	64.6	0.0
W Lane1	Num	2	1,861	948	1	34	17	6	22	51	15	5	1	7	0
	Flex	.00	.00	.01	.69	.45	.64	.33	.28	.67	.49	8.18	2.19	2.10	0.00
	Rigid	.00	.00	.01	1.10	.47	1.11	.99	.31	1.24	1.10	8.97	4.53	3.19	0.00
	GVW	2.4	2.4	4.3	31.6	17.4	29.6	45.2	22.1	47.1	52.2	92.9	73.5	72.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2022

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9